

About

BioClean validated sterile RABS and Isolator Gloves are manufactured from nitrile with incredibly low levels of particles and excellent ESD properties. Designed for precision work when increased grip is required, our GHG series of high grip gloves are fully validated for sterility with an SAL (Sterility Assurance Level) of 10⁻⁶.

Specifications

COMPATIBILITY:

ISO Class 4 & EU GMP Grade A

LENGTH:

840mm/33"

MATERIAL:

Nitrile

PROTEIN LEVEL:

Nitrile contains no natural latex proteins

SURFACE:

Smooth

SHAPE:

5 Finger Ambidextrous Size 9.75

COLOUR:

White

STERILIZATION:

Gamma irradiation

Features

- Tested against ASTM D6978-05 for handling chemo drugs
- Ultra-clean surface ensures product protection
- To fit port size: 10-12" / 254-305mm

BIOCLEAN STERILE NITRILE

High Grip RABS / Isolator Gloves GHG10NIT59

100% INSPECTED AND AIR LEAK TESTED

SUITABLE FOR AUTOCLAVING

CAN BE SANITIZED BY VHP OR IPA

HIGH GRIP

















Quality Standards

- Manufactured in a facility holding ISO 9001:2015 and PPER 2016/425 Module D
- Conforms to Category 3 Complex Design Personal Protective Equipment PPE Regulation (EU)2016/425
- Processed in an NEBB certified ISO Class 4 environment
- Complies with the requirements of Glove Standard EN420:2003+A1:2009, EN374-1:2016, EN374-5:2016 and EN421:2010
- Physical properties comply with European Medical Glove Standard EN455-2:2015
- Tested against permeation standard ASTM D6978-05 for cytotoxic drugs
- Suitable for contact with dry,alcoholic and acidic foodstuffs . Regulation (EC)1935/2004 and (EC) 2023/2006
- Sterilized in accordance with ISO 11137-1:2006
- Mechanical protection EN388:2016
- Complies with the requirements of European Glove Standard EN421
 Protection against particulate radioactive contamination.

Sterilization

Method: Gamma irradiation Minimum Dose: 25kGy Sterility Assurance Level: 10⁻⁶

Shelf Life & Storage

Three (3) years from date of manufacture. Store in a dry, cool place (<40°C) away from direct sunlight and fluorescent light.

Physical Properties

CHARACTERISTICS	VALUE		TEST METHOD
Freedom From Holes	100% Tested		EN 374-2:2016
Glove Length (mm/in)	840/33	Tolerance -10mm/+70mm	EN 420:2003 + A1:2009
Single Wall Thickness (mils/mm)	Cuff: 20/0.50 Palm: 20/0.50 Finger Tip: 24/0.60	-0.10mm/+0.15mm	EN 455-2:2015
Force At Break During Shelf Life	≥ 6N		EN 455-2:2015

PALM WIDTHS (mm) ± 5mm				
SIZE	9.75			
mm	129			
TEST METHOD	EN 420:2003 + A1:2009			





Protection Against Mechanical Risks, EN 388: 2016+A1:2018

Risk	Performance Level	Risk	Performance
Abrasion Resistance	Level 4	Tear resistance	Level 0
Blade cut resistance	Level 1	Puncture resistance	Level 1
TDM: Cut Resistance	Х	Impact Protection	N/A

TO ORDER

GHG10NIT59

Re-order code

Packing

Triple bagged: One piece per sealed inner PE bag; one inner bag per sealed second inner PE bag; one second inner bag per sealed outer PE bag; 20 outer bags per lined inner white Correx polyethylene box (20 pieces).

For additional information visit us at www.bioclean.com, or contact us at;

Size

9.75

Nitritex Ltd

Minton Enterprise Park Oaks Drive Newmarket, Suffolk CB8 7YY United Kingdom Tel: +44 1638 663338 Ansell US

111 Wood Avenue South Suite 210 Iselin, NJ 08830 USA


Tel: +1 800 800 0444

Nitritex (M) Sdn.Bhd

2 Jalan Jurunilai U1/20 Seksyen U1, Hicom Glenmarie Industrial Park 40150 Shah Alam, Selangor Malaysia

Tel: +603 5569 3857/3859

2009/GHG10NIT59/PDS12



*Warning: No glove provides complete protection against all chemicals. Users must test the gloves against the particular chemicals and environment in which they will be used.

**Please see product validation pack or contact Ansell customer service for specific data on use of gloves with cytotoxic drugs. Gloves used for protection against such drugs must be selected specifically for the type of chemicals used.

Ansell, ® and ™ are trademarks owned by Ansell Limited or one of its affiliates. © 2012 – 2020 Ansell Limited. All Rights Reserved.

