

Dual-layer exam gloves offering increased comfort and advanced barrier protection while reducing skin allergy risks

- **Reduced allergy risk:** Manufactured without accelerators, helping to prevent users from Type IV skin allergies
- **Comprehensive protection:** Tested for protection against chemo drugs, fentanyl, and hazardous chemicals, these nitrile gloves deliver exceptional safety
- **Low AQL:** These medical exam gloves' low 0.65 AQL reinforces their barrier integrity
- **Sustained grip:** Textured fingertips and a non-stick/non-foaming composition help medical users and healthcare professionals maintain a strong grip in dry and wet conditions
- **Extended protection:** Our gloves boast an extended cuff over the wrist and lower forearm, protecting workers on the job
- **Enhanced Comfort:** These gloves now ensure increased comfort while maintaining the same high level of protection



Industries

- Life Sciences
- Food Processing
- Healthcare

Recommended For

- Sample taking and processing
- Transferring liquids and solids
- Administering drugs
- Inspection, selecting, checking parts

TECHNICAL DATA SHEET

Product Information	
Material	Nitrile
External Glove Surface	Textured Fingers
Audit Standards	ISO 13485, ISO 9001
Product Certification	Medical Device Regulation (EU) 2017/745 Class I, Personal Protective Equipment Regulation (EU) 2016/425 Category III risks , FDA21 CFR 177-2600-US Food Contact Approved , ASTM D6319, NFPA 1999:2013,EN 455 1-4, EN 16523-1, ASTM D6977, EN ISO 21420:2020, EN ISO 374-1:2016 Type B KPT, EN ISO 374-5:2016 Virus, EN 421:2010, UKCA
Packaging Overview	100 gloves per dispenser 10 dispensers per case 1000 gloves per case
Storage Instructions	Keep out of direct sunlight; store in a cool and dry place. Keep away from sources of ozone or ignition.
Country Of Origin	Malaysia
Product Segmentation	High Risk
Antistatic	Yes EN1149
Silicone Free	No

PHYSICAL PROPERTIES

	Typical Values		Testing Method
	BEFORE AGING	AFTER AGING	
Length (mm/inches)	≥ 280 / 11.0		ASTM D3767,EN 420
Freedom from Holes (Inspection level I)	0.65 AQL		ASTM D5151,EN 374-2
Palm Thickness (mm/mils)	0.14/5.5		ASTM D3767,EN 420
Finger Thickness (mm/mils)	0.21/8.3		ASTM D3767,EN 420
Elongation at Break (%)	≥ 700	≥ 650	ASTM D412
Force at break (N)	≥ 10	≥ 9	EN 455-2

ORDERING INFORMATION

Size	S (6.5 - 7)	M (7.5 - 8)	L (8.5 - 9)	XL (9.5 - 10)	XXL (10.5 - 11)
Product Code	93868070	93868080	93868090	93868100	93868110

Performance Standards and Regulatory Compliance



For additional information visit us at www.ansell.com, or call us at

Europe, Middle East & Africa Region

Ansell Healthcare Europe NV
T: +32 (0) 2 528 74 00
F: +32 (0) 2 528 74 01

Asia Pacific Region

MY: +603 8310 6688
apac.medical@ansell.com
CN: +86 21 38275000
infochina@ansell.com
JP: +813 5549 8151
info.medical.jp@ansell.com

North America Region

Ansell Healthcare Products LLC
T: +1 800 800 0444
F: +1 800 800 0445

Latin America & Caribbean Region

BR: +55 (11) 3356-3100
latam.medical@ansell.com
MX: +52 442 296 2050
latam.medical@ansell.com
CO: +57 1 288 3247
latam.medical@ansell.com

Australia

Ansell Limited
T: +61 1800 337 041
F: +61 1800 803 578

Russia

Ansell PYC
Ten. +7 495 258 13 16

Ansell, ® and ™ are trademarks owned by Ansell Limited or one of its affiliates. US Patented and US and non-US Patents Pending; www.ansell.com/patentmarking © 2025 Ansell Limited. All Rights Reserved.

Neither this document nor any other statement made herein by or on behalf of Ansell should be construed as a warranty of merchantability or that any Ansell product is fit for a particular purpose. Ansell assumes no responsibility for the suitability or adequacy of an end user's selection of gloves for a specific application.

