

Neogard™ TOUCH 73-737

Comfortable neoprene exam gloves, certified for exceptional wet grip

Ultralight, comfortable neoprene exam gloves, recommended for exceptional wet grip

- Elevated comfort: Soft neoprene exam gloves featuring ERGOFORM™ Ergonomic Design Technology for extra comfort and support of musculoskeletal health
- Enhanced grip: Certified by US Ergonomics for enhanced wet grip capabilities*
- Heightened tactile sensitivity: Their thin, ultra-lightweight design offers enhanced tactile sensitivity, for more precise handling of tools and instruments
- Reduced waste: Packed 200 per box to reduce packaging waste

*this product has been certified by United States Ergonomics for exceptional wet grip performance in a variety of wet grip test conditions these included gripping tests involving soap solutions, artificial saliva, artificial blood



Industries

- Healthcare
- Dental
- Veterinary

Recommended For

- Enhanced grip in wet environments
- Environmentally friendly facilities
- Extra comfort during long, sustained procedures
- General dentistry
- Protection from Type I latex allergy in HCW's or patients
- Standard patient examinations



TECHNICAL DATA SHEET

| | Product Information |
|------------------------|----------------------------------------------------------------------------------------------------------|
| External Glove Surface | Textured Fingers |
| Audit Standards | ISO 13485, ISO 9001 |
| Packaging Overview | Case/Carton=2000 gloves/10 Dispensers; Dispenser=200 gloves (XS-L) |
| | Case/Carton=1800 gloves/10 Dispensers; Dispenser=180 gloves (XL) |
| Storage Instructions | Keep out of direct sunlight; store in a cool and dry place. Keep away from sources of ozone or ignition. |
| Country Of Origin | Indonesia |
| Product Segmentation | High Touch |
| Antistatic | Not Tested |

PHYSICAL PROPERTIES

| | Typical Values | | Testing Method | |
|-----------------------------------------|---------------------|-------------|-----------------------|--|
| Length (mm/inches) | 240 , | 9.5 | ASTM D3767,ASTM D6977 | |
| Freedom from Holes (Inspection level I) | 1.5 AQL | | ASTM D5151 | |
| Palm Thickness (mm/mils) | 0.07 | / 2.8 | ASTM D3767,ASTM D6977 | |
| Finger Thickness (mm/mils) | 0.09 | / 3.5 | ASTM D3767,ASTM D6977 | |
| | BEFORE AGING | AFTER AGING | | |
| Ultimate Tensile Strength (MPa) | ≥ 14 | ≥ 14 | ASTM D412 & D573 | |
| Elongation at Break (%) | ≥ 500 | ≥ 400 | ASTM D412 & D573 | |

ORDERING INFORMATION

| Size | XS (5.5 - 6) | S (6.5 - 7) | M (7.5 - 8) | L (8.5 - 9) | XL (9.5 - 10) |
|---------------------|--------------|-------------|-------------|-------------|---------------|
| Product Code | 73737060 | 73737070 | 73737080 | 73737090 | 73737100 |

Performance Standards and Regulatory Compliance







For additional information visit us at www.ansell.com, or call us at

Europe, Middle East & Africa Region Ansell Healthcare Europe NV T: +32 (0) 2 528 74 00 F: +32 (0) 2 528 74 01

Asia Pacific Region MY +603 8310 6688 apac.medical@ansell.com CN: +86 21 38275000 JP: +813 5549 8151

North America Region Ansell Healthcare Products LLC T: +1 800 800 0444 F: +1 800 800 0445

Latin America & Caribbean Region BR +55 (11) 3356-3100 latam.medical@ansell.com MX: +52 442 296 2050 latam.medical@ansell. CO: +57 1 288 3247 latam.medical@ansell.

Ansell Limited T: +61 1800 337 041 F: +61 1800 803 578 Russia

Ansell PYC Ten. +7 495 258 13 16

Technology



Ansell, $^{\textcircled{8}}$ and $^{\textcircled{M}}$ are trademarks owned by Ansell Limited or one of its affiliates. US Patented and US and non-US Patents Pending: www.ansell.com/patentmarking $^{\textcircled{C}}$ 2024 Ansell Limited. All Rights Reserved.

