

Nitrile exam gloves with excellent dexterity along with enhanced comfort, fit and feel

- **Elevated comfort:** These thin, black nitrile medical exam gloves offer enhanced dexterity and tactility in a thin, yet strong design
- **Black nitrile:** Distinctive black color provides contrast while also hiding the appearance of oils, bodily fluids and other stains
- **ERGOFORM™ Technology:** ERGOFORM™ Ergonomic Design Technology reduces muscle strain during repetitive tasks, improving worker comfort and productivity
- **Optimized grip:** Textured on the fingertips for secure handling of instruments and materials



Industries

- Food Service
- Cosmetics
- Tattoo
- Automotive Aftermarket
- Chemical
- Emergency Medical Services
- Healthcare
- Law Enforcement
- Life Sciences
- Dental
- Machinery and Equipment
- Metal fabrication

Recommended For

- General dentistry
- Standard patient examinations
- Emergency services
- Catering/Meal preparation
- General Purpose Auto Aftermarket
- Equipment repair and maintenance
- Laboratory analysis
- Cosmetic Procedures
- Tattoo

TECHNICAL DATA SHEET

	Product Information
Material	Nitrile
External Glove Surface	Textured Fingers
Audit Standards	ISO 13485, ISO 9001
Product Certification	ASTM D6319; Health Canada; ISO 13485; ISO 9001; REACH; ASTM D6978; ISO 10993-5, 10, 23; ASTM F1671; ISO 11737; FDA21 CFR 177-2600-US Food Contact Approved; US QSR/FDA 510(k) Medical Examination Grade
Packaging Overview	Case=1000 gloves/10 dispensers; Dispenser=100 gloves 2XL: Case=900 gloves/10 dispensers; Dispenser=90 gloves
Storage Instructions	Keep out of direct sunlight; store in a cool and dry place. Keep away from sources of ozone or ignition.
Country Of Origin	China
Product Segmentation	High Touch
Antistatic	No
Silicone Free	No

PHYSICAL PROPERTIES

	Typical Values		Testing Method
Length (mm/inches)	240 / 9.4		ASTM D6319,EN 455-2
Freedom from Holes (Inspection level I)	1.5 AQL		ASTM D5151,EN 455-1
Palm Thickness (mm/mils)	0.07 / 2.8		ASTM D6319,EN 455-2
Finger Thickness (mm/mils)	0.10 / 3.9		ASTM D6319,EN 455-2
	BEFORE AGING	AFTER AGING	
Ultimate Tensile Strength (MPa)	≥ 18	≥ 16	ASTM D412 & D573
Elongation at Break (%)	≥ 500	≥ 400	ASTM D412 & D573
Force at break (N)	≥ 6	≥ 6	EN 455

ORDERING INFORMATION

Size	XS (5.5 - 6)	S (6.5 - 7)	M (7.5 - 8)	L (8.5 - 9)	XL (9.5 - 10)	XXL (10.5 - 11)
Product Code	93732060	93732070	93732080	93732090	93732100	93732110

Performance Standards and Regulatory Compliance

CE 0493

MD

EN ISO 374-1:2016
Type B



K P T

EN ISO 374-5



VIRUS

ISO 18889 G1



ISO 18889

ISO 9001



ISO 9001

UK
CA



UK
CA

EN 421



EN 421

ISO 13485



ISO 13485

For additional information visit us at www.ansell.com, or call us at

Europe, Middle East & Africa Region
Ansell Healthcare Europe NV
T: +32 (0) 2 528 74 00
F: +32 (0) 2 528 74 01

Asia Pacific Region
MY: +603 8310 6688
apac.medical@ansell.com
CN: +86 21 38275000
infochina@ansell.com
JP: +813 5549 8151
info.medical.jp@ansell.com

North America Region
Ansell Healthcare Products LLC
T: +1 800 800 0444
F: +1 800 800 0445

Latin America & Caribbean Region
BR: +55 (11) 3356-3100
latam.medical@ansell.com
MX: +52 442 296 2050
latam.medical@ansell.com
CO: +57 1 288 3247
latam.medical@ansell.com

Australia
Ansell Limited
T: +61 1800 337 041
F: +61 1800 803 578

Russia
Ansell PYC
Ten. +7 495 258 13 16

Technology



ERGOFORM™
Ergonomic Design Technology

Ansell, ® and ™ are trademarks owned by Ansell Limited or one of its affiliates. US Patented and US and non-US Patents Pending: www.ansell.com/patentmarking © 2025 Ansell Limited. All Rights Reserved.

Neither this document nor any other statement made herein by or on behalf of Ansell should be construed as a warranty of merchantability or that any Ansell product is fit for a particular purpose. Ansell assumes no responsibility for the suitability or adequacy of an end user's selection of gloves for a specific application.

