

MICRO $\oplus$ FLEX™

Neogard™ TOUCH 73-737

Comfortable neoprene exam gloves,
certified for exceptional wet grip

Ultralight, comfortable neoprene exam gloves, recommended for exceptional wet grip

- **Elevated comfort:** Soft neoprene exam gloves featuring ERGOFORM™ Ergonomic Design Technology for extra comfort and support of musculoskeletal health
- **Enhanced grip:** Certified by US Ergonomics for enhanced wet grip capabilities*
- **Heightened tactile sensitivity:** Their thin, ultra-lightweight design offers enhanced tactile sensitivity, for more precise handling of tools and instruments
- **Reduced waste:** Packed 200 per box to reduce packaging waste



*this product has been certified by United States Ergonomics for exceptional wet grip performance in a variety of wet grip test conditions — these included gripping tests involving soap solutions, artificial saliva, artificial blood

Industries

- Healthcare
- Dental

Recommended For

- Protection from Type I latex allergy in HCW's or patients
- General dentistry
- Enhanced grip in wet environments
- Environmentally friendly facilities
- Extra comfort during long, sustained procedures
- Standard patient examinations

TECHNICAL DATA SHEET

	Product Information
Material	Neoprene
External Glove Surface	Textured Fingers
Audit Standards	ISO 13485, ISO 9001
Product Certification	ASTM D6977, US Ergo Wet Grip, FDA21 CFR 177-2600-US Food Contact Approved, US QSR/FDA 510(k) Medical Examination Grade, ISO 13485, ISO 9001
Packaging Overview	Case/Carton=2000 gloves/10 Dispensers; Dispenser=200 gloves (XS-L) Case/Carton=1800 gloves/10 Dispensers; Dispenser=180 gloves (XL)
Storage Instructions	Keep out of direct sunlight; store in a cool and dry place. Keep away from sources of ozone or ignition.
Country Of Origin	Indonesia
Product Segmentation	High Touch
Antistatic	Not Tested
Silicone Free	No

PHYSICAL PROPERTIES

	Typical Values		Testing Method
Length (mm/inches)	240 / 9.45		ASTM D3767,ASTM D6977
Freedom from Holes (Inspection level I)	1.5 AQL		ASTM D5151
Palm Thickness (mm/mils)	0.07 / 2.8		ASTM D3767,ASTM D6977
Finger Thickness (mm/mils)	0.09 / 3.5		ASTM D3767,ASTM D6977
	BEFORE AGING	AFTER AGING	
Ultimate Tensile Strength (MPa)	14	14	ASTM D412 & D573
Elongation at Break (%)	≥ 500	≥ 400	ASTM D412 & D573

ORDERING INFORMATION

Size	XS (5.5 - 6)	S (6.5 - 7)	M (7.5 - 8)	L (8.5 - 9)	XL (9.5 - 10)
Product Code	73737060	73737070	73737080	73737090	73737100

Performance Standards and Regulatory Compliance



For additional information visit us at www.ansell.com, or call us at

Europe, Middle East & Africa Region
Ansell Healthcare Europe NV
T: +32 (0) 2 528 74 00
F: +32 (0) 2 528 74 01
Asia Pacific Region
MY: +603 8310 6688
apac.medical@ansell.com
CN: +86 21 38275000
infochina@ansell.com
JP: +813 5549 8151
info.medical.jp@ansell.com

North America Region
Ansell Healthcare Products LLC
T: +1 800 800 0444
F: +1 800 800 0445
Latin America & Caribbean Region
BR: +55 (11) 3356-3100
latam.medical@ansell.com
MX: +52 442 296 2050
latam.medical@ansell.com
CO: +57 1 288 3247
latam.medical@ansell.com

Australia
Ansell Limited
T: +61 1800 337 041
F: +61 1800 803 578
Russia
Ansell PYC
Ten. +7 495 258 13 16



Ansell, ® and ™ are trademarks owned by Ansell Limited or one of its affiliates. US Patented and US and non-US Patents Pending: www.ansell.com/patentmarking © 2025 Ansell Limited. All Rights Reserved.

Neither this document nor any other statement made herein by or on behalf of Ansell should be construed as a warranty of merchantability or that any Ansell product is fit for a particular purpose. Ansell assumes no responsibility for the suitability or adequacy of an end user's selection of gloves for a specific application.

