

Disposable neoprene gloves, offering chemical splash protection with enhanced grip

- **Superior chemical splash protection:** Provides chemical splash protection against a broad array of chemicals
- **Strong grip:** These PPE gloves' neoprene formulation and textured fingertips offer advanced grip performance in wet and dry conditions
- **Specialized healthcare protection:** They have also been tested against cytotoxic/chemotherapy drugs*, thereby ensuring personal protection for healthcare workers in high-risk environments
- **Easy donning:** A polymer coating makes these gloves easy to don
- **Enhanced features:** These neoprene work gloves' beaded cuff design further improves workplace safety by limiting hazardous liquid roll-off



*see product packaging for details

Industries

- Life Sciences
- Healthcare
- Dental
- Fire and Rescue
- Automotive

Recommended For

- Sample taking and processing
- Testing
- Tested for use with chemotherapy drugs
- Protection from Type I latex allergy in HCW's or patients
- Loading centrifuges and chromatography columns
- Higher-risk clinical applications
- Assembly of parts
- Blending, compounding solids and liquids
- Administering drugs
- Maintenance
- Enhanced grip in wet environments
- Damp donning

TECHNICAL DATA SHEET

Product Information	
Material	Neoprene
External Glove Surface	Textured Fingers
Audit Standards	EN ISO 13485:2012
Product Certification	ASTM D6977, ASTM D6978, EN ISO 21420:2020, US QSR/FDA 510(k) Medical Examination Grade
Packaging Overview	100 gloves per dispenser 10 dispensers per case 1000 gloves per case
Storage Instructions	Keep out of direct sunlight; store in a cool and dry place. Keep away from sources of ozone or ignition.
Country Of Origin	Indonesia
Product Segmentation	Robust
Antistatic	Yes
Silicone Free	No

PHYSICAL PROPERTIES

	Typical Values		Testing Method
Length (mm/inches)	245 / 9.65		ASTM D3767,EN 420
Freedom from Holes (Inspection level I)	1.5 AQL		ASTM D5151,EN 455-1
Palm Thickness (mm/mils)	0.13 / 5.1		ASTM D3767,EN 420
Finger Thickness (mm/mils)	0.16 / 6.3		ASTM D3767,EN 420
	BEFORE AGING	AFTER AGING	
Elongation at Break (%)	≥ 650	≥ 400	ASTM D412
Force at break (N)	≥ 9	≥ 9	ASTM D6977

ORDERING INFORMATION

Size	XS (5.5 - 6)	S (6.5 - 7)	M (7.5 - 8)	L (8.5 - 9)	XL (9.5 - 10)
Product Code	NPG-888-XS	NPG-888-S	NPG-888-M	NPG-888-L	NPG-888-XL

For additional information visit us at www.ansell.com, or call us at

Europe, Middle East & Africa Region

Ansell Healthcare Europe NV

T: +32 (0) 2 528 74 00

F: +32 (0) 2 528 74 01

Asia Pacific Region

MY: +603 8310 6688

apac.medical@ansell.com

CN: +86 21 38275000

infochina@ansell.com

JP: +813 5549 8151

info.medical.jp@ansell.com

North America Region

Ansell Healthcare Products LLC

T: +1 800 800 0444

F: +1 800 800 0445

Latin America & Caribbean Region

BR: +55 (11) 3356-3100

latam.medical@ansell.com

MX: +52 442 296 2050

latam.medical@ansell.com

CO: +57 1 288 3247

latam.medical@ansell.com

Australia

Ansell Limited

T: +61 1800 337 041

F: +61 1800 803 578

Russia

Ansell PYC

Ten. +7 495 258 13 16

Ansell, ® and ™ are trademarks owned by Ansell Limited or one of its affiliates. US Patented and US and non-US Patents Pending; www.ansell.com/patentmarking © 2025 Ansell Limited. All Rights Reserved.

Neither this document nor any other statement made herein by or on behalf of Ansell should be construed as a warranty of merchantability or that any Ansell product is fit for a particular purpose. Ansell assumes no responsibility for the suitability or adequacy of an end user's selection of gloves for a specific application.

