

## A revolution in skin moisturization with sensational grip

- Skin moisturization:** MICROFLEX® NEOSOFT™ are comfortable neoprene medical exam gloves designed with HYDRASOFT™, a unique technology that helps skin retain moisture to improve skin health. In fact, lab tests show wearing MICROFLEX® NEOSOFT™ gloves help skin retain 2X more moisture\*
- Elevated comfort:** The gloves' soft and stretchy formulation provides exceptional comfort and ease of use
- Exceptional grip:** Advanced neoprene formulation and textured fingers deliver a secure, reliable wet grip
- Tactile sensitivity:** An ultra-lightweight design allows for enhanced tactile sensitivity when handling delicate instruments, parts and pieces



\*based on internal testing (data on file)

### Industries

- Healthcare

### Recommended For

- Enhanced grip in wet environments
- Enhanced tactile sensitivity and dexterity, especially for delicate procedures
- Extra comfort during long, sustained procedures
- Damp donning
- Standard patient examinations
- Protection from Type I latex allergy in HCW's or patients
- Helping protect skin from drying or cracking

# TECHNICAL DATA SHEET

Product Information	
<b>Material</b>	Neoprene (Polychloroprene)
<b>External Glove Surface</b>	Textured Fingers
<b>Audit Standards</b>	ISO 13485, ISO 9001
<b>Product Certification</b>	ASTM D6977, EN ISO 21420:2020, FDA21 CFR 177-2600-US Food Contact Approved, US QSR/FDA 510(k) Medical Examination Grade, ISO 13485, ISO 9001
<b>Packaging Overview</b>	100 gloves per dispenser 10 dispensers per case 1000 gloves per case
<b>Storage Instructions</b>	Keep out of direct sunlight; store in a cool and dry place. Keep away from sources of ozone or ignition.
<b>Country Of Origin</b>	Indonesia
<b>Product Segmentation</b>	Standard Thin
<b>Antistatic</b>	No
<b>Silicone Free</b>	No

## PHYSICAL PROPERTIES

	Typical Values	Testing Method
Length (mm/inches)	240 / 9.5	ASTM D3767,EN 420
Freedom from Holes (Inspection level I)	1.5 AQL	ASTM D5151,EN 374-2
Palm Thickness (mm/mils)	0.07 / 2.8	ASTM D3767,EN 420
Finger Thickness (mm/mils)	0.09 / 3.5	ASTM D3767,EN 420
	BEFORE AGING	AFTER AGING
Ultimate Tensile Strength (MPa)	≥ 14	≥ 14
Elongation at Break (%)	≥ 500	≥ 400

## ORDERING INFORMATION

Size	XS (5.5 - 6)	S (6.5 - 7)	M (7.5 - 8)	L (8.5 - 9)	XL (9.5 - 10)
Product Code	73837060	73837070	73837080	73837090	73837100

## Performance Standards and Regulatory Compliance



ISO 13485 ISO 9001

For additional information visit us at [www.ansell.com](http://www.ansell.com), or call us at

**Europe, Middle East & Africa Region**  
Ansell Healthcare Europe NV

T: +32 (0) 2 528 74 00  
F: +32 (0) 2 528 74 01

**Asia Pacific Region**  
MY: +603 8310 6688  
apac.medical@ansell.com  
CN: +86 21 38275000  
infochina@ansell.com  
JP: +813 5549 8151  
info.medical.jp@ansell.com

**North America Region**  
Ansell Healthcare Products LLC

T: +1 800 800 0444  
F: +1 800 800 0445

**Latin America & Caribbean Region**  
BR: +55 (11) 3356-3100  
latam.medical@ansell.com  
MX: +52 442 296 2050  
latam.medical@ansell.com  
CO: +57 1 288 3247  
latam.medical@ansell.com

**Australia**  
Ansell Limited

T: +61 1800 337 041  
F: +61 1800 803 578

**Russia**  
Ansell PYC  
Ten: +7 495 258 13 16

## Technology



Ansell, ® and ™ are trademarks owned by Ansell Limited or one of its affiliates. US Patented and US and non-US Patents Pending: [www.ansell.com/patentmarking](http://www.ansell.com/patentmarking) © 2025 Ansell Limited. All Rights Reserved.

Neither this document nor any other statement made herein by or on behalf of Ansell should be construed as a warranty of merchantability or that any Ansell product is fit for a particular purpose. Ansell assumes no responsibility for the suitability or adequacy of an end user's selection of gloves for a specific application.

