

## Robust nitrile exam gloves, ensuring hand protection for diverse applications

- **Improved durability:** MICROFLEX® Supreno® SE SU-690 exam gloves are made with a strong nitrile formulation, offering wearers robust personal protection
- **Strong grip:** These gloves' textured fingertips ensure better grip when handling tools and equipment
- **Low AQL:** 0.65 AQL means these gloves offer excellent barrier protection against potentially hazardous substances



### Industries

- Automotive
- Automotive Aftermarket
- Life Sciences
- Healthcare
- Agriculture
- Emergency Medical Services
- Utilities
- Warehousing

### Recommended For

- Inspection, selecting, checking parts
- Assembly and inspection of components
- Picking and fastening components
- Equipment repair and maintenance
- General Purpose Auto Aftermarket
- Oil, fluids and filter change
- Engine transmission and repair
- Tire rotation & changes
- Maintaining lab furniture and equipment
- Assembly of parts
- Sample taking and processing
- Raw material sample collection
- Higher-risk clinical applications
- Protection from Type I latex allergy in HCW's or patients

TECHNICAL DATA SHEET

|                        | Product Information                                                                                      |
|------------------------|----------------------------------------------------------------------------------------------------------|
| External Glove Surface | Textured Fingers                                                                                         |
| Audit Standards        | EN ISO 13485:2012                                                                                        |
| Packaging Overview     | 100 gloves per dispenser<br>10 dispensers per case<br>1000 gloves per case                               |
| Storage Instructions   | Keep out of direct sunlight; store in a cool and dry place. Keep away from sources of ozone or ignition. |
| Country Of Origin      | Malaysia                                                                                                 |
| Product Segmentation   | Robust                                                                                                   |
| Antistatic             | Yes                                                                                                      |

PHYSICAL PROPERTIES

|                                         | Typical Values |             | Testing Method      |
|-----------------------------------------|----------------|-------------|---------------------|
| Length (mm/inches)                      | 245 / 9.6      |             | ASTM D3767,EN 420   |
| Freedom from Holes (Inspection level I) | 0.65 AQL       |             | ASTM D5151,EN 455-1 |
| Palm Thickness (mm/mils)                | 0.11 / 4.3     |             | ASTM D3767,EN 420   |
| Finger Thickness (mm/mils)              | 0.18 / 7.1     |             | ASTM D3767,EN 420   |
|                                         | BEFORE AGING   | AFTER AGING |                     |
| Ultimate Tensile Strength (MPa)         | 32             | 27          | ASTM D412 & D573    |
| Elongation at Break (%)                 | 550            | 500         | ASTM D412           |
| Force at break (N)                      | 12             | 9           | EN 455-2            |

ORDERING INFORMATION

| Size         | XS (5.5 - 6) | S (6.5 - 7) | M (7.5 - 8) | L (8.5 - 9) | XL (9.5 - 10) |
|--------------|--------------|-------------|-------------|-------------|---------------|
| Product Code | SU-690-XS    | SU-690-S    | SU-690-M    | SU-690-L    | SU-690-XL     |

Performance Standards and Regulatory Compliance



For additional information visit us at [www.ansell.com](http://www.ansell.com), or call us at

|                                                                                                                                                                                                                                                                                                                         |                                                                                                                                                                                                                                                                                                                          |                                                                                                                                              |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Europe, Middle East &amp; Africa Region</b><br>Ansell Healthcare Europe NV<br>T: +32 (0) 2 528 74 00<br>F: +32 (0) 2 528 74 01<br><br><b>Asia Pacific Region</b><br>MY: +603 8310 6688<br>apac.medical@ansell.com<br>CN: +86 21 38275000<br>infochina@ansell.com<br>JP: +813 5549 8151<br>info.medical.jp@ansell.com | <b>North America Region</b><br>Ansell Healthcare Products LLC<br>T: +1 800 800 0444<br>F: +1 800 800 0445<br><br><b>Latin America &amp; Caribbean Region</b><br>BR: +55 (11) 3356-3100<br>latam.medical@ansell.com<br>MX: +52 442 296 2050<br>latam.medical@ansell.com<br>CO: +57 1 288 3247<br>latam.medical@ansell.com | <b>Australia</b><br>Ansell Limited<br>T: +61 1800 337 041<br>F: +61 1800 803 578<br><br><b>Russia</b><br>Ansell PYC<br>Ten. +7 495 258 13 16 |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------|

Ansell, ® and ™ are trademarks owned by Ansell Limited or one of its affiliates. US Patented and US and non-US Patents Pending; [www.ansell.com/patentmarking](http://www.ansell.com/patentmarking) © 2024 Ansell Limited. All Rights Reserved.

Neither this document nor any other statement made herein by or on behalf of Ansell should be construed as a warranty of merchantability or that any Ansell product is fit for a particular purpose. Ansell assumes no responsibility for the suitability or adequacy of an end user's selection of gloves for a specific application.

