

## Gloves with sensitivity plus durability for all-around protection

- **Heightened sensitivity:** This lightweight glove is suitable for demanding jobs requiring tactile sensitivity and fine motor control
- **Tear resistance:** The high-quality nitrile formulation provides enhanced resistance against rips and tears
- **Genuine versatility:** Offers an unbeatable quality-to-price ratio for demanding jobs in a wide variety of industries



### Industries

- Automotive
- Food Processing
- Janitorial / Sanitation

### Recommended For

- Catering/Meal preparation
- Food processing and handling
- Meat, Fish and Food Processing
- Marinating
- Packing of fillets and ground meat
- Equipment, maintenance and repair
- Janitorial, clean up and maintenance
- Personal care and beauty salons

# TECHNICAL DATA SHEET

| Product Information    |   |
|------------------------|---|
| Material               | Nitrile   |
| External Glove Surface | Textured Fingers  |
| Audit Standards        | ISO 9001  |
| Product Certification  | Personal Protective Equipment Regulation (EU) 2016/425 Category III risks, EC 2023/2006, EC 2002/72, EN ISO 21420:2020, EN ISO 374-1:2016 Type C Chemical, EN ISO 374-5:2016 Virus, FDA21 CFR 177-2600-US Food Contact Approved, EU Food Contact Approved, ISO 9001 |
| Packaging Overview     | 100 gloves per dispenser/box<br>10 dispensers/box per carton/case   |
| Storage Instructions   | Keep out of direct sunlight; store in a cool and dry place. Keep away from sources of ozone or ignition.  |
| Country Of Origin      | China   |
| Product Segmentation   | Standard Thin   |
| Antistatic             | No  |
| Silicone Free          | No  |

## PHYSICAL PROPERTIES

|   | Typical Values |                    | Testing Method                |
|---|----------------|--------------------|-------------------------------|
| Length (mm/inches)                      | 240 / 9.5      |                    | ASTM D3767,EN 420             |
| Freedom from Holes (Inspection level I) | 1.5 AQL        |                    | ASTM D5151-06 (2011),EN 374-2 |
| Palm Thickness (mm/mils)                | 0.07/2.8       |                    | ASTM D3767,EN 420             |
| Finger Thickness (mm/mils)              | 0.11/4.3       |                    | ASTM D3767,EN 420             |
| <b>BEFORE AGING</b>                     |                | <b>AFTER AGING</b> |                               |
| Ultimate Tensile Strength (MPa)         | 14             | 14                 | ASTM D412 & D573              |
| Elongation at Break (%)                 | 500            | 400                | ASTM D412                     |
| Force at break (N)                      | 6              | 6                  | EN 455-2                      |

## ORDERING INFORMATION

| Size         | XS (5.5 - 6) | S (6.5 - 7) | M (7.5 - 8) | L (8.5 - 9) | XL (9.5 - 10) |
|--------------|--------------|-------------|-------------|-------------|---------------|
| Product Code | 82134060     | 82134070    | 82134080    | 82134090    | 82134100      |

## Performance Standards and Regulatory Compliance



For additional information visit us at [www.ansell.com](http://www.ansell.com), or call us at

**Europe, Middle East & Africa Region**  
Ansell Healthcare Europe NV  
T: +32 (0) 2 528 74 00  
F: +32 (0) 2 528 74 01

**Asia Pacific Region**  
MY: +603 8310 6688  
apac.medical@ansell.com  
CN: +86 21 38275000  
infochina@ansell.com  
JP: +813 5549 8151  
info.medical.jp@ansell.com

**North America Region**  
Ansell Healthcare Products LLC  
T: +1 800 800 0444  
F: +1 800 800 0445

**Latin America & Caribbean Region**  
BR: +55 (11) 3356-3100  
latam.medical@ansell.com  
MX: +52 442 296 2050  
latam.medical@ansell.com  
CO: +57 1 288 3247  
latam.medical@ansell.com

**Australia**  
Ansell Limited  
T: +61 1800 337 041  
F: +61 1800 803 578

**Russia**  
Ansell PYC  
T: +7 495 258 1316

Ansell, ® and ™ are trademarks owned by Ansell Limited or one of its affiliates. US Patented and US and non-US Patents Pending: [www.ansell.com/patentmarking](http://www.ansell.com/patentmarking) © 2025 Ansell Limited. All Rights Reserved.

Neither this document nor any other statement made herein by or on behalf of Ansell should be construed as a warranty of merchantability or that any Ansell product is fit for a particular purpose. Ansell assumes no responsibility for the suitability or adequacy of an end user's selection of gloves for a specific application.

