

# 10-134

Disposable Nitrile Glove with Textured Fingers

# Comfortable nitrile gloves with sensitivity and durability for all around protection

- Heightened sensitivity: Lightweight construction, for tactile sensitivity and fine motor control
- Thin nitrile formulation: High-quality nitrile formulation provides resistance against rips and tears
- Genuine versatility: Designed for a broad range of applications across industries and available through online retailers



#### **Industries**

- Automotive
- Food Processing
- Janitorial / Sanitation

#### **Recommended For**

- Catering/Meal preparation
- Food processing and handling
- Meat, Fish and Food Processing
- Marinating
- Packing of fillets and ground meat
- Equipment, maintenance and repair
- Janitorial, clean up and maintenance
- Personal care and beauty salons



#### **TECHNICAL DATA SHEET**

	Product Information
Material	Nitrile
External Glove Surface	Textured Fingers
Audit Standards	ISO 13485, ISO 9001
Product Certification	Medical Device Regulation (EU) 2017/745 Class I, Personal Protective Equipment Regulation (EU) 2016/425 Category III risks, ASTM D6319, CE 0493, EAC TP TC 019:2011, FDA21 CFR 177-2600-US Food Contact Approved, EU Food Contact Approved, EC 2023/2006, EC 2002/72, EN ISO 374-1:2016 Type C Chemical, EN ISO 374-5:2016 Virus, EN ISO 21420:2020, ISO 13485, ISO 9001, UKCA
Packaging Overview	100 gloves per dispenser, 10 dispensers per case, 1000 gloves per case
Storage Instructions	Keep out of direct sunlight; store in a cool and dry place. Keep away from sources of ozone or ignition.
Country Of Origin	Malaysia
Product Segmentation	Standard Thin
Antistatic	No
Silicone Free	No

### **PHYSICAL PROPERTIES**

	Typical '	Values	Testing Method
Length (mm/inches)	240 / 9.5		ASTM D3767,EN 420
Freedom from Holes (Inspection level I)	1.5 AQL		ASTM D5151-06 (2011),EN 374-2
Palm Thickness (mm/mils)	0.07 / 2.8		ASTM D3767,EN 420
Finger Thickness (mm/mils)	0.11 / 4.3		ASTM D3767,EN 420
	<b>BEFORE AGING</b>	AFTER AGING	
Ultimate Tensile Strength (MPa)	14	14	ASTM D412-06a
Elongation at Break (%)	500	400	ASTM D412-06a
Force at break (N)	6	6	EN 455-2

#### **ORDERING INFORMATION**

Size	S (6.5 - 7)	M (7.5 - 8)	L (8.5 - 9)
Product Code	10134070	10134080	10134090

### **Performance Standards and Regulatory Compliance**



## For additional information visit us at www.ansell.com, or call us at

Ansell Healthcare Europe NV T: +32 (0) 2 528 74 00 F: +32 (0) 2 528 74 01 Asia Pacific Region MY +603 8310 6688 anac medical@ansell.com

CN: +86 21 38275000 infochina@ansell.com JP: +813 5549 8151 info.medical.jp@ansell.com Ansell Healthcare Products LLC T:+1 800 800 0444 F: ±1 800 800 0445 Latin America & Caribbean Region BR +55 (11) 3356-3100

latam medical@ansell.com MX: +52 442 296 2050 latam.medical@ansell.com CO: +57 1 288 3247 latam.medical@ansell.com

Ansell Limited T: +61 1800 337 041 F: ±61 1800 803 578

Ansell PYC Ten. +7 495 258 13 16

Ansell, ® and ™ are trademarks owned by Ansell Limited or one of its affiliates. US Patented and US and non-US Patents Pending: www.ansell.com/patentmarking © 2025 Ansell Limited. All Rights Reserved.

Neither this document nor any other statement made herein by or on behalf of Ansell should be construed as a warranty of merchantability or that any Ansell product is fit for a particular purpose. Ansell assumes no responsibility for the suitability or adequacy of an end user's selection of gloves for a specific application.

