

Durable disposable gloves for extended wear time

- **Durability:** Robust design allows for longer wear time in a variety of heavy-duty jobs
- **Secure grip:** Fully textured for a firm, safe grip in dry and wet environments
- **Genuine versatility:** Designed for heavy-duty jobs across industries, and available in a broad range of sizes through online retailers
- **Cost-effective:** Durable protection offered at excellent value
- **Food handling compliance:** Suitable for a wide range of food handling applications, as per GB 4806.11 (contact time with foodstuffs at 40°C/104°F, for a maximum of 30 minutes)



Industries

- Agriculture
- Food Processing

Recommended For

- Food processing and handling
- Handling of machined parts coated with light oil
- Lab work, blending, compounding, filling, cleaning
- Maintenance and equipment clean up
- Mechanical jobs
- Handling of paint/glue guns and sprayers
- Equipment repair and maintenance
- Fastening, screwing, unscrewing parts

TECHNICAL DATA SHEET

	Product Information
Material	Nitrile
External Glove Surface	Fully Textured
Audit Standards	ISO 13485, ISO 9001
Product Certification	Medical Device Regulation (EU) 2017/745 Class I, Personal Protective Equipment Regulation (EU) 2016/425 Category III risks, Arrêté du 09/04/04, EC 2002/72, EU Food Contact Approved, EC 2023/2006, ASTM D6319, CE 0493, EAC TP TC 019:2011, FDA21 CFR 177-2600-US Food Contact Approved, EN ISO 21420:2020, EN ISO 374-1:2016 Type B JKPT, EN ISO 374-5:2016 Virus, ISO 13485, ISO 9001, UKCA
Packaging Overview	500 gloves per dispenser 50 dispensers per case
Storage Instructions	Keep out of direct sunlight; store in a cool and dry place. Keep away from sources of ozone or ignition.
Country Of Origin	Malaysia
Product Segmentation	Robust
Antistatic	No
Silicone Free	Yes

PHYSICAL PROPERTIES

	Typical Values		Testing Method
Length (mm/inches)	240 / 9.45		ASTM D3767,EN 420
Freedom from Holes (Inspection level I)	1.5 AQL		ASTM D5151,EN 374-2
Palm Thickness (mm/mils)	0.17/6.7		ASTM D3767,EN 420
Finger Thickness (mm/mils)	0.19/7.5		ASTM D3767,EN 420
	BEFORE AGING	AFTER AGING	
Elongation at Break (%)	500	400	ASTM D412-06a
Force at break (N)	8	8	EN 455-2

ORDERING INFORMATION

Size	S (6.5 - 7)	M (7.5 - 8)	L (8.5 - 9)
Product Code	10135070	10135080	10135090

Performance Standards and Regulatory Compliance





For additional information visit us at www.ansell.com, or call us at

Europe, Middle East & Africa Region
Ansell Healthcare Europe NV
T: +32 (0) 2 528 74 00
F: +32 (0) 2 528 74 01

Asia Pacific Region
MY +603 8310 6688
apac.medical@ansell.com
CN: +86 21 38275000
infochina@ansell.com
JP: +813 5549 8151
info.medical.jp@ansell.com

North America Region
Ansell Healthcare Products LLC
T: +1 800 800 0444
F: +1 800 800 0445

Latin America & Caribbean Region
BR +55 (11) 3356-3100
latam.medical@ansell.com
MX: +52 442 296 2050
latam.medical@ansell.com
CO: +57 1 288 3247
latam.medical@ansell.com

Australia
Ansell Limited
T: +61 1800 337 041
F: +61 1800 803 578

Russia
Ansell PYC
Ten. +7 495 258 13 16

Ansell, ® and ™ are trademarks owned by Ansell Limited or one of its affiliates. US Patented and US and non-US Patents Pending: www.ansell.com/patentmarking © 2025 Ansell Limited. All Rights Reserved.

Neither this document nor any other statement made herein by or on behalf of Ansell should be construed as a warranty of merchantability or that any Ansell product is fit for a particular purpose. Ansell assumes no responsibility for the suitability or adequacy of an end user's selection of gloves for a specific application.

