

# 10-154

Disposable Nitrile Glove with Textured Fingers

# Comfortable nitrile gloves, delivering sensitivity and durability, for all-around protection

- Heightened sensitivity: Lightweight construction for tactile sensitivity and fine motor control
- Thin nitrile formulation: High-quality nitrile formulation provides resistance against rips and tears
- Genuine versatility: Designed for a broad range of applications across industries and available through online retailers



#### **Industries**

- Automotive
- Food Processing
- Janitorial / Sanitation

#### **Recommended For**

- Catering/Meal preparation
- Food processing and handling
- Meat, Fish and Food Processing
- Marinating
- Packing of fillets and ground meat
- Equipment, maintenance and repair
- Janitorial, clean up and maintenance
- Personal care and beauty salons



# **TECHNICAL DATA SHEET**

	Product Information
Material	Nitrile
External Glove Surface	Textured Fingers
Audit Standards	ISO 9001:2008
Product Certification	Medical Device Regulation (EU) 2017/745 Class I, Personal Protective Equipment Regulation (EU) 2016/425 Category III risks, ASTM D6319, CE 0493, EAC TP TC 019:2011, FDA21 CFR 177-2600-US Food Contact Approved, EU Food Contact Approved, EC 2023/2006, EC 2002/72, EN ISO 21420:2020, EN ISO 374-1:2016 Type C Chemical, EN ISO 374-5:2016 Virus, ISO 13485, ISO 9001, UKCA
Packaging Overview	50 gloves per dispenser, 24 dispensers per case
Storage Instructions	Keep out of direct sunlight; store in a cool and dry place. Keep away from sources of ozone or ignition.
Country Of Origin	China
Product Segmentation	Standard Thin
Antistatic	No
Silicone Free	No

# **PHYSICAL PROPERTIES**

	Typical Values		Testing Method
Length (mm/inches)	240 / 9.5		ASTM D3767,EN 420
Freedom from Holes (Inspection level I)	1.5 AQL		ASTM D5151-06 (2011),EN 374-2
Palm Thickness (mm/mils)	0.07 / 2.8		ASTM D3767,EN 420
Finger Thickness (mm/mils)	0.11 / 4.3		ASTM D3767,EN 420
	<b>BEFORE AGING</b>	AFTER AGING	
Ultimate Tensile Strength (MPa)	14	14	ASTM D412-06a
Elongation at Break (%)	500	400	ASTM D412-06a
Force at break (N)	6	6	EN 455-2

### **ORDERING INFORMATION**

Size	S (6.5 - 7)	M (7.5 - 8)	L (8.5 - 9)
Product Code	10154070	10154080	10154090

# **Performance Standards and Regulatory Compliance**



#### For additional information visit us at www.ansell.com, or call us at

Europe, Middle East & Africa Region Ansell Healthcare Europe NV T:+32 (0) 2 528 74 00 F:+32 (0) 2 528 74 01 Asia Parific Region

Asia Pacific Region
MY +603 8310 6688
apac.medical@ansell.com
CN: +86 21 38275000
infochina@ansell.com
JP: +813 5549 8151
info.medical.jp@ansell.com

North America Region
Ansell Healthcare Products LLC
T.+1800 800 0444
F.+1800 800 0445
Latin America & Caribbean Region
BR.+55 (11) 3356-3100
latam.medica@ansell.com
MX.+52.442 296 2050

CO: +57 1 288 3247 latam.medical@ansell.com Australia
Ansell Limited
T: +61 1800 337 041
F: +61 1800 803 578
Russia

Russia Ansell PYC Ten. +7 495 258 13 16

Ansell, ® and ™ are trademarks owned by Ansell Limited or one of its affiliates. US Patented and US and non-US Patents Pending: www.ansell.com/patentmarking © 2025 Ansell Limited. All Rights Reserved.

Neither this document nor any other statement made herein by or on behalf of Ansell should be construed as a warranty of merchantability or that any Ansell product is fit for a particular purpose. Ansell assumes no responsibility for the suitability or adequacy of an end user's selection of gloves for a specific application.

