

# TouchNTuff™

## 92-600

Disposable Nitrile Glove with Enhanced Chemical Splash Protection

## An unparalleled combination of chemical splash protection, comfort and durability

- **World leader:** TouchNTuff™ 92-600 gloves are the world's leading disposable gloves for chemical splash protection
- **Superior protection:** Made with TNT™ Chemical Splash Resistance Technology, these gloves effectively safeguard hands from exposure to harmful chemicals
- **Elevated comfort:** Super soft nitrile provides a comfortable feel during extended wear
- **Robust durability:** EN388 certified, meeting level 1 abrasion to prevent ripping and tearing during heavy-duty work
- **Prevents surface defects:** Silicone-free, they prevent contaminant transfer that causes flaws in paints, coatings and finishes
- **Dermatest™ certified:** Supports reduced risk of skin irritation



### Industries

- Life Sciences
- Food Processing
- Automotive
- Agriculture
- Infrastructure Maintenance
- Chemical

### Recommended For

- Meat, Fish and Food Processing
- Industrial Production
- Transferring liquids and solids
- Laboratory analysis
- Maintenance
- Chemical Handling

## TECHNICAL DATA SHEET

| Product Information    |                                                                                                                                                                                                                                                                                                                                                            |
|------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Material               | Nitrile                                                                                                                                                                                                                                                                                                                                                    |
| External Glove Surface | Smooth                                                                                                                                                                                                                                                                                                                                                     |
| Audit Standards        | ISO 9001                                                                                                                                                                                                                                                                                                                                                   |
| Product Certification  | Category III, EN 388:2016 1XXXX, EN ISO 21420:2020, EN ISO 374-1:2016 Type B JKPT, EN ISO 374-5:2016 Virus, FDA21 CFR 177-2600-US Food Contact Approved, EU Food Contact Approved, ISO 18889:2019, ISO 9001, UKCA, DOSH-SIRIM certified, Dermatest                                                                                                         |
| Packaging Overview     | <p>XS-XL: 100 gloves per dispenser, 10 dispensers per case, 1000 gloves per case<br/>                     XXL: 90 gloves per dispenser, 10 dispensers per case, 900 gloves per case<br/>                     Size XS and XXL are not available in China and Brazil</p> <p>Vend Pack Variant (Size S, M, L, XL): 20 gloves per box, 24 boxes per carton</p> |
| Storage Instructions   | Keep out of direct sunlight; store in a cool and dry place. Keep away from sources of ozone or ignition.                                                                                                                                                                                                                                                   |
| Country Of Origin      | Thailand;Sri Lanka                                                                                                                                                                                                                                                                                                                                         |
| Product Segmentation   | Robust                                                                                                                                                                                                                                                                                                                                                     |
| Antistatic             | Yes EN1149                                                                                                                                                                                                                                                                                                                                                 |
| Silicone Free          | Yes                                                                                                                                                                                                                                                                                                                                                        |

## PHYSICAL PROPERTIES

|                                         | Typical Values      |                    | Testing Method      |
|-----------------------------------------|---------------------|--------------------|---------------------|
| Length (mm/inches)                      | 240 / 9.45          |                    | ASTM D3767,EN 420   |
| Freedom from Holes (Inspection level I) | 1.5 AQL             |                    | ASTM D5151,EN 455-1 |
| Palm Thickness (mm/mils)                | 0.125 / 4.92        |                    | ASTM D3767,EN 420   |
| Finger Thickness (mm/mils)              | 0.14 / 5.5          |                    | ASTM D3767,EN 420   |
|                                         | <b>BEFORE AGING</b> | <b>AFTER AGING</b> |                     |
| Elongation at Break (%)                 | ≥ 600               | ≥ 525              | ASTM D412           |
| Force at break (N)                      | ≥ 10                | ≥ 10               | EN 455-2            |

ORDERING INFORMATION

| Size         | S (6.5 - 7) | M (7.5 - 8) | L (8.5 - 9) | XL (9.5 - 10) |
|--------------|-------------|-------------|-------------|---------------|
| Product Code | 92600070    | 92600080    | 92600090    | 92600100      |

Performance Standards and Regulatory Compliance

  
1XXXX

  
JKPT

  
VIRUS



  
ISO 18889

  
ISO 9001



For additional information visit us at [www.ansell.com](http://www.ansell.com), or call us at

**Europe, Middle East & Africa Region**  
Ansell Healthcare Europe NV  
T: +32 (0) 2 528 74 00  
F: +32 (0) 2 528 74 01

**Asia Pacific Region**  
MY +603 8310 6688  
apac.medical@ansell.com  
CN: +86 21 38275000  
infochina@ansell.com  
JP: +813 5549 8151  
info.medical.jp@ansell.com

**North America Region**  
Ansell Healthcare Products LLC  
T: +1 800 800 0444  
F: +1 800 800 0445

**Latin America & Caribbean Region**  
BR +55 (11) 3356-3100  
latam.medical@ansell.com  
MX: +52 442 296 2050  
latam.medical@ansell.com  
CO: +57 1 288 3247  
latam.medical@ansell.com

**Australia**  
Ansell Limited  
T: +61 1800 337 041  
F: +61 1800 803 578

**Russia**  
Ansell PYC  
Ten. +7 495 258 13 16

Technology

**TNT™**  
Chemical Splash  
Resistance Technology

Ansell, ® and ™ are trademarks owned by Ansell Limited or one of its affiliates. US Patented and US and non-US Patents Pending: [www.ansell.com/patentmarking](http://www.ansell.com/patentmarking) © 2025 Ansell Limited. All Rights Reserved.

Neither this document nor any other statement made herein by or on behalf of Ansell should be construed as a warranty of merchantability or that any Ansell product is fit for a particular purpose. Ansell assumes no responsibility for the suitability or adequacy of an end user's selection of gloves for a specific application.

