

## 92-605

Extended Cuff Disposable Nitrile Glove with Enhanced Chemical Splash Protection

# Long-cuffed disposable gloves, delivering superior chemical splash protection and comfort

- World leader: Extended-cuff version of TouchNTuff<sup>®</sup> 92-600, the world's leading disposable gloves for chemical splash protection
- Superior, extended cuff protection:
   Made with TNT™ Chemical Splash
   Resistance Technology, these gloves
   guard hands, wrists and forearms against harmful chemical splashes
- Elevated comfort: Super soft nitrile provides a comfortable feel during extended wear
- Robust durability: Proprietary formulation is extra-strong to prevent tearing during heavy-duty work
- Prevents surface defects: Silicone-free, they prevent contaminant transfer that causes flaws in paints, coatings and finishes



#### **Industries**

- Life Sciences
- Food Processing
- Automotive
- Machinery and Equipment
- Chemical

#### **Recommended For**

- Sample taking and processing
- Laboratory analysis
- Transferring liquids and solids
- Meat, Fish and Food Processing
- Industrial Production
- Maintenance
- Chemical Handling



#### **TECHNICAL DATA SHEET**

	Product Information
External Glove Surface	Textured Fingers
Audit Standards	ISO 9001
Packaging Overview	100 gloves per dispenser 10 dispensers per case 1000 gloves per case
Storage Instructions	Keep out of direct sunlight; store in a cool and dry place. Keep away from sources of ozone or ignition.
Country Of Origin	Thailand
Product Segmentation	High Risk
Antistatic	Yes EN1149

#### **PHYSICAL PROPERTIES**

	Typical	Testing Method	
Length (mm/inches)	n (mm/inches) 300 / 12		ASTM D3767,EN 420
Freedom from Holes (Inspection level I)	1.5 AQL		ASTM D5151,EN 455-1
Palm Thickness (mm/mils)	0.12 / 4.7		ASTM D3767,EN 420
Finger Thickness (mm/mils)	0.16 / 6.3		ASTM D3767,EN 420
	<b>BEFORE AGING</b>	AFTER AGING	
Ultimate Tensile Strength (MPa)	≥ 14	≥ 14	ASTM D412 & D573
Elongation at Break (%)	≥ 500	≥ 400	ASTM D412
Force at break (N)	≥ 6	≥ 6	EN 455-2

#### **ORDERING INFORMATION**

Size	S (6.5 - 7)	M (7.5 - 8)	L (8.5 - 9)	XL (9.5 - 10)
Product Code	92605070	92605080	92605090	92605100

#### **Performance Standards and Regulatory Compliance**













#### For additional information visit us at www.ansell.com, or call us at

Europe, Middle East & Africa Region Ansell Healthcare Europe NV T: +32 (0) 2 528 74 00 F: +32 (0) 2 528 74 01

Asia Pacific Region MY +603 8310 6688 apac.medical@ansell.com CN: +86 21 38275000 infochina@ansell.com JP: +813 5549 8151 info.medical.jp@ansell.com North America Region Ansell Healthcare Products LLC T: +1 800 800 0444

F: +1 800 800 0445 Latin America & Caribbean Region BR +55 (11) 3356-3100

latam.medical@ansell.com MX: +52 442 296 2050 latam.medical@ansell.com CO: +57 1 288 3247 latam.medical@ansell.com

Δustralia

Ansell Limited T: +61 1800 337 041 F: +61 1800 803 578

Ansell PYC Ten. +7 495 258 13 16

### **Technology**



Ansell, ® and ™ are trademarks owned by Ansell Limited or one of its affiliates. US Patented and US and non-US Patents Pending: www.ansell.com/patentmarking © 2024 Ansell Limited. All Rights Reserved.

Neither this document nor any other statement made herein by or on behalf of Ansell should be construed as a warranty of merchantability or that any Ansell product is fit for a particular purpose. Ansell assumes no responsibility for the suitability or adequacy of an end user's selection of gloves for a specific application.

