

Chemical-resistant CSM gloves, offering lasting hand protection

Port size: 203mm/8" Thickness: 0.4mm/16 mil

- Specialized defenses: The AlphaTec® CSM Isolator Glove 85-300 offers excellent chemical resistance, protecting wearers against concentrated acids and bases
- Elevated comfort: These CSM gloves are made from soft, flexible material, for everyday comfort and usability
- Prolonged glove life: The AlphaTec® CSM Isolator Glove 85-300 can also withstand prolonged exposure to oxygen, UV rays and ozone without rapidly aging, and they boast EN 388:2016+A1:2018 Level 3 abrasion resistance
- **Reduced contamination risks:** These PPE gloves are white in color, facilitating contamination detection

KEY FEATURES & BENEFITS

- Robust CSM composition: Resistant against concentrated acids/bases
- Flexible material: For comfortable, easy-to-use safety gloves
- **Durable design:** Withstands prolonged oxygen, UV ray and ozone exposure





AlphaTec® Advanced chemical protection

85-300 Non-clean/Non-sterile CSM RABS/Isolator Gloves

TECHNICAL DATA SHEET

| Product Reference | 85-300 |
|--|--|
| Material | Chlorosulfonated polyethylene_CSM |
| Color | White |
| Shape | Ambidextrous |
| External Glove Surface | Smooth |
| Cuff Style | Beaded |
| Storage Instructions | Store in a dry and dark environment, temperature of 5°C to 22°C. Retain in original packaging when not in use. |
| Available Sizes | 11, 9.5 |
| Temperature Range | From -20°C to 120°C |
| Shelf Life | Three (3) years from date of manufacture. |
| Standards | CE 0493, EN 388:2016 +A1:2018, EN ISO 21420:2020, EN ISO 374-5:2016, EN ISO 374-1:2016 Type B, Category III |
| Vulcanization Chemical Accelerators | None |

AlphaTec[®]

PHYSICAL PROPERTIES

| | Typical Values | Testing Method |
|---|-----------------|----------------|
| Typical Length (mm/in) | 800 mm / 32" | EN ISO 21420 |
| Port Size | 8" | |
| | | |
| | | |
| Target Single Wall Palm Thickness (mm/mil) | 0.4 mm /16 mil | EN 455-2 |
| Target Single Wall Cuff Thickness (mm/mil) | 0.4 mm / 16 mil | EN 455-2 |

PROTECTION AGAINST MECHANICAL RISKS, EN 388:2016+A1:2018

| Risk | Performance level | |
|----------------------|-------------------|--|
| Abrasion Resistance | Level 3 | |
| Blade Cut Resistance | Level 1 | |
| Tear Resistance | Level O | |
| Puncture Resistance | Level 1 | |

ORDERING INFORMATION

| | PORT SIZE | 8"/203mm | 8"/203mm |
|--------|-------------|----------|----------|
| | SIZE | 9.5 | 11 |
| 85-300 | REORDER NO. | 85300095 | 85300110 |

For additional information visit us at www.ansell.com, or call us at

Europe, Middle East & Africa Region Ansell Healthcare Europe NV T: +32 (0) 2 528 74 00 F: +32 (0) 2 528 74 01

Asia Pacific Region Ansell Global Trading Center T: +603 8310 6688 F: +603 8310 6699 North America Region Ansell Healthcare Products LLC US T: +1 800 800 0444 US F: +1 800 800 0445 CA T: +1-800-363-8340

CA T: +1-800-363-8340 Latin America & Caribbean Region Ansell Commercial Mexico S.A. de C.V. T: +52 442 248 1544 / 248 3133 Australia Ansell Limited T: +61 1800 337 041 F: +61 1800 803 578 UK

Ansell Nitritex T: +44 1638 663338 F: +44 1638 668890

Performance Standards and Regulatory Compliance



Ansell, [®] and [™] are trademarks owned by Ansell Limited or one of its affiliates. US Patented and US and non-US Patents Pending: www.ansell.com/patentmarking © 2024 Ansell Limited. All Rights Reserved.

Neither this document nor any other statement made herein by or on behalf of Ansell should be construed as a warranty of merchantability or that any Ansell product is fit for a particular purpose. Ansell assumes no responsibility for the suitability or adequacy of an end user's selection of gloves for a specific application.

