

Chemical splash-resistant neoprene gloves, ideal for Class 100 (ISO 5) cleanroom environments

- **Assured cleanliness:** TouchNTuff® 73-300 cleanroom gloves are specially designed for compatibility with Class 100 (ISO 5) cleanroom environments
- **Specialized protection:** Thanks to their unique formulation, these neoprene disposable gloves offer splash resistance against a range of chemical hazards
- **Reduced allergy risks:** As these neoprene gloves are free of latex proteins and chemical accelerators, the risk of Type I and Type IV allergic reactions is minimized
- **Improved fit and usability:** A beaded cuff design featuring SUREFIT™ Cuff Roll-Down Technology offers a secure fit, prevents liquid roll-off and makes these cleanroom gloves ideal for double donning



KEY FEATURES & BENEFITS

- **Class 100 (ISO 5) cleanroom compatibility:** Assured cleanliness
- **Latex-free, chemical accelerator-free:** Low allergy risks
- **Robust neoprene formulation:** Durability and chemical splash resistance

Industries

- Pharmaceutical Manufacturing
- Medical Device Manufacturing
- Laboratory Research and Development
- Controlled and Critical Environments
- Production and Manufacturing

Recommended For

- Packaging and labeling
- Clean room cleaning and preparing
- Sample taking and processing

TECHNICAL DATA SHEET


| | Product Information |
|--|--|
| Material | Neoprene (Polychloroprene) |
| Color | Cream |
| Shape | Anatomic with Curved Fingers |
| Cuff | Beaded with SUREFIT™ Technology |
| Manufacturing/QMS Audit Standards | ISO 9001:2015 |
| Regulatory/Standard Compliance | AS/NZS 4179, ASTM D3577, ASTM D7160, CE 0493, EN ISO 21420:2020, EN ISO 374-1:2016 Type B (KLT), EN ISO 374-5:2016, EN 421:2010, ISO 10282, ISO 11193, ISO 13485, Category III, UKCA |
| Packaging | <p>20 pairs per inner polybag; 1 inner polybag per outer poly bag; 2 outer polybags per bag; 5 bags per master bag; 1 master bag of 200 pairs per carton/case</p> <p>More sustainable packaging: These non-sterile gloves are packed in recyclable plastic packaging* and delivered in recycled cardboard shipper cases.</p> <p>*Inner wrap, pouch, bag and liner are made from polyethylene (PE) based film. Always check your local recyclable status as these materials may not be considered suitable for recycling in your location.</p> |
| Storage | Keep away from direct sunlight; store in a dry place and keep in the original packaging. Keep away from ozone sources. If products are properly stored, as indicated, they won't lose their performances or change characteristics significantly. If products could be affected by ageing or storage, the expiry date is mentioned on the packaging materials. |
| Country of Origin | Sri Lanka |
| Available sizes | 5.5, 6, 6.5, 7, 7.5, 8, 8.5, 9 |
| Powder Content | Powder-Free |
| External Glove Surface | Smooth |
| Internal Glove Surface | Polymer Coated with DERMASHIELD™ Technology |
| Cleanroom Class | Class 100/ISO 5 |
| Shelf Life | 5 Years |
| Tested for use with Chemotherapy Drugs | Yes, in accordance with ASTM D6978 (Not listed in the US FDA 510k) |
| Protein Level | N/A: contains no natural rubber latex |
| Anti-static | No |
| Vulcanization Chemical Accelerators | <ul style="list-style-type: none"> None |

| Physical Properties | | Testing Method |
|--|-------------|---------------------|
| Typical Length (mm/in) | 300 / 12 | EN 420/ASTM D3767 |
| Freedom from Holes | 0.65 AQL | EN 455-1/ASTM D3577 |
| Typical Particle Count $\geq 0.5\mu\text{m}$ (counts / cm^2) | < 1500 | IEST-RP-CC005.4 |
| Target Single Wall Palm Thickness (mm/mil) | 0.15 / 5.90 | EN 420/ASTM D3767 |
| Target Single Wall Finger Thickness (mm/mil) | 0.16 / 6.29 | EN 420/ASTM D3767 |
| Target Single Wall Cuff Thickness (mm/mil) | 0.14 / 5.51 | EN 420/ASTM D3767 |
| Ultimate tensile strength (MPa) Before Aging | 17 | ASTM D412-06a |
| Ultimate tensile strength (MPa) During Aging | 12 | ASTM D412-06a |
| Force at Break (N) Before Aging | 9 | EN 455-2 |
| Force at Break (N) During Aging | 9 | EN 455-2 |

ORDERING INFORMATION

| SIZE | 5.5 | 6 | 6.5 | 7 | 7.5 | 8 | 8.5 | 9 |
|-------------|----------|----------|----------|----------|----------|----------|----------|----------|
| REORDER NO. | 73300055 | 73300060 | 73300065 | 73300070 | 73300075 | 73300080 | 73300085 | 73300090 |

PERFORMANCE STANDARDS AND REGULATORY COMPLIANCE



For additional information visit us at www.ansell.com, or call us at

Europe, Middle East & Africa Region

Ansell Healthcare Europe NV
T: +32 (0) 2 528 74 00
F: +32 (0) 2 528 74 01

Asia Pacific Region

Ansell Global Trading Center
T: +603 8310 6688
F: +603 8310 6699

North America Region

Ansell Healthcare Products LLC
US T: +1 800 800 0444
US F: +1 800 800 0445
CA T: +1-800-363-8340

Latin America & Caribbean Region

Ansell Commercial Mexico S.A. de C.V.
T: +52 442 248 1544 / 248 3133

Australia

Ansell Limited
T: +61 1800 337 041
F: +61 1800 803 578

UK

Ansell Nitritex
T: +44 1638 663338
F: +44 1638 668890

Technology



Pinhole Barrier Technology



Ergonomic Design Technology



Cuff Roll-down Technology



Donning Aid Technology



Ultra Thin Neoprene Technology