

# TouchNTuff™

## 93-250

Dark Grey Disposable Nitrile Glove with Ansell Grip™ Technology

## Tough disposable hand protection offering superior wet, oily and dry grip

- **Reduces gripping effort:** Designed with ANSELL GRIP™ Technology, lab tests show 80% less finger force and 33% less palm force is required to hold objects when wearing these gloves
- **Superior durability and productivity:** The strong material helps increase productivity by preventing slippage when handling wet, dry or oily equipment in tough environments
- **Elevated comfort:** Soft nitrile enhances comfort when wearing gloves during long shifts
- **Prevents surface defects:** Silicone-free, they prevent contaminant transfer that causes flaws in paints, coatings and finishes
- **Reliable chemical splash protection:** TouchNTuff™ 93-250 gloves protect against accidental exposure to a range of acids, bases and solvents



### Industries

- Automotive Aftermarket
- Life Sciences

### Recommended For

- General Purpose Auto Aftermarket
- Spill or leakage cleanup
- Transferring liquids and solids
- Transferring liquids
- Sample taking and processing
- Product shipping, transport and delivery
- Testing
- Oil, fluids and filter change
- Engine transmission and repair
- Maintenance

## TECHNICAL DATA SHEET

|                                     | Product Information                                                                                                                                                                                                                                                                                                                   |
|-------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Material                            | Nitrile                                                                                                                                                                                                                                                                                                                               |
| External Glove Surface              | Textured Fingers                                                                                                                                                                                                                                                                                                                      |
| Audit Standards                     | ISO 9001                                                                                                                                                                                                                                                                                                                              |
| Packaging Overview                  | 100 gloves per dispenser<br>10 dispensers per case<br>1000 gloves per case                                                                                                                                                                                                                                                            |
| Storage Instructions                | Keep out of direct sunlight; store in a cool and dry place. Keep away from sources of ozone or ignition.                                                                                                                                                                                                                              |
| Country Of Origin                   | Portugal                                                                                                                                                                                                                                                                                                                              |
| Product Segmentation                | Robust                                                                                                                                                                                                                                                                                                                                |
| Antistatic                          | Yes EN1149                                                                                                                                                                                                                                                                                                                            |
| Silicone Free                       | Yes                                                                                                                                                                                                                                                                                                                                   |
| Vulcanization Chemical Accelerators | <ul style="list-style-type: none"> <li>• Zinc Dibutyldithiocarbamate (ZDBC)</li> <li>• Zinc 2-mercaptobenzothiazole</li> <li>• Zinc Diethyldithiocarbamate (ZDEC)</li> </ul> <p><i>Only a very small number of users may be sensitive to this ingredient(s) and hence may develop irritant and/or allergic contact reactions.</i></p> |


## PHYSICAL PROPERTIES

|                                         | Typical Values |             | Testing Method      |
|-----------------------------------------|----------------|-------------|---------------------|
| Length (mm/inches)                      | 245 / 9.65     |             | ASTM D3767,EN 420   |
| Freedom from Holes (Inspection level I) | 1.5 AQL        |             | ASTM D5151,EN 455-1 |
| Palm Thickness (mm/mils)                | 0.13 / 5.1     |             | ASTM D3767,EN 420   |
| Finger Thickness (mm/mils)              | 0.20 / 7.9     |             | ASTM D3767,EN 420   |
|                                         | BEFORE AGING   | AFTER AGING |                     |
| Elongation at Break (%)                 | ≥ 590          | ≥ 520       | ASTM D412           |
| Force at break (N)                      | ≥ 10           | ≥ 9         | EN 455-2            |

ORDERING INFORMATION

| Size         | XS (5.5 - 6) | S (6.5 - 7) | M (7.5 - 8) | L (8.5 - 9) | XL (9.5 - 10) |
|--------------|--------------|-------------|-------------|-------------|---------------|
| Product Code | 93250060     | 93250070    | 93250080    | 93250090    | 93250100      |

Performance Standards and Regulatory Compliance



For additional information visit us at [www.ansell.com](http://www.ansell.com), or call us at

**Europe, Middle East & Africa Region**  
Ansell Healthcare Europe NV  
T: +32 (0) 2 528 74 00  
F: +32 (0) 2 528 74 01

**Asia Pacific Region**  
MY: +603 8310 6688  
apac.medical@ansell.com  
CN: +86 21 38275000  
infochina@ansell.com  
JP: +813 5549 8151  
info.medical.jp@ansell.com

**North America Region**  
Ansell Healthcare Products LLC  
T: +1 800 800 0444  
F: +1 800 800 0445

**Latin America & Caribbean Region**  
BR: +55 (11) 3356-3100  
latam.medical@ansell.com  
MX: +52 442 296 2050  
latam.medical@ansell.com  
CO: +57 1 288 3247  
latam.medical@ansell.com

**Australia**  
Ansell Limited  
T: +61 1800 337 041  
F: +61 1800 803 578  
**Russia**  
Ansell PYC  
Ten. +7 495 258 13 16



Ansell, ® and ™ are trademarks owned by Ansell Limited or one of its affiliates. US Patented and US and non-US Patents Pending: [www.ansell.com/patentmarking](http://www.ansell.com/patentmarking) © 2025 Ansell Limited. All Rights Reserved.

Neither this document nor any other statement made herein by or on behalf of Ansell should be construed as a warranty of merchantability or that any Ansell product is fit for a particular purpose. Ansell assumes no responsibility for the suitability or adequacy of an end user's selection of gloves for a specific application.

