

# HyFlex™

## 11-581

Ultra-light cut protection for 4x longer wear



Cut



Light Duty

## Ultra-light ANSI/ISEA 105-2024 A6/ EN ISO F cut protection with FORTIX™ for 4x longer-lasting performance

- **Superior durability:** FORTIX™ Technology delivers 4x higher abrasion resistance for extended performance in abrasive conditions\*
  - **Ultra-light comfort:** 20% lighter design with ANSI/ISEA 105-2024 CUT A6 and EN ISO F protection for high cut resistance and dexterity\*\*
  - **Advanced cut protection:** Next-gen INTERCEPT™ HPPE yarn provides up to 6x greater cut resistance for high-performance hand protection\*\*\*
  - **Excellent grip:** Palm-dipped coating improves grip, while reinforced thumb crotch defends against rapid wear
  - **Touchscreen compatible:** Enables use of touchscreen devices without removing gloves
- \* Comparison is based on Ansell lab tests under standardized conditions in December 2025 versus similar competitive gloves. Results may vary by application.  
\*\* Versus standard ANSI/ISEA 105-2024 CUT A6 and EN ISO F rated gloves  
\*\*\* Versus similar gloves made of standard HPPE yarn



### Industries

- Automotive
- Manufacturing

### Applications

- Light duty stamping
- Handling sharp metal parts
- Assembly of sharp parts
- Maintenance

# HyFlex™

## 11-581

Ultra-light cut protection for 4x longer wear

### Key Features

- ♦ **Longer wear life:** FORTIX™ Technology for 4x longer use\*
- ♦ **Ultra-light design:** 20% lighter for greater dexterity\*\*
- ♦ **Comfort & convenience:** Touchscreen compatible, flexible all-day wear

\* Comparison is based on Ansell lab tests under standardized conditions in December 2025 versus similar competitive gloves. Results may vary by application.

\*\* Versus standard ANSI/ISEA 105-2024 CUT A6 and EN ISO F gloves.

### Technologies

 **FORTIX™**  
Abrasion Resistance Technology

 **INTERCEPT™**  
Cut Resistance Technology



**Touchscreen Compatible**



DMF free

### Performance Standards & Regulatory Compliance

ANSI/ISEA 105-2024



EN388: 2016



3X42F

EN 388



3X42F

EN 16350



STANDARD 100  
1408033

### Specifications

BRAND   STYLE	DESCRIPTION	Gauge	SIZE	LENGTH	COATING COLOR	PACKAGE
HyFlex™ 11-581	<b>Finishing:</b> Palm dipped, Thumbcrotch reinforcement <b>Coating Material:</b> Nitrile <b>Liner Material:</b> INTERCEPT™ reinforced HPPE yarn <b>Cuff Style:</b> Knitwrist	21	6, 7, 8, 9, 10, 11, 12	225-278 mm / 8.86-10.94 inches	Black	• 12 pairs/bag, 12 bags/carton

For additional information visit us at [www.ansell.com](http://www.ansell.com), or call us at

#### Europe, Middle East & Africa Region

Ansell Healthcare Europe NV  
Riverside Business Park  
Blvd International, 55  
1070 Brussels, Belgium  
T: +32 (0) 2 528 74 00  
F: +32 (0) 2 528 74 01

#### North America Region

Ansell Healthcare Products LLC  
111 Wood Avenue South,  
Suite 900  
Iselin, NJ 08830, USA  
T: +1 800 800 0444  
F: +1 800 800 0445

#### Australia

Ansell Limited  
Level 3, 678 Victoria Street,  
Richmond, Vic, 3121  
Australia  
T: +61 1800 337 041  
F: +61 1800 803 578

#### Asia Pacific Region

Ansell Global Trading Center  
(Malaysia) Sdn Bhd  
Prima 6, Prima Avenue  
Block 3512, Jaijan Teknokrat 6  
T: +603 8310 6688  
F: +603 8310 6699

#### Latin America & Caribbean Region

Ansell Commercial Mexico S.A. de C.V.  
Blvd. Bernardo Quintana No. 7001-C,  
Q7001 Torre II,  
Suites 1304, 1305 y 1306,  
Col. Centro Sur, c.p. 76079  
Queretaro, Qro. Mexico  
T: +52 442 248 1544 / 248 3133

#### Canada

Ansell Canada  
105 Lauder  
Cowansville, QC J2K 2K8  
Canada  
T: +1 800 363 8340  
F: +1 800 267 3551

Ansell, ® and ™ are trademarks owned by Ansell Limited or one of its affiliates. US Patented and US and non-US Patents Pending: [www.ansell.com/patentmarking](http://www.ansell.com/patentmarking) © 2025 Ansell Limited. All Rights Reserved.

Neither this document nor any other statement made herein by or on behalf of Ansell should be construed as a warranty of merchantability or that any Ansell product is fit for a particular purpose. Ansell assumes no responsibility for the suitability or adequacy of an end user's selection of gloves for a specific application.

