

85-304
Non-clean/Non-sterile CSM
RABS/Isolator Gloves

Chemical-resistant cleanroom gloves, offering hard-wearing personal protection

Port size: 305mm/12"
Thickness: 0.4mm/16 mil

- Specialized defenses: Ansell's AlphaTec® CSM Isolator Glove 85-304 is highly resistant against concentrated acids and bases, ensuring advanced workplace safety and the prevention of workplace injuries
- Elevated comfort: These cleanroom gloves are made from soft, flexible material, resulting in comfortable, easyto-use CSM gloves
- Optimized glove life: The AlphaTec® CSM Isolator Glove 85-304 is designed to withstand exposure to oxygen, UV rays and ozone without rapidly aging
- Limited contamination risks: These isolator gloves' white color also makes contamination easier to detect

KEY FEATURES & BENEFITS

- Sturdy CSM composition: Protection from concentrated acids and bases
- Flexible material: For softness, comfort and everyday usability
- **Durable design:** Resistant against oxygen, UV ray and ozone exposure







85-304Non-clean/Non-sterile CSM RABS/Isolator Gloves

TECHNICAL DATA SHEET

| Product Reference | 85-304 |
|------------------------|--|
| Material | Chlorosulfonated polyethylene_CSM |
| Color | White |
| Shape | Ambidextrous |
| External Glove Surface | Smooth |
| Cuff Style | Beaded |
| Storage Instructions | Store in a dry and dark environment, temperature of 5°C to 22°C. Retain in original packaging when not in use. |
| Available Sizes | 11, 9.5 |
| Temperature Range | From -20°C to 120°C |
| Shelf Life | Three (3) years from date of manufacture. |
| Standards | CE 0493, EN ISO 374-5:2016, EN 388:2016 +A1:2018, EN ISO 21420:2020, EN ISO 374-1:2016 Type B, Category III, UKCA |





85-304 Non-clean/Non-sterile CSM **RABS/Isolator Gloves**

PHYSICAL PROPERTIES

| | Typical Values | Testing Method |
|---|----------------|----------------|
| Typical Length (mm/in) | 800 / 32 | EN ISO 21420 |
| Port Size | 305mm/12" | |
| | | |
| | | |
| Target Single Wall Palm Thickness (mm/mil) | 0.4 / 16 | EN 455-2 |
| Target Single Wall Cuff Thickness (mm/mil) | 0.4 / 16 | EN 455-2 |

PROTECTION AGAINST MECHANICAL RISKS, EN 388:2016+A1:2018

| Risk | Performance level | |
|--------------------------|-------------------|--|
| Abrasion Resistance | Level 3 | |
| Blade Cut Resistance | Level 1 | |
| Tear Resistance | Level O | |
| Puncture Resistance | Level 1 | |
| ISO 13997 Cut Resistance | Level A | |

ORDERING INFORMATION

| | PORT SIZE | 12"/305mm | 12"/305mm |
|--------|-------------|-----------|-----------|
| | SIZE | 9.5 | 11 |
| 85-304 | REORDER NO. | 85304095 | 85304110 |

Performance Standards and Regulatory Compliance









For additional information visit us at www.ansell.com, or call us at

Europe, Middle East & Africa Region

Ansell Healthcare Europe NV T: +32 (0) 2 528 74 00 F: +32 (0) 2 528 74 01

Asia Pacific Region

Ansell Global Trading Center T: +603 8310 6688 F: +603 8310 6699

North America Region

Ansell Healthcare Products LLC US T: +1 800 800 0444 US F: +1 800 800 0445 CA T: +1-800-363-8340

Latin America & Caribbean Region

Ansell Commercial Mexico S.A. de C.V. T: +52 442 248 1544 / 248 3133

Australia

Ansell Limited T: +61 1800 337 041 F: +61 1800 803 578

UK

Ansell Nitritex T: +44 1638 663338 F: +44 1638 668890

Ansell, ® and ™ are trademarks owned by Ansell Limited or one of its affiliates. US Patented and US and non-US Patents Pending: www.ansell.com/patentmarking © 2025 Ansell Limited. All Rights Reserved.



Neither this document nor any other statement made herein by or on behalf of Ansell should be construed as a warranty of merchantability or that any Ansell product is fit for a particular purpose. Ansell assumes no responsibility for the suitability or adequacy of an end user's selection of gloves for a specific application.