

# HyFlex™

## 11-926

Light duty oil repellent, oil grip multi-purpose glove



Oil

Low Chemical Protection



Light Duty

## Lightweight abrasion-resistant gloves with advanced oil-repellent capabilities

- **Specialized protection:** HyFlex™ 11-926 industrial safety gloves possess a RIPEL™ Liquid Repellence surface barrier, which prevents skin contact with oil or chemicals, ensuring workplace safety
- **Enhanced grip:** These HyFlex™ gloves' three quarter-dipped coating and force-minimizing ANSELL GRIP™ treatment enhances their grip performance
- **Increased flexibility:** HyFlex™ 11-926 industrial gloves' ergonomic hand shape and lightweight liner help diminish hand fatigue by making them flexible and maneuverable
- **Elevated comfort:** Spandex™ and nylon combine to grant the HyFlex™ 11-926's liner a "second skin" feel, for light, comfortable handling
- **Improved durability:** HyFlex™ 11-926 industrial working gloves achieve ANSI/ISEA 105-2024 ABRASION LEVEL 3 and EN ABRASION LEVEL 4 standards, for long-lasting wear



### Industries

- Automotive
- Machinery and Equipment
- Agriculture

### Applications

- Metalworking & assembly operations
- Picking, fastening components
- Production line support & maintenance
- Assembling and mounting components
- Loading and unloading rough parts or boxes
- Changing tools and dies
- Final assembly
- Assembly & inspection of components
- Assembly and disassembly of equipment
- Warehousing of raw materials
- Loading and unloading trucks and vehicles
- Handling incoming goods
- Opening furnaces draining pumps valves or lines and crackers BTX process

# HyFlex™

## 11-926

Light duty oil repellent, oil grip multi-purpose glove

### Key Features

- ◆ **RIPEL™ Liquid Repellence:** Safety gloves adapted to oily conditions
- ◆ **Three-quarter dipping:** For protective coating with secure grip
- ◆ **Lightweight fine-gauge liner:** Offering flexibility and comfort

### Technologies

 **ANSELL GRIP™**  
Ansell Grip Technology

 **RIPEL™**  
Liquid Repellence Technology

### Performance Standards & Regulatory Compliance

ANSI/ISEA 105-2024



EN388: 2016



4121A



ISO 18889

EN 388



4121

EN 388



4121A



### Specifications

BRAND   STYLE	DESCRIPTION	Gauge	SIZE	LENGTH	COATING COLOR	PACKAGE
HyFlex™ 11-926	<b>Finishing:</b> 3/4 Coated <b>Coating Material:</b> Nitrile <b>Liner Material:</b> Nylon <b>Cuff Style:</b> Knitwrist	18	6, 7, 8, 9, 10, 11	225-270 mm / 8.86-10.62 inches	Purple	• 12 pairs/bag, 12 bags/carton

For additional information visit us at [www.ansell.com](http://www.ansell.com), or call us at

#### Europe, Middle East & Africa Region

Ansell Healthcare Europe NV  
Riverside Business Park  
Blvd International, 55  
1070 Brussels, Belgium  
T: +32 (0) 2 528 74 00  
F: +32 (0) 2 528 74 01

#### North America Region

Ansell Healthcare Products LLC  
111 Wood Avenue South,  
Suite 900  
Iselin, NJ 08830, USA  
T: +1 800 800 0444  
F: +1 800 800 0445

#### Australia

Ansell Limited  
Level 3,678 Victoria Street,  
Richmond, Vic, 3121  
Australia  
T: +61 1800 337 041  
F: +61 1800 803 578

#### Asia Pacific Region

Ansell Global Trading Center  
(Malaysia) Sdn Bhd  
Prima 6, Prima Avenue  
Block 3512, Jaijan Teknokrat 6  
T: +603 8310 6688  
F: +603 8310 6699

#### Latin America & Caribbean Region

Ansell Commercial Mexico S.A. de C.V.  
Blvd. Bernardo Quintana No. 7001-C,  
Q7001 Torre II,  
Suites 1304, 1305 y 1306,  
Col. Centro Sur, c.p. 76079  
Queretaro, Qro. Mexico  
T: +52 442 248 1544 / 248 3133

#### Canada

Ansell Canada  
105 Lauder  
Cowansville, QC J2K 2K8  
Canada  
T: +1 800 363 8340  
F: +1 800 267 3551

Ansell, ® and ™ are trademarks owned by Ansell Limited or one of its affiliates. US Patented and US and non-US Patents Pending: [www.ansell.com/patentmarking](http://www.ansell.com/patentmarking) © 2025 Ansell Limited. All Rights Reserved.

Neither this document nor any other statement made herein by or on behalf of Ansell should be construed as a warranty of merchantability or that any Ansell product is fit for a particular purpose. Ansell assumes no responsibility for the suitability or adequacy of an end user's selection of gloves for a specific application.

