

## Durable disposable gloves for extended wear time

- **Durability:** Robust design allows for longer wear time in a variety of heavy-duty jobs
- **Secure grip:** Fully textured for a firm, safe grip in dry and wet environments
- **Genuine versatility:** Designed for heavy-duty jobs across industries, and available in a broad range of sizes through online retailers
- **Cost-effective:** Durable protection offered at excellent value
- **Food handling compliance:** Suitable for a wide range of food handling applications, as per GB 4806.11 (contact time with foodstuffs at 40°C/104°F, for a maximum of 30 minutes)



### Industries

- Agriculture
- Food Processing

### Recommended For

- Food processing and handling
- Handling of machined parts coated with light oil
- Lab work, blending, compounding, filling, cleaning
- Maintenance and equipment clean up
- Mechanical jobs
- Handling of paint/glue guns and sprayers
- Equipment repair and maintenance
- Fastening, screwing, unscrewing parts

# TECHNICAL DATA SHEET

Product Information	
<b>Material</b>	Nitrile
<b>External Glove Surface</b>	Fully Textured
<b>Audit Standards</b>	ISO 13485, ISO 9001
<b>Product Certification</b>	Medical Device Regulation (EU) 2017/745 Class I, Personal Protective Equipment Regulation (EU) 2016/425 Category III risks, Arrêté du 09/04/04, EC 2002/72, EU Food Contact Approved, EC 2023/2006, ASTM D6319, CE 0493, EAC TP TC 019:2011, FDA21 CFR 177-2600-US Food Contact Approved, EN ISO 21420:2020, EN ISO 374-1:2016 Type B JKPT, EN ISO 374-5:2016 Virus, ISO 13485, ISO 9001, UKCA
<b>Packaging Overview</b>	500 gloves per dispenser 50 dispensers per case
<b>Storage Instructions</b>	Keep out of direct sunlight; store in a cool and dry place. Keep away from sources of ozone or ignition.
<b>Country Of Origin</b>	Malaysia
<b>Product Segmentation</b>	Robust
<b>Antistatic</b>	No
<b>Silicone Free</b>	Yes

## PHYSICAL PROPERTIES

	Typical Values		Testing Method
	BEFORE AGING	AFTER AGING	
Length (mm/inches)	240 / 9.45		ASTM D3767,EN 420
Freedom from Holes (Inspection level I)	1.5 AQL		ASTM D5151,EN 374-2
Palm Thickness (mm/mils)	0.17/6.7		ASTM D3767,EN 420
Finger Thickness (mm/mils)	0.19/7.5		ASTM D3767,EN 420
Elongation at Break (%)	500	400	ASTM D412-06a
Force at break (N)	8	8	EN 455-2

## ORDERING INFORMATION

Size	S (6.5 - 7)	M (7.5 - 8)	L (8.5 - 9)
Product Code	10135070	10135080	10135090

### Performance Standards and Regulatory Compliance



### For additional information visit us at [www.ansell.com](http://www.ansell.com), or call us at

#### Europe, Middle East & Africa Region

Ansell Healthcare Europe NV  
 T: +32 (0) 2 528 74 00  
 F: +32 (0) 2 528 74 01

#### Asia Pacific Region

MY: +603 8310 6688  
 apac.medical@ansell.com  
 CN: +86 21 38275000  
 infochina@ansell.com  
 JP: +813 5549 8151  
 info.medical.jp@ansell.com

#### North America Region

Ansell Healthcare Products LLC  
 T: +1 800 800 0444  
 F: +1 800 800 0445

#### Latin America & Caribbean Region

BR: +55 (11) 3356-3100  
 latam.medical@ansell.com  
 MX: +52 442 296 2050  
 latam.medical@ansell.com  
 CO: +57 1 288 3247  
 latam.medical@ansell.com

#### Australia

Ansell Limited  
 T: +61 1800 337 041  
 F: +61 1800 803 578

#### Russia

Ansell PYC  
 Ten. +7 495 258 13 16

Ansell, ® and ™ are trademarks owned by Ansell Limited or one of its affiliates. US Patented and US and non-US Patents Pending;  
[www.ansell.com/patentmarking](http://www.ansell.com/patentmarking) © 2025 Ansell Limited. All Rights Reserved.

Neither this document nor any other statement made herein by or on behalf of Ansell should be construed as a warranty of  
 merchantability or that any Ansell product is fit for a particular purpose. Ansell assumes no responsibility for the suitability or adequacy of  
 an end user's selection of gloves for a specific application.

