

Latex exam gloves with exceptional fit and feel for extended wear

- **Secure grip:** MICROFLEX™ 63-854 disposable latex gloves are fully textured for a secure grip, and in both wet or dry environments
- **Tactile sensitivity:** Excellent tactile sensitivity ensures precise handling of sensitive or delicate items, such as laboratory instruments
- **Comfortable and elastic fit:** Superior elasticity means gloves move with you for greater comfort
- **Outstanding quality:** Exceeds standards for tensile strength, elasticity/elongation and other quality standards for average latex gloves



***CAUTION:** This product contains natural rubber latex, which may cause allergic reactions

Industries

- Food Processing
- Life Sciences
- Healthcare

Recommended For

- All food processing, applications that have food contact
- Sample taking and processing
- Equipment repair and maintenance
- Extra comfort during long, sustained procedures

TECHNICAL DATA SHEET

	Product Information
Material	Natural Rubber Latex
External Glove Surface	Fully Textured
Audit Standards	ISO 13485
Product Certification	Personal Protective Equipment Regulation (EU) 2016/425 Category III risks, CE 0493, Medical Device Regulation (EU) 2017/745 Class I, European Directive 89/686/EEC, ASTM D3578, EU Food Contact Approved, EC 2023/2006, EN 455 1-4, EN ISO 21420:2020, EN ISO 374-1:2016 Type B KPT, EN ISO 374-5:2016 Virus, FDA21 CFR 177-2600-US Food Contact Approved, ISO 13485, UKCA, PMDA Notification Number: 13B3X10307AH0002, Trade Name: Ansell Latex Medical Examination Glove
Packaging Overview	100 Gloves Per Dispenser 10 Dispensers Per Case 1000 Gloves Per Case
Storage Instructions	Keep out of direct sunlight; store in a cool and dry place. Keep away from sources of ozone or ignition.
Country Of Origin	Malaysia
Antistatic	Not Tested
Silicone Free	Yes


PHYSICAL PROPERTIES

	Typical Values		Testing Method
Length (mm/inches)	245 / 9.65		ASTM D3767,EN 420
Freedom from Holes (Inspection level I)	1.5 AQL		ASTM D5151,EN 455-1
Palm Thickness (mm/mils)	0.13 / 5.1		ASTM D3767,EN 420
Finger Thickness (mm/mils)	0.16 / 6.3		ASTM D3767,EN 420
	BEFORE AGING	AFTER AGING	
Elongation at Break (%)	≥ 700	≥ 600	ASTM D412
Force at break (N)	9	6	EN 455-2

ORDERING INFORMATION

Size	XS (5.5 - 6)	S (6.5 - 7)	M (7.5 - 8)	L (8.5 - 9)	XL (9.5 - 10)
Product Code	63854060	63854070	63854080	63854090	63854100

Performance Standards and Regulatory Compliance



For additional information visit us at www.ansell.com, or call us at

Europe, Middle East & Africa Region Ansell Healthcare Europe NV T: +32 (0) 2 528 74 00 F: +32 (0) 2 528 74 01 Asia Pacific Region MY: +603 8310 6688 apac.medical@ansell.com CN: +86 21 38275000 infochina@ansell.com JP: +813 5549 8151 info.medical.jp@ansell.com	North America Region Ansell Healthcare Products LLC T: +1 800 800 0444 F: +1 800 800 0445 Latin America & Caribbean Region BR: +55 (11) 3356-3100 latam.medical@ansell.com MX: +52 442 296 2050 latam.medical@ansell.com CO: +57 1 288 3247 latam.medical@ansell.com	Australia Ansell Limited T: +61 1800 337 041 F: +61 1800 803 578 Russia Ansell PYC Ten. +7 495 258 13 16
---	--	--

Ansell, ® and ™ are trademarks owned by Ansell Limited or one of its affiliates. US Patented and US and non-US Patents Pending: www.ansell.com/patentmarking © 2025 Ansell Limited. All Rights Reserved.

Neither this document nor any other statement made herein by or on behalf of Ansell should be construed as a warranty of merchantability or that any Ansell product is fit for a particular purpose. Ansell assumes no responsibility for the suitability or adequacy of an end user's selection of gloves for a specific application.

