

94-242 Static Dissipative

Disposable static dissipative gloves

Gloves that reduce risk of fire, explosion, or damage caused by electrostatic discharge

- Ansell's first disposable static dissipative gloves: MICROFLEX® 94-242 gloves reduce the risk of electrostatic discharge, which can cause spontaneous combustion in atmospheric explosive environments
- Low vertical resistivity: Proprietary nitrile formulation infused with an engineered material that channels electricity through the glove polymer, for a low vertical resistance below 108 Ω
- Advanced protection: Made with TNT™ Chemical Splash Resistance Technology for soft, durable protection against a wide range of chemicals
- Touchscreen compatibility: Provides capacitive and resistive touchscreen capability when working with industrial electronics
- Improved visibility: Black color provides contrast against potentially combustible dust, while hiding the appearance of oils, dirt and stains
- Certified harm-free: Dermatest® certification ensures these PPE gloves are skin-friendly



Industries

- Aerospace
- Electronics
- Food Processing
- Life Sciences
- Manufacturing
- Infrastructure Maintenance

Recommended For

- Handling chemicals and cleaning materials
- Handling of tools
- Equipment, maintenance and repair
- Food processing and handling
- Unpacking of bulk goods
- Product shipping, transport and delivery
- Packaging and labeling
- Oil, fluids and filter change
- Inspection of parts, equipment



TECHNICAL DATA SHEET

	Product Information		
Material	Nitrile		
External Glove Surface	Textured Fingers		
Audit Standards	ISO 13485, ISO 14001, ISO 9001		
Product Certification	Personal Protective Equipment Regulation (EU) 2016/425, Arrette du 05/08/2020, EU Food Contact Approved, EC 2023/2006, ASTM D6319, Dermatest, EN 16350:2014, EN ISO 21420:2020, EN ISO 374-1:2016 Type B JKPT, EN ISO 374-5:2016 Virus, FDA21 CFR 177-2600-US Food Contact Approved, Personal Protective Equipment Regulation (EU) 2016/425 Category III risks, UKCA, CE		
Packaging Overview	Case Per Carton=1000 gloves Per 10 Dispensers Dispenser=100 gloves		
Storage Instructions	Keep out of direct sunlight; store in a cool and dry place. Keep away from sources of ozone or ignition.		
Product Segmentation	Robust		
Antistatic	Yes EN1149 + EN16350		
Silicone Free	Yes		

PHYSICAL PROPERTIES

	Typical	Testing Method	
Length (mm/inches)	245 /	EN ISO 21420	
Freedom from Holes (Inspection level I)	1.5 A	EN 374-2	
	BEFORE AGING	AFTER AGING	
Elongation at Break (%)	≥500	≥400	ASTM D412
Force at break (N)	≥6	≥6	EN 455-2

ORDERING INFORMATION

Size	S (6.5 - 7)	M (7.5 - 8)	L (8.5 - 9)	XL (9.5 - 10)	XXL (10.5 - 11)
Product Code	94242070	94242080	94242090	94242100	94242110

Performance Standards and Regulatory Compliance















For additional information visit us at www.ansell.com, or call us at Europe, Middle East & Africa Region North America Region Australia

Ansell Healthcare Products LLC

Europe, Middle East & Africa Region Ansell Healthcare Europe NV T: +32 (0) 2 528 74 00 F: +32 (0) 2 528 74 01

Asia Pacific Region MY +603 8310 6688 apac.medical@ansell.com CN: +86 21 38275000 infochina@ansell.com JP: +813 5549 8151 T: +1 800 800 0444
F: +1 800 800 0445

Latin America & Caribbean Region
BR +55 (11) 3356-3100
latam.medical@ansell.com
MX: +52 442 296 2050
latam.medical@ansell.com
CO: +57 1 288 3247
latam.medical@ansell.com

Australia
Ansell Limited
T: +61 1800 337 041
F: +61 1800 803 578
Russia

Ansell PYC Ten. +7 495 258 13 16

Technology





Ansell, ® and ™ are trademarks owned by Ansell Limited or one of its affiliates. US Patented and US and non-US Patents Pending: www.ansell.com/patentmarking © 2025 Ansell Limited. All Rights Reserved.

Neither this document nor any other statement made herein by or on behalf of Ansell should be construed as a warranty of merchantability or that any Ansell product is fit for a particular purpose. Ansell assumes no responsibility for the suitability or adequacy of an end user's selection of gloves for a specific application.

