

# MidKnight® MK-296

Distinctive, Black Nitrile Exam Glove

## Black nitrile exam gloves with superior grip

- Masks stains: MICROFLEX® MidKnight® MK-296 exam gloves' black color disguises dirt while enhancing the visibility of light-colored objects
- Enhanced grip: A fully textured, nonfoaming design offers these powderand silicone-free nitrile gloves superior grip
- Genuine versatility: These gloves are suitable for various applications, used notably by auto mechanics, maintenance workers and law enforcement officers
- Food handling compliant: Also ideal for a wide range of food handling applications



#### **Industries**

- Automotive
- Automotive Aftermarket
- Life Sciences
- Machinery and Equipment
- Healthcare
- Emergency Medical Services
- Utilities
- Warehousing

#### **Recommended For**

- Inspection, selecting, checking parts
- General Purpose Auto Aftermarket
- Use of cleaning tools and robotic equipment
- Oil, fluids and filter change
- Engine transmission and repair
- Tire rotation & changes
- Maintaining lab furniture and equipment
- Sample taking and processing
- Blending, compounding solids and liquids
- Raw material sample collection
- Weighing and dispensing of solid and liquid raw materials
- Inspection (picking, checking and marking)
- Standard, moderate risk examination procedures
- Protection from Type I latex allergy in HCW's or patients



## **TECHNICAL DATA SHEET**

	Product Information	
Material	Nitrile	
External Glove Surface	Fully Textured	
Audit Standards	ISO 13485:2003	
Product Certification	ASTM D6319, EN 1149-1/2/3, EN ISO 21420:2020, FDA21 CFR 177-2600-US Food Contact Approved, US QSR/FDA 510(k) Medical Examination Grade, EU Food Contact Approved, ISO 11193	
Packaging Overview	100 gloves per dispenser 10 dispensers per case 1000 gloves per case  Also available in retail packs 10 gloves per pack 50 packs per carton/case	
Storage Instructions	Keep out of direct sunlight; store in a cool and dry place. Keep away from sources of ozone or ignition.	
Country Of Origin	Malaysia	
<b>Product Segmentation</b>	Robust	
Antistatic	Yes	
Silicone Free	Yes	

## **PHYSICAL PROPERTIES**

	Typical	Testing Method	
Length (mm/inches)	245 /	ASTM D3767,EN 420	
Freedom from Holes (Inspection level I)	1.5 A	ASTM D5151,EN 455-1	
Palm Thickness (mm/mils)	0.11/	ASTM D3767,EN 420	
Finger Thickness (mm/mils)	0.15/6.0		ASTM D3767,EN 420
	<b>BEFORE AGING</b>	AFTER AGING	
Ultimate Tensile Strength (MPa)	24	20	ASTM D412 & D573
Elongation at Break (%)	600	500	ASTM D412
Force at break (N)	7	6	EN 455-2

#### ORDERING INFORMATION

Size	XS (5.5 - 6)	S (6.5 - 7)	M (7.5 - 8)	L (8.5 - 9)	XL (9.5 - 10)	XXL (10.5 - 11)
<b>Product Code</b>	MK-296-XS	MK-296-S	MK-296-M	MK-296-L	MK-296-XL	MK-296-XXL

## **Performance Standards and Regulatory Compliance**



## For additional information visit us at www.ansell.com, or call us at

Europe, Middle East & Africa Region Ansell Healthcare Europe NV T: +32 (0) 2 528 74 00 F: +32 (0) 2 528 74 01

Asia Pacific Region MY +603 8310 6688 apac.medical@ansell.com CN: +86 21 38275000 JP: +813 5549 8151

North America Region Ansell Healthcare Products LLC T: +1 800 800 0444 F: +1 800 800 0445

Latin America & Caribbean Region BR +55 (11) 3356-3100 latam.medical@ansell.com MX: +52 442 296 2050 latam.medical@ansell.com CO: +57 1 288 3247 latam.medical@ansell.com

Ansell Limited T: +61 1800 337 041 F: +61 1800 803 578

Russia Ansell PYC Ten. +7 495 258 13 16

Ansell, ® and ™ are trademarks owned by Ansell Limited or one of its affiliates. US Patented and US and non-US Patents Pending: www.ansell.com/patentmarking © 2025 Ansell Limited. All Rights Reserved.

