

## Nitrile disposable gloves offering extended chemical splash protection

- **Strong formulation:** MICROFLEX™ Supreno™ Plus 93-753 gloves' robust nitrile formulation makes them more durable and resistant to rips, snags and tears
- **Real-world performance:** These robust disposable gloves boast EN ISO Type B chemical splash protection, making them suitable for professionals in high-risk environments
- **Low AQL:** MICROFLEX™ Supreno™ Plus 93-753 gloves' low 0.65 AQL reinforces their barrier integrity
- **Extended protection:** Featuring an extended cuff, these gloves offer forearm and wrist protection for workers



### Industries

- Automotive
- Automotive Aftermarket
- Life Sciences

### Recommended For

- General Purpose Auto Aftermarket
- Tire rotation & changes
- Sample taking and processing
- Raw material sample collection
- Maintaining lab furniture and equipment
- Inspection, selecting, checking parts
- Assembly and inspection of components
- Picking and fastening components
- Equipment repair and maintenance
- Animal care feeding and cleanup
- Administering drugs
- Extra protection over the wrist and arm

# TECHNICAL DATA SHEET

Product Information	
<b>Material</b>	Nitrile
<b>External Glove Surface</b>	Textured Fingers
<b>Audit Standards</b>	ISO 13485, ISO 9001
<b>Product Certification</b>	ASTM D6319, Category III, European Directive 89/686/EEC, EN 1149-1/2/3, EN ISO 374-5:2016 Virus, EN ISO 374-1:2016 Type B KPT, EN ISO 21420:2020, ISO 11193, ISO 13485, ISO 9001
<b>Packaging Overview</b>	50 gloves per dispenser 10 dispensers per case 500 gloves per case
<b>Storage Instructions</b>	Keep out of direct sunlight; store in a cool and dry place. Keep away from sources of ozone or ignition.
<b>Country Of Origin</b>	Malaysia
<b>Product Segmentation</b>	High Risk
<b>Antistatic</b>	Yes
<b>Silicone Free</b>	No

## PHYSICAL PROPERTIES

	Typical Values		Testing Method
Length (mm/inches)	295 / 11.6		ASTM D3767,EN 420
Freedom from Holes (Inspection level I)	0.65 AQL		ASTM D5151,EN 374-2
Palm Thickness (mm/mils)	0.14 / 5.5		ASTM D3767,EN 420
Finger Thickness (mm/mils)	0.22 / 8.7		ASTM D3767,EN 420
	<b>BEFORE AGING</b>	<b>AFTER AGING</b>	
Elongation at Break (%)	550	500	ASTM D412
Force at break (N)	15	12	EN 455-2

## ORDERING INFORMATION

Size	S (6.5 - 7)	M (7.5 - 8)	L (8.5 - 9)	XL (9.5 - 10)
Product Code	93753070	93753080	93753090	93753100

### Performance Standards and Regulatory Compliance



### For additional information visit us at [www.ansell.com](http://www.ansell.com), or call us at

#### Europe, Middle East & Africa Region

Ansell Healthcare Europe NV  
T: +32 (0) 2 528 74 00  
F: +32 (0) 2 528 74 01

#### Asia Pacific Region

MY: +603 8310 6688  
apac.medical@ansell.com  
CN: +86 21 38275000  
infochina@ansell.com  
JP: +813 5549 8151  
info.medical.jp@ansell.com

#### North America Region

Ansell Healthcare Products LLC  
T: +1 800 800 0444  
F: +1 800 800 0445

#### Latin America & Caribbean Region

BR: +55 (11) 3356-3100  
latam.medical@ansell.com  
MX: +52 442 296 2050  
latam.medical@ansell.com  
CO: +57 1 288 3247  
latam.medical@ansell.com

#### Australia

Ansell Limited  
T: +61 1800 337 041  
F: +61 1800 803 578

#### Russia

Ansell PYC  
Ten. +7 495 258 13 16

Ansell, ® and ™ are trademarks owned by Ansell Limited or one of its affiliates. US Patented and US and non-US Patents Pending; [www.ansell.com/patentmarking](http://www.ansell.com/patentmarking) © 2025 Ansell Limited. All Rights Reserved.

Neither this document nor any other statement made herein by or on behalf of Ansell should be construed as a warranty of merchantability or that any Ansell product is fit for a particular purpose. Ansell assumes no responsibility for the suitability or adequacy of an end user's selection of gloves for a specific application.

