

Offers excellent dexterity and comfortable hand protection with an ergonomic design

- **Heightened tactility and comfort:** These soft, thin nitrile gloves reliably protect while offering exceptional fit and tactility for jobs requiring fine motor control
- **ERGOFORM™ Technology:** Proven to reduce the amount of muscle effort wearers exert while performing repetitive tasks when compared to similar disposable nitrile gloves*
- **Food handling compliance:** Suitable for a wide variety of food handling scenarios
- **Smart-packed:** Smartly packed with 300 gloves per dispenser box**
- **Available in half sizes:** Available in XS/S, S/M, M/L in addition to normal sizes to ensure a perfect fit



*based on lab tests conducted by US Ergo and commissioned by Ansell

**size XL is packed with 250 gloves per dispenser box

Industries

- Food Processing
- Life Sciences
- Healthcare
- Agriculture
- Automotive
- Utilities
- Warehousing

Recommended For

- Protection from Type I latex allergy in HCW's or patients
- Enhanced tactile sensitivity and dexterity, especially for delicate procedures
- Brief, low-risk examination procedures
- Extra comfort during long, sustained procedures
- Plant disinfection and sanitization
- All food processing, applications that have food contact
- Assembly of parts
- Sample taking and processing
- Extra comfort during long, sustained procedures

TECHNICAL DATA SHEET

	Product Information
Material	Nitrile
External Glove Surface	Textured Fingers
Audit Standards	EN ISO 13485:2012
Product Certification	Korean Standard
Packaging Overview	300 gloves per dispenser 10 dispensers per case 3000 gloves per case *250 gloves per dispenser (Size XL) *2500 gloves per case (Size XL)
Storage Instructions	Keep out of direct sunlight; store in a cool and dry place. Keep away from sources of ozone or ignition.
Country Of Origin	China
Product Segmentation	High Touch
Antistatic	No
Silicone Free	No

PHYSICAL PROPERTIES

	Typical Values		Testing Method
Length (mm/inches)	230 / 9.1		ASTM D3767,EN 420
Freedom from Holes (Inspection level I)	1.5 AQL		ASTM D5151,EN 455-1
Palm Thickness (mm/mils)	0.06/2.4		ASTM D3767,EN 420
Finger Thickness (mm/mils)	0.10/3.9		ASTM D3767,EN 420
	BEFORE AGING	AFTER AGING	
Ultimate Tensile Strength (MPa)	23	≥ 14	ASTM D412 & D573
Elongation at Break (%)	≥ 500	≥ 400	ASTM D412
Force at break (N)	≥ 3	≥ 3	

ORDERING INFORMATION

Size	XS (5.5 - 6)	XS-S (5.5- 7.0)	S (6.5 - 7)	S/M (7.5)	M (7.5 - 8)	M-L (7.5- 9.0)	L (8.5 - 9)	XL (9.5 - 10)
Product Code	UF-524-XS	UF-524-XSS	UF-524-S	UF-524-SM	UF-524-M	UF-524-ML	UF-524-L	UF-524-XL

For additional information visit us at www.ansell.com, or call us at

Europe, Middle East & Africa Region
Ansell Healthcare Europe NV
T: +32 (0) 2 528 74 00
F: +32 (0) 2 528 74 01

Asia Pacific Region
MY +603 8310 6688
apac.medical@ansell.com
CN: +86 21 38275000
infochina@ansell.com
JP: +813 5549 8151
info.medical.jp@ansell.com

North America Region
Ansell Healthcare Products LLC
T: +1 800 800 0444
F: +1 800 800 0445

Latin America & Caribbean Region
BR +55 (11) 3356-3100
latam.medical@ansell.com
MX: +52 442 296 2050
latam.medical@ansell.com
CO: +57 1 288 3247
latam.medical@ansell.com

Australia
Ansell Limited
T: +61 1800 337 041
F: +61 1800 803 578

Russia
Ansell PYC
Ten. +7 495 258 13 16

Technology



Ansell, ® and ™ are trademarks owned by Ansell Limited or one of its affiliates. US Patented and US and non-US Patents Pending: www.ansell.com/patentmarking © 2025 Ansell Limited. All Rights Reserved.

Neither this document nor any other statement made herein by or on behalf of Ansell should be construed as a warranty of merchantability or that any Ansell product is fit for a particular purpose. Ansell assumes no responsibility for the suitability or adequacy of an end user's selection of gloves for a specific application.

