

Clearview autoclave panoramic goggles, for excellent optical clarity

- Maximized vision: BioClean[™] Clearview Autoclavable Goggles BCAP feature an antiscratch, anti-fog lens that is both deep and extra-wide, for an increased field of vision
- Reduced contamination risks: These BioClean[™] clearview goggles are processed in a NEBB-certified ISO Class 4 environment and possess an indirect ventilation system to reduce the risk of contamination
- Improved durability: These autoclavable goggles' robust design can withstand 40 autoclave cycles of 30 minutes duration at 121°C/250° F
- Enhanced comfort: These autoclavable cleanroom goggles are constructed with a supersoft thermoplastic rubber frame, non-linting latex-free silicone headband, and polypropylene hooks suitable to be worn over eyeglasses

Key Features and Benefits

- Panoramic, wide-angle lens: For a deeper, wider field of vision
- Indirect ventilation system: Reduced risks of contamination
- Autoclave-resistant design: For durable clearview goggles

Industries

- **Controlled and Critical Environments**
- Laboratory and Research
- Production and Manufacturing



- Medical Device Manufacturing
- Biotechnologies Blending operations Handling active material Maintaining •
- equipment and instruments
- Organic and material synthesis
- Preparing pharmaceutical products
- Clean room cleaning and preparing
- Nutraceutical manufacturing Semiconductor manufacturing
- White goods assembly







BioClean[™] Clearview Autoclavable Goggles BCAP

TECHNICAL DATA SHEET

PRODUCT INFORMATION

Material	Thermoplastic rubber, Polycarbonate, Silicone, Polypropylene
Color	White
Audit Standards	Manufacturing QMS Audit Standards ISO 9001
Standards	EN 166:2001, Category II
Packaging Overview	Goggle (BCAP & BCAP-1): One piece per sealed PE bag (to be removed prior to autoclaving); 12 bags per inner box; five boxes per carton (60 pieces). Replacement Lens (BCAP-SL): One piece per sealed PE bag; 10 bags per inner box; 10 boxes per carton (100 pieces) Replacement Strap (BCAP-SS)*: 25 pieces per sealed PE bag; two bags per inner box; 10 boxes per carton (500 pieces) *Each individual strap includes adjuster hooks and strap clips.
Country Of Origin	Taiwan
Sterilization Method	Supplied non-sterile. To be autoclaved at 121 $^\circ$ C/250 $^\circ$ F for 30 minutes
Cleanroom Class	Class 10/ISO 4 & EU GMP Grade A
Shelf Life	Five (5) years from date of manufacture.
Classification	EN166
Storage Instructions	Store in a dry, cool place (<40 $^{\circ}$ C) away from direct sunlight and fluorescent light.

PHYSICAL PROPERTIES

Overall Dimensions	Lens Thickness (± 0.3mm): 2.1mm Bridge Width (± 0.5mm): 50mm Bridge Height (±0.5mm): 25mm Overall Width (hinge to hinge)(±3mm): 160mm Overall Height (±3mm): 85mm Overall Weight: 103g
--------------------	---

ORDERING INFORMATION

	SIZE	Panoramic Autoclavable Goggles
BCAP	REORDER NO.	BCAP





BioClean[™] Clearview Autoclavable Goggles **BCAP**

EXPLANATION OF FRAME MARKINGS

Required Markings	Markings On Frame	Meaning
Manufacturers Identification Mark	BioClean™	BioClean™
Standard Number	EN166	European Standard on Personal Eye Protection
Field of Use	BT	Medium energy impact at extremes of temperature
Conformity Mark	CE	Comformity with European Standards

For additional information visit us at www.ansell.com, or call us at

Europe, Middle East & Africa North America Region Ansell Healthcare Europe NV T: +32 (0) 2 528 74 00 F: +32 (0) 2 528 74 01

Asia Pacific Region Ansell Global Trading Center T: +603 8310 6688 F: +603 8310 6699

Ansell Healthcare Products LLC US T: +1 800 800 0444 US F: +1 800 800 0445 CA T: +1-800-363-8340
 Latin America & Caribbean Region
 Ansell Nitritex

 Ansell Commercial Mexico S.A. de C.V.
 T: +52 442 248 1544 / 248 3133

 F: +44 1638 668390
 F: +44 1638 668890

Australia Ansell Limited T: +61 1800 337 041 F: +61 1800 803 578 UΚ

Ansell, [®] and [™] are trademarks owned by Ansell Limited or one of its affiliates. US Patented and US and non–US Patents Pending: www.ansell.com/patentmarking © 2024 Ansell Limited. All Rights Reserved.

Neither this document nor any other statement made herein by or on behalf of Ansell should be construed as a warranty of merchantability or that any Ansell product is fit for a particular purpose. Ansell assumes no responsibility for the suitability or adequacy of an end user's selection of gloves for a specific application.

