

Gloves that reduce risk of fire, explosion, or damage caused by electrostatic discharge

- **Ansell's first disposable static dissipative gloves:** MICROFLEX™ 94-242 gloves reduce the risk of electrostatic discharge, which can cause spontaneous combustion in atmospheric explosive environments
- **Low vertical resistivity:** Proprietary nitrile formulation infused with an engineered material that channels electricity through the glove polymer, for a low vertical resistance below 108 Ω
- **Advanced protection:** Made with TNT™ Chemical Splash Resistance Technology for soft, durable protection against a wide range of chemicals
- **Touchscreen compatibility:** Provides capacitive and resistive touchscreen capability when working with industrial electronics
- **Improved visibility:** Black color provides contrast against potentially combustible dust, while hiding the appearance of oils, dirt and stains
- **Dermatest™ certified:** Supports reduced risk of skin irritation



Industries

- Aerospace
- Electronics
- Food Processing
- Life Sciences
- Manufacturing
- Infrastructure Maintenance

Recommended For

- Handling chemicals and cleaning materials
- Unpacking of bulk goods
- Product shipping, transport and delivery
- Handling of tools
- Food processing and handling
- Packaging and labeling
- Oil, fluids and filter change
- Equipment repair and maintenance
- Inspection of parts, equipment

TECHNICAL DATA SHEET

Product Information	
Material	Nitrile
External Glove Surface	Textured Fingers
Audit Standards	ISO 13485, ISO 14001, ISO 9001
Product Certification	Personal Protective Equipment Regulation (EU) 2016/425, Arrette du 05/08/2020, EU Food Contact Approved, EC 2023/2006, ASTM D6319, Dermatest, EN 16350:2014, EN ISO 21420:2020, EN ISO 374-1:2016 Type B JKPT, EN ISO 374-5:2016 Virus, FDA21 CFR 177-2600-US Food Contact Approved, Personal Protective Equipment Regulation (EU) 2016/425 Category III risks, UKCA, CE
Packaging Overview	Case Per Carton=1000 gloves Per 10 Dispensers Dispenser=100 gloves
Storage Instructions	Keep out of direct sunlight; store in a cool and dry place. Keep away from sources of ozone or ignition.
Country Of Origin	Thailand
Product Segmentation	Robust
Antistatic	Yes EN1149 + EN16350
Silicone Free	Yes


PHYSICAL PROPERTIES

	Typical Values		Testing Method
	BEFORE AGING	AFTER AGING	
Length (mm/inches)	245 / 9.65		EN ISO 21420
Freedom from Holes (Inspection level I)	1.5 AQL		EN 374-2
Palm Thickness (mm/mils)	0.12/4.7		
Finger Thickness (mm/mils)	0.16/6.3		
Elongation at Break (%)	≥500	≥400	ASTM D412
Force at break (N)	≥6	≥6	EN 455-2

ORDERING INFORMATION

Size	S (6.5 – 7)	M (7.5 – 8)	L (8.5 – 9)	XL (9.5 – 10)	XXL (10.5 – 11)
Product Code	94242070	94242080	94242090	94242100	94242110

Performance Standards and Regulatory Compliance



For additional information visit us at www.ansell.com, or call us at

Europe, Middle East & Africa Region

Ansell Healthcare Europe NV

T: +32 (0) 2 528 74 00
F: +32 (0) 2 528 74 01

Asia Pacific Region

MY: +603 8310 6688
apac.medical@ansell.com
CN: +86 21 38275000
infochina@ansell.com
JP: +813 5549 8151
info.medical.jp@ansell.com

North America Region

Ansell Healthcare Products LLC

T: +1 800 800 0444
F: +1 800 800 0445

Latin America & Caribbean Region

BR: +55 (11) 3356-3100
latam.medical@ansell.com
MX: +52 442 296 2050
latam.medical@ansell.com
CO: +57 1 288 3247
latam.medical@ansell.com

Australia

Ansell Limited

T: +61 1800 337 041
F: +61 1800 803 578

Russia

Ansell PYC
Ten. +7 495 258 13 16

Technology



Ansell, ® and ™ are trademarks owned by Ansell Limited or one of its affiliates. US Patented and US and non-US Patents Pending: www.ansell.com/patentmarking © 2025 Ansell Limited. All Rights Reserved.

Neither this document nor any other statement made herein by or on behalf of Ansell should be construed as a warranty of merchantability or that any Ansell product is fit for a particular purpose. Ansell assumes no responsibility for the suitability or adequacy of an end user's selection of gloves for a specific application.

