

MICROFLEX™

Soft White Nitrile TQ-601

Comfortably protects hands while replenishing moisture and preventing dryness

White nitrile medical exam glove with HYDRASOFT™ Skin Moisturizing Technology

- **HYDRASOFT™ Skin Moisturizing**

Technology: Unique inner coating is proven to help skin retain 2x more moisture* than gloves without HYDRASOFT™ Technology, preventing dryness and discomfort

- **Comfortable fit:** The soft, nitrile formulation provides a comfortable fit and feel
- **Heightened tactility:** The lightweight nitrile construction provides extra comfort and tactility while working

*based on internal testing (data on file)



NOW FEATURING
HYDRASOFT™
Skin Moisturizing Technology

Industries

- Dental
- Healthcare
- Life Sciences

Recommended For

- Sample taking and processing
- Protection from Type I latex allergy in HCW's or patients
- Testing
- Oral examinations
- Laboratory analysis
- Helping protect skin from drying or cracking
- Pharmaceutical manufacturing
- General dentistry
- Standard patient examinations
- Enhanced tactile sensitivity and dexterity, especially for delicate procedures

TECHNICAL DATA SHEET

	Product Information
Material	Nitrile
External Glove Surface	Textured Fingers
Audit Standards	ISO 13485, ISO 9001
Product Certification	Medical Device Regulation (EU) 2017/745 Class I, ASTM D6319, CE Number, EN 455 1-4, EN ISO 13485, US QSR/FDA 510(k) Medical Examination Grade, UKCA, PMDA Notification Number: 13B3X10307AH0001, Trade Name: Ansell Non Latex Medical Examination Glove
Packaging Overview	100 gloves per dispenser 10 dispensers per case 1000 gloves per case
Storage Instructions	Keep out of direct sunlight; store in a cool and dry place. Keep away from sources of ozone or ignition.
Country Of Origin	Indonesia
Product Segmentation	High Touch
Antistatic	Not Tested
Silicone Free	No

PHYSICAL PROPERTIES

	Typical Values		Testing Method
Length (mm/inches)	245 / 9.65		ASTM D3767, EN 420
Freedom from Holes (Inspection level I)	1.5 AQL		ASTM D5151, EN 455-1
Palm Thickness (mm/mils)	0.07/2.8		ASTM D3767, EN 420
Finger Thickness (mm/mils)	0.12/4.7		ASTM D3767, EN 420
	BEFORE AGING	AFTER AGING	
Ultimate Tensile Strength (MPa)	14	14	ASTM D412 & D573
Elongation at Break (%)	≥ 500	≥ 400	ASTM D412
Force at break (N)	≥ 6N	≥ 6	

ORDERING INFORMATION

Size	XS (5.5 – 6)	S (6.5 – 7)	M (7.5 – 8)	L (8.5 – 9)	XL (9.5 – 10)
Product Code	TQ-601-XS	TQ-601-S	TQ-601-M	TQ-601-L	TQ-601-XL

Performance Standards and Regulatory Compliance



For additional information visit us at www.ansell.com, or call us at

Europe, Middle East & Africa Region
Ansell Healthcare Europe NV
T: +32 (0) 2 528 74 00
F: +32 (0) 2 528 74 01
Asia Pacific Region
MY: +603 8310 6688
apac.medical@ansell.com
CN: +86 21 38275000
infochina@ansell.com
JP: +813 5549 8151
info.medical.jp@ansell.com

North America Region
Ansell Healthcare Products LLC
T: +1 800 800 0444
F: +1 800 800 0445
Latin America & Caribbean Region
BR: +55 (11) 3356-3100
latam.medical@ansell.com
MX: +52 442 296 2050
latam.medical@ansell.com
CO: +57 1 288 3247
latam.medical@ansell.com

Australia
Ansell Limited
T: +61 1800 337 041
F: +61 1800 803 578
Russia
Ansell PYC
Ten. +7 495 258 13 16

Technology



Ansell, ® and ™ are trademarks owned by Ansell Limited or one of its affiliates. US Patented and US and non-US Patents Pending: www.ansell.com/patentmarking © 2025 Ansell Limited. All Rights Reserved.

Neither this document nor any other statement made herein by or on behalf of Ansell should be construed as a warranty of merchantability or that any Ansell product is fit for a particular purpose. Ansell assumes no responsibility for the suitability or adequacy of an end user's selection of gloves for a specific application.

