

An unparalleled combination of chemical splash protection, comfort and durability

- **World leader:** TouchNTuff™ 92-600 gloves are the world's leading disposable gloves for chemical splash protection
- **Superior protection:** Made with TNT™ Chemical Splash Resistance Technology, these gloves effectively safeguard hands from exposure to harmful chemicals
- **Elevated comfort:** Super soft nitrile provides a comfortable feel during extended wear
- **Robust durability:** EN388 certified, meeting level 1 abrasion to prevent ripping and tearing during heavy-duty work
- **Prevents surface defects:** Silicone-free, they prevent contaminant transfer that causes flaws in paints, coatings and finishes
- **Dermatest™ certified:** Supports reduced risk of skin irritation



Industries

- Life Sciences
- Food Processing
- Automotive
- Agriculture
- Infrastructure Maintenance
- Chemical

Recommended For

- Transferring liquids and solids
- Meat, Fish and Food Processing
- Industrial Production
- Maintenance
- Laboratory analysis
- Chemical Handling

TECHNICAL DATA SHEET

Product Information	
Material	Nitrile
External Glove Surface	Smooth
Audit Standards	ISO 9001
Product Certification	Category III, EN 388:2016 1XXXX, EN ISO 21420:2020, EN ISO 374-1:2016 Type B JKPT, EN ISO 374-5:2016 Virus, FDA21 CFR 177-2600-US Food Contact Approved, EU Food Contact Approved, ISO 18889:2019, ISO 9001, UKCA, DOSH-SIRIM certified, Dermatest
Packaging Overview	XS-XL: 100 gloves per dispenser, 10 dispensers per case, 1000 gloves per case XXL: 90 gloves per dispenser, 10 dispensers per case, 900 gloves per case Size XS and XXL are not available in China and Brazil
Storage Instructions	Vend Pack Variant (Size S, M, L, XL): 20 gloves per box, 24 boxes per carton
Product Segmentation	Keep out of direct sunlight; store in a cool and dry place. Keep away from sources of ozone or ignition.
Antistatic	Robust
	Yes EN1149

PHYSICAL PROPERTIES

	Typical Values	Testing Method
Length (mm/inches)	240 / 9.45	ASTM D3767,EN 420
Freedom from Holes (Inspection level I)	1.5 AQL	ASTM D5151,EN 455-1
Finger Thickness (mm/mils)	0.14	ASTM D3767,EN 420
	BEFORE AGING	AFTER AGING
Elongation at Break (%)	≥ 600	≥ 525
Force at break (N)	≥ 10	≥ 10

ORDERING INFORMATION

Size	XS (5.5 - 6)	S (6.5 - 7)	M (7.5 - 8)	L (8.5 - 9)	XL (9.5 - 10)	XXL (10.5 - 11)
Product Code	92600060	92600070	92600080	92600090	92600100	92600110

Performance Standards and Regulatory Compliance



For additional information visit us at www.ansell.com, or call us at

Europe, Middle East & Africa Region
Ansell Healthcare Europe NV
T: +32 (0) 2 528 74 00
F: +32 (0) 2 528 74 01

Asia Pacific Region
MY: +603 8310 6688
apac.medical@ansell.com
CN: +86 21 38275000
infochina@ansell.com
JP: +813 5549 8151
info.medical.jp@ansell.com

North America Region
Ansell Healthcare Products LLC
T: +1 800 800 0444
F: +1 800 800 0445

Latin America & Caribbean Region
BR: +55 (11) 3356-3100
latam.medical@ansell.com
MX: +52 442 296 2050
latam.medical@ansell.com
CO: +57 1 288 3247
latam.medical@ansell.com

Australia
Ansell Limited
T: +61 1800 337 041
F: +61 1800 803 578

Russia
Ansell PYC
T: +7 495 258 1316

Technology

 **TNT™**
Chemical Splash
Resistance Technology

Ansell, ® and ™ are trademarks owned by Ansell Limited or one of its affiliates. US Patented and US and non-US Patents Pending: www.ansell.com/patentmarking © 2025
Ansell Limited. All Rights Reserved.

Neither this document nor any other statement made herein by or on behalf of Ansell should be construed as a warranty of merchantability or that any Ansell product is fit for a particular purpose. Ansell assumes no responsibility for the suitability or adequacy of an end user's selection of gloves for a specific application.

