

# HyFlex™

## 11-644

Flexible cut protection with thinner palm



Cut

Abrasion Protection



Medium Duty

## Flexible cut protection with 20% thinner palm design\* for improved dexterity

- **Improved dexterity:** Sleek palm design is 20% thinner\* than competitors, for greater flexibility and freedom of movement
  - **Ergonomic fit:** Proprietary Ansell materials offer a soft, comfortable feel while working
  - **Enhanced cut protection:** HyFlex™ 11-644 gloves utilize INTERCEPT™ Cut Resistance Technology to deliver ANSI/ISEA 105-2024 A2/EN ISO B cut protection, achieving higher performance within the same cut class
  - **Enhanced durability:** Polyurethane coating remains flexible while providing reliable resistance to abrasion over time
  - **Genuine practicality:** Available in vend pack form for easy access, storage and re-application
- \* Comparison is based on Ansell lab tests under standardized conditions versus similar competitive gloves available at the time of testing. Results may vary by application.



### Industries

- Automotive
- Machinery and Equipment

### Applications

- Press shop operations
- Handling metal sheets & panels
- Handling parts with sharp, rough edges
- Inspection (picking, checking and marking)
- Cutting glasses, sheets, panels

# HyFlex™

## 11-644

Flexible cut protection with thinner palm

### Key Features

- Improved dexterity: 20% thinner palm vs competitors\*
  - Ergonomic fit: Soft, comfortable feel while working
  - Enhanced cut performance: INTERCEPT™ cut protection
- \* Comparison is based on Ansell lab tests under standardized conditions in December 2025 versus similar competitive gloves. Results may vary by application.

### Technologies



### Performance Standards & Regulatory Compliance



ANSI/ISEA 105-2024



EN388: 2016



4342B

### Specifications

| BRAND   STYLE  | DESCRIPTION   | Gauge | SIZE                      | LENGTH                         | COATING COLOR | PACKAGE                        |
|----------------|---|-------|---------------------------|--------------------------------|---------------|--------------------------------|
| HyFlex™ 11-644 | <b>Finishing:</b> Palm Coated<br><b>Coating Material:</b> Polyurethane<br><b>Liner Material:</b> Nylon, HPPE, Spandex<br><b>Cuff Style:</b> Knitwrist | 13    | 5, 6, 7, 8, 9, 10, 11, 12 | 207-277 mm / 8.14-10.90 inches | Grey          | • 12 pairs/bag, 12 bags/carton |

For additional information visit us at [www.ansell.com](http://www.ansell.com), or call us at

#### Europe, Middle East & Africa Region

Ansell Healthcare Europe NV  
Riverside Business Park  
Blvd International, 55  
1070 Brussels, Belgium  
T: +32 (0) 2 528 74 00  
F: +32 (0) 2 528 74 01

#### North America Region

Ansell Healthcare Products LLC  
111 Wood Avenue South,  
Suite 900  
Iselin, NJ 08830, USA  
T: +1 800 800 0444  
F: +1 800 800 0445

#### Australia

Ansell Limited  
Level 3, 678 Victoria Street,  
Richmond, Vic, 3121  
Australia  
T: +61 1800 337 041  
F: +61 1800 803 578

#### Asia Pacific Region

Ansell Global Trading Center  
(Malaysia) Sdn Bhd  
Prima 6, Prima Avenue  
Block 3512, Jaiin Teknokrat 6  
T: +603 8310 6688  
F: +603 8310 6699

#### Latin America & Caribbean Region

Ansell Commercial Mexico S.A. de C.V.  
Blvd. Bernardo Quintana No. 7001-C,  
Q7001 Torre II,  
Suites 1304, 1305 y 1306,  
Col. Centro Sur, c.p. 76079  
Queretaro, Qro. Mexico  
T: +52 442 248 1544 / 248 3133

#### Canada

Ansell Canada  
105 Lauder  
Cowansville, QC J2K 2K8  
Canada  
T: +1 800 363 8340  
F: +1 800 267 3551

Ansell, ® and ™ are trademarks owned by Ansell Limited or one of its affiliates. US Patented and US and non-US Patents Pending: [www.ansell.com/patentmarking](http://www.ansell.com/patentmarking) © 2025 Ansell Limited. All Rights Reserved.

Neither this document nor any other statement made herein by or on behalf of Ansell should be construed as a warranty of merchantability or that any Ansell product is fit for a particular purpose. Ansell assumes no responsibility for the suitability or adequacy of an end user's selection of gloves for a specific application.

