

## Chemical-resistant disposable gloves that deliver durable protection and superior comfort.

- **Three-layer design:** Three layers ensure superior protection against harsh chemicals
- **Tactility:** Designed to be thinner than standard reusable chemical-resistant gloves, providing protection while allowing for better tactility when handling small objects and tools
- **Elevated comfort:** Soft material and ergonomic design offer outstanding fit, feel and flexibility
- **Assured quality:** Their low AQL (0.65) means minimal pinhole defect risks
- **High standards:** Meets EN 374 Type A certified in Europe and KOSHA certified in Korea
- **Retail pack:** Available in convenient packaging of 6 gloves, size specific



### Industries

- Aerospace
- Automotive
- Automotive Aftermarket
- Life Sciences
- Agriculture
- Infrastructure Maintenance
- Chemical

### Recommended For

- General Purpose Auto Aftermarket
- Production line support and maintenance
- Sample taking and processing
- Transferring liquids and solids between vessels and tanks and process equipment
- Oil, fluids and filter change
- Inspection, selecting, checking parts
- Assembly and inspection of components
- Equipment repair and maintenance
- Blending, compounding solids and liquids

# TECHNICAL DATA SHEET

| Product Information                 |                                                                                                                                                                                                                                                                                                                      |
|-------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Material                            | Nitrile, Neoprene                                                                                                                                                                                                                                                                                                    |
| External Glove Surface              | Textured Fingers                                                                                                                                                                                                                                                                                                     |
| Audit Standards                     | ISO 9001                                                                                                                                                                                                                                                                                                             |
| Product Certification               | Personal Protective Equipment Regulation (EU) 2016/425 Category III risks, EN 388:2016 2000X, CE 0493, EN 421:2010, EN ISO 21420:2020, EN ISO 374-1:2016 Type A JKLOPST, EN ISO 374-5:2016 Virus, FDA21 CFR 177-2600-US Food Contact Approved, ISO 18889:2019, ISO 9001, DOSH-SIRIM certified, Kosha certified, UKCA |
| Packaging Overview                  | 50 gloves per dispenser<br>10 dispensers per case<br>500 gloves per case<br><br>Retail Pack: 6 gloves per pack; 50 packs per case; 300 gloves per case                                                                                                                                                               |
| Storage Instructions                | Keep out of direct sunlight; store in a cool and dry place. Keep away from sources of ozone or ignition.                                                                                                                                                                                                             |
| Country Of Origin                   | Sri Lanka                                                                                                                                                                                                                                                                                                            |
| Product Segmentation                | High Risk                                                                                                                                                                                                                                                                                                            |
| Antistatic                          | Yes EN1149                                                                                                                                                                                                                                                                                                           |
| Fentanyl Tested                     | Yes                                                                                                                                                                                                                                                                                                                  |
| Silicone Free                       | Yes                                                                                                                                                                                                                                                                                                                  |
| Vulcanization Chemical Accelerators | <ul style="list-style-type: none"> <li>Zinc Dibutyldithiocarbamate (ZDBC)</li> </ul> <i>Only a very small number of users may be sensitive to this ingredient(s) and hence may develop irritant and/or allergic contact reactions.</i>                                                                               |

## PHYSICAL PROPERTIES

|                                         | Typical Values |             | Testing Method      |
|-----------------------------------------|----------------|-------------|---------------------|
| Length (mm/inches)                      | ≥ 285 / 11.2   |             | ASTM D3767,EN 420   |
| Freedom from Holes (Inspection level I) | 0.65 AQL       |             | ASTM D5151,EN 455-1 |
| Palm Thickness (mm/mils)                | 0.20/7.9       |             | ASTM D3767,EN 420   |
| Finger Thickness (mm/mils)              | 0.20/7.9       |             | ASTM D3767,EN 420   |
|                                         | BEFORE AGING   | AFTER AGING |                     |
| Elongation at Break (%)                 | ≥ 500          | ≥ 400       | ASTM D412           |
| Force at break (N)                      | ≥ 6            | ≥ 6         | EN 455-2            |

ORDERING INFORMATION

| Size                   | XS (5.5 - 6) | S (6.5 - 7) | M (7.5 - 8) | L (8.5 - 9) | XL (9.5 - 10) | XXL (10.5 - 11) | M (7.5 - 8) | L (8.5 - 9) | XL (9.5 - 10) | XXL (10.5 - 11) |
|------------------------|--------------|-------------|-------------|-------------|---------------|-----------------|-------------|-------------|---------------|-----------------|
| Product Code           | 93260060     | 93260070    | 93260080    | 93260090    | 93260100      | 93260110        | 93260RP080  | 93260RP090  | 93260RP100    | 93260RP110      |
| Retail Pack Catalog No |              |             | 93260RP080  | 93260RP090  | 93260RP100    |                 | 93260RP080  | 93260RP090  | 93260RP100    |                 |

Performance Standards and Regulatory Compliance



For additional information visit us at [www.ansell.com](http://www.ansell.com), or call us at

|                                                                                                                                                                                                                                                                                                                     |                                                                                                                                                                                                                                                                                                                      |                                                                                                                                          |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Europe, Middle East &amp; Africa Region</b><br>Ansell Healthcare Europe NV<br>T: +32 (0) 2 528 74 00<br>F: +32 (0) 2 528 74 01<br><b>Asia Pacific Region</b><br>MY: +603 8310 6688<br>apac.medical@ansell.com<br>CN: +86 21 38275000<br>infochina@ansell.com<br>JP: +813 5549 8151<br>info.medical.jp@ansell.com | <b>North America Region</b><br>Ansell Healthcare Products LLC<br>T: +1 800 800 0444<br>F: +1 800 800 0445<br><b>Latin America &amp; Caribbean Region</b><br>BR: +55 (11) 3356-3100<br>latam.medical@ansell.com<br>MX: +52 442 296 2050<br>latam.medical@ansell.com<br>CO: +57 1 288 3247<br>latam.medical@ansell.com | <b>Australia</b><br>Ansell Limited<br>T: +61 1800 337 041<br>F: +61 1800 803 578<br><b>Russia</b><br>Ansell PYC<br>Ten. +7 495 258 13 16 |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------|

Ansell, ® and ™ are trademarks owned by Ansell Limited or one of its affiliates. US Patented and US and non-US Patents Pending: [www.ansell.com/patentmarking](http://www.ansell.com/patentmarking) © 2025 Ansell Limited. All Rights Reserved.

Neither this document nor any other statement made herein by or on behalf of Ansell should be construed as a warranty of merchantability or that any Ansell product is fit for a particular purpose. Ansell assumes no responsibility for the suitability or adequacy of an end user's selection of gloves for a specific application.

