

## Offers comfortable and reliable hand protection

- **Heightened sensitivity:** Designed with a lightweight nitrile formulation for enhanced comfort and tactile sensitivity
- **Secure grip:** Textured on the fingertips to promote sure handling of materials and instruments
- **Specialized protection:** They offer protection against hazardous chemicals, including chemotherapy drugs\*
- **Genuine versatility:** These gloves provide reliable protection for healthcare, laboratory workers, or any glove wearers seeking an exceptional fit
- **Smart packed:** Packaged 200 gloves per box to reduce restocking orders



\*see product packaging for details

### Industries

- Healthcare
- Emergency Medical Services
- Life Sciences
- Dental

### Recommended For

- Standard patient examinations
- General dentistry
- Emergency services
- Laboratory analysis
- Protection from Type I latex allergy in HCW's or patients
- Tested for use with chemotherapy drugs

TECHNICAL DATA SHEET

	Product Information
External Glove Surface	Textured Fingers
Audit Standards	ISO 13485, ISO 9001
Product Certification	UE: marquage CE en vertu du Règlement relatif aux Dispositifs Médicaux (RDM) (UE) 2017/745 (Classe I) et Règlement (UE) 2016/425 relatif aux EPI (risques Cat. III) par Centexbel (0493)
Packaging Overview	200 gloves per dispenser 10 dispensers (2000 gloves) per carton
Storage Instructions	Keep out of direct sunlight; store in a cool and dry place. Keep away from sources of ozone or ignition.
Country Of Origin	China
Product Segmentation	Standard Thin
Antistatic	Not Tested
Vulcanization Chemical Accelerators	<ul style="list-style-type: none"><li>Zinc Dibutyldithiocarbamate (ZDBC)</li><li>Zinc Diethyldithiocarbamate (ZDEC)</li></ul> <p><i>Only a very small number of users may be sensitive to this ingredient(s) and hence may develop irritant and/or allergic contact reactions.</i></p>

PHYSICAL PROPERTIES

	Typical Values	Testing Method
Length (mm/inches)	240 / 9.5	EN 455-2
Freedom from Holes (Inspection level I)	1.5 AQL	EN 455-1
Palm Thickness (mm/mils)	0.08 / 3.2	EN 455-2
Finger Thickness (mm/mils)	0.10 / 3.9	EN 455-2
BEFORE AGINGAFTER AGING		
Ultimate Tensile Strength (MPa)		
Force at break (N)	≥ 6	EN 455-2

ORDERING INFORMATION

Size	XS (5.5 - 6)	S (6.5 - 7)	M (7.5 - 8)	L (8.5 - 9)	XL (9.5 - 10)
Product Code	PN-290-XS	PN-290-S	PN-290-M	PN-290-L	PN-290-XL

Performance Standards and Regulatory Compliance



For additional information visit us at [www.ansell.com](http://www.ansell.com), or call us at

<b>Europe, Middle East &amp; Africa Region</b> Ansell Healthcare Europe NV T: +32 (0) 2 528 74 00 F: +32 (0) 2 528 74 01  <b>Asia Pacific Region</b> MY: +603 8310 6688 apac.medical@ansell.com CN: +86 21 38275000 infochina@ansell.com JP: +813 5549 8151 info.medical.jp@ansell.com	<b>North America Region</b> Ansell Healthcare Products LLC T: +1 800 800 0444 F: +1 800 800 0445  <b>Latin America &amp; Caribbean Region</b> BR: +55 (11) 3356-3100 latam.medical@ansell.com MX: +52 442 296 2050 latam.medical@ansell.com CO: +57 1 288 3247 latam.medical@ansell.com	<b>Australia</b> Ansell Limited T: +61 1800 337 041 F: +61 1800 803 578  <b>Russia</b> Ansell PYC Ten. +7 495 258 13 16
---	--	--

Ansell, ® and ™ are trademarks owned by Ansell Limited or one of its affiliates. US Patented and US and non-US Patents Pending: [www.ansell.com/patentmarking](http://www.ansell.com/patentmarking) © 2024 Ansell Limited. All Rights Reserved.

Neither this document nor any other statement made herein by or on behalf of Ansell should be construed as a warranty of merchantability or that any Ansell product is fit for a particular purpose. Ansell assumes no responsibility for the suitability or adequacy of an end user's selection of gloves for a specific application.

