

2000 STANDARD - Model

Superior breathable microporous laminate technology, Type 5/6 protection

Previously known as: MICROGARD® 2000 STANDARD - Model 156

Superior protection from low hazard liquid spray and fine particulates with bound seams for improved overall protection..

DESIGN

MICROGARD® 2000 provides both protection and comfort with exceptional liquid and particulate protection. Ideal for a wide range of industrial applications. Low hazard liquid chemical repellence, particle protection, protection from pesticides and barrier to biological agents. Spray tight and ultra low linting for critical environments.

BOUND SEAMS

Superior strength, liquid and particle barrier

SUIT FEATURES

- 3 piece hood
- Elasticated hood, wrists, waist and ankles
- 2-way front zipper with resealable storm flap
- · Finger loops
- Integrated socks with boot overflaps

COLORS

White

SIZES

S-5XL





Industries

- Life Sciences
- Automotive
- Metal fabrication
- Food Processing
- Defense

Applications

- Clean room cleaning and preparing
- Body painting including surface inspection
- Production line support
 & maintenance
- Cleaning of plant and machines
- Maintenance of plant and machines
- Crime Scene Investigation (CSI)
- Veterinary Services

KEY FEATURES & BENEFITS

- Proven protective barrier to low concentration liquid chemicals, liquid & particulate biological hazards
- Comfortable to wear featuring moisture vapor permeable fabric ("breathable") to help reduce the risk of heat stress
- Optimized body fit, improving wearer comfort and safety
- Anti-static, tested according to EN 1149-5
- Low linting to help reduce the risk of cross contamination in critical areas
- Silicone free, critical in spray painting applications

Material Diagram

Microporous Polyethylene Film Non-woven inner layer

Seam Diagram



Performance Standards

















Product Information

Product Information	
Available Sizes	S, M, L, XL, 2XL, 3XL
Color	White
Packaging Overview	Individually packaged
Product Material	Microporous polyethylene Laminate non-woven
Product Reference	2000 STANDARD - Model 156
Standards Overview	CE CATEGORY III (Type 5-B, Type 6-B, EN 1073-2, EN 14126, DIN 32781, EN 1149-5)
Seam Type	Bound
Style Number	W20B156



Suit components & accessories

Suit Components and Accessories

Design Features

3-piece hood, 2-way front zipper with re-sealable storm flap, finger loops. Elasticated hood, waist, wrists, ankles and overflaps. Integrated socks with boot overflaps.

For additional in formation visit us at www.ansell.com, or call us at

Europe, Middle East & Africa Region Ansell Healthcare Europe NV T: +32 (0) 2 528 74 00

Asia Pacific Region Ansell Global Trading Center T: +603 8310 6688 North America Region Ansell Healthcare Products LLC T: +1 800 800 0444

Latin America & Caribbean Region

Australia Ansell Limited T: +61 1800 337 041

Ansell Commercial Mexico S.A. de C.V. T: +52 442 248 1544 / 248 3133

Ansell, @ and $^{\text{M}}$ are trademarks owned by Ansell Limited or one of its affiliates. US Patented and US and non-US Patents Pending: www.ansell.com/patentmarking @ 2025 Ansell Limited. All Rights Reserved.

Neither this document nor any other statement made herein by or on behalf of Ansell should be construed as a warranty of merchantability or that any Ansell product is fit for a particular purpose. Ansell assumes no responsibility for the suitability or adequacy of an end user's selection of gloves for a specific application.

