

## Blue nitrile gloves with raised texture surface, offering confident wet, dry and oily grip

- **Strong grip:** Thanks to a Mega Texture surface, MICROFLEX™ 93-283 disposable gloves boast secure grip, for handling wet, oily, or fatty objects
- **Tear-resistant:** These nitrile gloves' 0.2mm/8 mil thickness increases their resistance to tears
- **Food handling compliance:** Certified as food handling gloves, these gloves are ideal for a wide range of food handling applications
- **Ideal for double donning:** Their generous fit allows them to be worn comfortably over thermal or cut-resistant gloves
- **Expanded protection:** Added forearm and wrist protection is provided by an extended cuff design



### Industries

- Food Processing
- Automotive Aftermarket
- Machinery and Equipment

### Recommended For

- General Purpose Auto Aftermarket
- Chemical Splash
- Production line support and maintenance
- Use as an underglove when double gloving
- Vehicle maintenance
- Packaging and labeling
- Handling of frozen foods
- Janitorial, clean up and maintenance
- Handling of machined parts coated with light oil
- Maintenance of plant and machines
- Chemical Handling
- Enhanced grip in wet environments

## TECHNICAL DATA SHEET

|                        | Product Information                                                                                                                                                                                                                                                                                           |
|------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Material               | Nitrile                                                                                                                                                                                                                                                                                                       |
| External Glove Surface | Raised Diamond Grip Pattern                                                                                                                                                                                                                                                                                   |
| Audit Standards        | ISO 13485, ISO 9001                                                                                                                                                                                                                                                                                           |
| Product Certification  | Medical Device Regulation (EU) 2017/745 Class I, Personal Protective Equipment Regulation (EU) 2016/425 Category III risks, ASTM D6319, CE 0493, EC 2023/2006, EU Food Contact Approved, EN ISO 21420:2020, EN ISO 374-1:2016 Type B JKPT, EN ISO 374-5:2016 Virus, ISO 9001, ISO 13485, ISO 18889:2019, UKCA |
| Packaging Overview     | 50 gloves per dispenser<br>10 dispensers per case<br>500 gloves per case<br>2XL and 3XL: 44 gloves per dispenser<br>440 gloves per case                                                                                                                                                                       |
| Storage Instructions   | Keep out of direct sunlight; store in a cool and dry place. Keep away from sources of ozone or ignition.                                                                                                                                                                                                      |
| Country Of Origin      | Thailand                                                                                                                                                                                                                                                                                                      |
| Product Segmentation   | High Risk                                                                                                                                                                                                                                                                                                     |
| Antistatic             | Yes EN1149                                                                                                                                                                                                                                                                                                    |
| Silicone Free          | No                                                                                                                                                                                                                                                                                                            |

## PHYSICAL PROPERTIES

|                                         | Typical Values |             | Testing Method      |
|-----------------------------------------|----------------|-------------|---------------------|
| Length (mm/inches)                      | 300 / 12       |             | ASTM D3767,EN 420   |
| Freedom from Holes (Inspection level I) | 1.5 AQL        |             | ASTM D5151,EN 374-2 |
| Palm Thickness (mm/mils)                | 0.20/7.9       |             | ASTM D3767,EN 420   |
| Finger Thickness (mm/mils)              | 0.24/9.4       |             | ASTM D3767,EN 420   |
|                                         | BEFORE AGING   | AFTER AGING |                     |
| Elongation at Break (%)                 | 500            | 400         | ASTM D412           |
| Force at break (N)                      | >6             | >6          | EN 455-2            |

ORDERING INFORMATION

| Size         | S (6.5 - 7) | M (7.5 - 8) | L (8.5 - 9) | XL (9.5 - 10) | XXL (10.5 - 11) | XXXL (11.5 - 12) |
|--------------|-------------|-------------|-------------|---------------|-----------------|------------------|
| Product Code | 93283070    | 93283080    | 93283090    | 93283100      | 93283110        | 93283120         |

Performance Standards and Regulatory Compliance

CE 0493

EN ISO 374-1:2016  
Type B



J K P T

EN ISO 374-5



VIRUS



ISO

ISO 9001

ISO

ISO 13485



G1

ISO 18889

UK

CA

For additional information visit us at [www.ansell.com](http://www.ansell.com), or call us at

**Europe, Middle East & Africa Region**  
Ansell Healthcare Europe NV  
T: +32 (0) 2 528 74 00  
F: +32 (0) 2 528 74 01

**Asia Pacific Region**  
MY: +603 8310 6688  
apac.medical@ansell.com  
CN: +86 21 38275000  
infochina@ansell.com  
JP: +813 5549 8151  
info.medical.jp@ansell.com

**North America Region**  
Ansell Healthcare Products LLC  
T: +1 800 800 0444  
F: +1 800 800 0445

**Latin America & Caribbean Region**  
BR: +55 (11) 3356-3100  
latam.medical@ansell.com  
MX: +52 442 296 2050  
latam.medical@ansell.com  
CO: +57 1 288 3247  
latam.medical@ansell.com

**Australia**  
Ansell Limited  
T: +61 1800 337 041  
F: +61 1800 803 578

**Russia**  
Ansell PYC  
Ten. +7 495 258 13 16

Ansell, ® and ™ are trademarks owned by Ansell Limited or one of its affiliates. US Patented and US and non-US Patents Pending: [www.ansell.com/patentmarking](http://www.ansell.com/patentmarking) © 2025 Ansell Limited. All Rights Reserved.

Neither this document nor any other statement made herein by or on behalf of Ansell should be construed as a warranty of merchantability or that any Ansell product is fit for a particular purpose. Ansell assumes no responsibility for the suitability or adequacy of an end user's selection of gloves for a specific application.

