

## An unparalleled combination of chemical splash protection, comfort and durability

- **World leader:** TouchNTuff™ 92-600 gloves are the world's leading disposable gloves for chemical splash protection
- **Superior protection:** Made with TNT™ Chemical Splash Resistance Technology, these gloves effectively safeguard hands from exposure to harmful chemicals
- **Elevated comfort:** Super soft nitrile provides a comfortable feel during extended wear
- **Robust durability:** EN388 certified, meeting level 1 abrasion to prevent ripping and tearing during heavy-duty work
- **Prevents surface defects:** Silicone-free, they prevent contaminant transfer that causes flaws in paints, coatings and finishes
- **Certified harm-free:** Dermatest™ certification ensures these PPE gloves are skin-friendly



### Industries

- Life Sciences
- Food Processing
- Automotive
- Agriculture
- Infrastructure Maintenance
- Chemical

### Recommended For

- Transferring liquids and solids
- Meat, Fish and Food Processing
- Industrial Production
- Maintenance
- Laboratory analysis
- Chemical Handling

# TECHNICAL DATA SHEET

|                        | Product Information                                                                                                                                                                                                                                                                                     |
|------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Material               | Nitrile                                                                                                                                                                                                                                                                                                 |
| External Glove Surface | Smooth                                                                                                                                                                                                                                                                                                  |
| Audit Standards        | ISO 9001                                                                                                                                                                                                                                                                                                |
| Product Certification  | Category III, EN 388:2016 1XXXX, EN ISO 21420:2020, EN ISO 374-1:2016 Type B JKPT, EN ISO 374-5:2016 Virus, FDA21 CFR 177-2600-US Food Contact Approved, EU Food Contact Approved, ISO 18889:2019, ISO 9001, UKCA, DOSH-SIRIM certified, Dermatest                                                      |
| Packaging Overview     | XS-XL: 100 gloves per dispenser, 10 dispensers per case, 1000 gloves per case<br>XXL: 90 gloves per dispenser, 10 dispensers per case, 900 gloves per case<br>Size XS and XXL are not available in China and Brazil<br><br>Vend Pack Variant (Size S, M, L, XL): 20 gloves per box, 24 boxes per carton |
| Storage Instructions   | Keep out of direct sunlight; store in a cool and dry place. Keep away from sources of ozone or ignition.                                                                                                                                                                                                |
| Product Segmentation   | Robust                                                                                                                                                                                                                                                                                                  |
| Antistatic             | Yes EN1149                                                                                                                                                                                                                                                                                              |

## PHYSICAL PROPERTIES

|                                                | Typical Values                                                                                                | Testing Method       |
|------------------------------------------------|---------------------------------------------------------------------------------------------------------------|----------------------|
| Length (mm/inches)                             | 240 / 9.45                                                                                                    | ASTM D3767, EN 420   |
| Freedom from Holes (Inspection level I)        | 4.0 AQL (North & South America, except Brazil) / 1.5 AQL (Europe, Middle East, Africa, Asia, Pacific, Brazil) | ASTM D5151, EN 455-1 |
| <div>BEFORE AGING</div> <div>AFTER AGING</div> |                                                                                                               |                      |
| Elongation at Break (%)                        | ≥ 600                                                                                                         | ASTM D412            |
| Force at break (N)                             | ≥ 10                                                                                                          | EN 455-2             |

## ORDERING INFORMATION

| Size         | XS (5.5 - 6) | S (6.5 - 7) | M (7.5 - 8) | L (8.5 - 9) | XL (9.5 - 10) | XXL (10.5 - 11) |
|--------------|--------------|-------------|-------------|-------------|---------------|-----------------|
| Product Code | 92600060     | 92600070    | 92600080    | 92600090    | 92600100      | 92600110        |

## Performance Standards and Regulatory Compliance



For additional information visit us at [www.ansell.com](http://www.ansell.com), or call us at

**Europe, Middle East & Africa Region**  
Ansell Healthcare Europe NV  
T: +32 (0) 2 528 74 00  
F: +32 (0) 2 528 74 01

**Asia Pacific Region**  
MY: +603 8310 6688  
apac.medical@ansell.com  
CN: +86 21 38275000  
infochina@ansell.com  
JP: +813 5549 8151  
info.medical.jp@ansell.com

**North America Region**  
Ansell Healthcare Products LLC  
T: +1 800 800 0444  
F: +1 800 800 0445

**Latin America & Caribbean Region**  
BR: +55 (11) 3356-3100  
latam.medical@ansell.com  
MX: +52 442 296 2050  
latam.medical@ansell.com  
CO: +57 1 288 3247  
latam.medical@ansell.com

**Australia**  
Ansell Limited  
T: +61 1800 337 041  
F: +61 1800 803 578  
  
**Russia**  
Ansell PYC  
Ten. +7 495 258 13 16

## Technology



Ansell, ® and ™ are trademarks owned by Ansell Limited or one of its affiliates. US Patented and US and non-US Patents Pending: [www.ansell.com/patentmarking](http://www.ansell.com/patentmarking) © 2025 Ansell Limited. All Rights Reserved.

Neither this document nor any other statement made herein by or on behalf of Ansell should be construed as a warranty of merchantability or that any Ansell product is fit for a particular purpose. Ansell assumes no responsibility for the suitability or adequacy of an end user's selection of gloves for a specific application.

