

## The first disposable glove on the market to be resistant to acetone for at least 15 minutes

- **Market first:** TouchNTuff 93-800 offer 15 times longer acetone resistance than standard nitrile disposable gloves
- **Innovative multi-layer design (with NRL not in direct contact with the skin):** MICROCHEM™ Chemical Barrier Technology with Type A chemical resistance, eliminating the need for multiple gloves
- **Increased mechanical properties:** Certified EN388 2110A, offering abrasion (level 2) and cut (ISO Cut A) protection suitable for disposable application
- **High visibility color:** Vivid orange color enhances visibility and foreign object detection (FOD)
- **Improved fit, feel and flexibility:** Flexible formulation and design compared to chemical gloves
- **TÜV certified bio-based formulation:** Containing over 60% bio-based carbon for lower emissions and a smarter, more sustainable choice in hand protection



### Industries

- Aerospace
- Automotive Aftermarket
- Automotive
- Chemical
- Machinery and Equipment
- Metal fabrication
- Manufacturing
- Electronics

### Recommended For

- Cleaning and degreasing parts and machines
- Paint and ink removal
- Surface preparation
- Handling chemicals and cleaning materials
- Spill or leakage cleanup
- Use of cleaning tools and robotic equipment
- Vehicle maintenance
- Handling of paint/glue guns and sprayers
- Lab work, blending, compounding, filling, cleaning
- Laboratory analysis
- Maintenance and equipment clean up
- Oil, fluids and filter change
- Painting or cleaning tools or robots
- Plant disinfection and sanitization
- Assembly of parts
- Blending, compounding materials
- Engine transmission and repair

## TECHNICAL DATA SHEET

|                        | Product Information                                                                                                                                                                          |
|------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Material               | Natural Rubber Latex, Nitrile, Neoprene                                                                                                                                                      |
| External Glove Surface | Textured Fingers                                                                                                                                                                             |
| Audit Standards        | ISO 9001                                                                                                                                                                                     |
| Product Certification  | ASTM D6319; CE 0493; EN 16523-1; EN 374-1,2,3; EN ISO 374-1 Type A JKLOAPST; EN ISO 21420:2020; EN 388 2110A; ISO 14001; ISO 18889; ISO 9001; UKCA; EN ISO 374-5:2016 VIRUS; EN421; EN1149-3 |
| Packaging Overview     | 30 gloves per dispenser<br>10 dispensers per case<br>300 gloves per carton                                                                                                                   |
| Storage Instructions   | Keep out of direct sunlight; store in a cool and dry place. Keep away from sources of ozone or ignition.                                                                                     |
| Country Of Origin      | Sri Lanka                                                                                                                                                                                    |
| Product Segmentation   | High Risk                                                                                                                                                                                    |
| Antistatic             | Yes EN1149                                                                                                                                                                                   |
| Fentanyl Tested        | No                                                                                                                                                                                           |
| Silicone Free          | Yes                                                                                                                                                                                          |
| RightCycle             | Yes                                                                                                                                                                                          |


## PHYSICAL PROPERTIES

|                                         | Typical Values |             | Testing Method      |
|-----------------------------------------|----------------|-------------|---------------------|
| Length (mm/inches)                      | 285 / 11.2     |             | ASTM D3767,EN 420   |
| Freedom from Holes (Inspection level I) | 1.5 AQL        |             | ASTM D5151,EN 455-1 |
| Palm Thickness (mm/mils)                | 0.50 / 19.7    |             | ASTM D3767,EN 420   |
| Finger Thickness (mm/mils)              | 0.60 / 23.6    |             | ASTM D3767,EN 420   |
|                                         | BEFORE AGING   | AFTER AGING |                     |
| Elongation at Break (%)                 | Min 500        | Min 400     | ASTM D412           |
| Force at break (N)                      | Min 6          | Min 6       | EN 455-2            |

## ORDERING INFORMATION

| Size         | S (6.5 - 7) | M (7.5 - 8) | L (8.5 - 9) | XL (9.5 - 10) |
|--------------|-------------|-------------|-------------|---------------|
| Product Code | 93800070    | 93800080    | 93800090    | 93800100      |

## Performance Standards and Regulatory Compliance



For additional information visit us at [www.ansell.com](http://www.ansell.com), or call us at

**Europe, Middle East & Africa Region**  
Ansell Healthcare Europe NV  
T: +32 (0) 2 528 74 00  
F: +32 (0) 2 528 74 01

**Asia Pacific Region**  
MY: +603 8310 6688  
apac.medical@ansell.com  
CN: +86 21 38275000  
infochina@ansell.com  
JP: +813 5549 8151  
info.medical.jp@ansell.com

**North America Region**  
Ansell Healthcare Products LLC  
T: +1 800 800 0444  
F: +1 800 800 0445

**Latin America & Caribbean Region**  
BR: +55 (11) 3356-3100  
latam.medical@ansell.com  
MX: +52 442 296 2050  
latam.medical@ansell.com  
CO: +57 1 288 3247  
latam.medical@ansell.com

**Australia**  
Ansell Limited  
T: +61 1800 337 041  
F: +61 1800 803 578

**Russia**  
Ansell PYC  
Ten. +7 495 258 13 16

Technology



Ansell, ® and ™ are trademarks owned by Ansell Limited or one of its affiliates. US Patented and US and non-US Patents Pending: [www.ansell.com/patentmarking](http://www.ansell.com/patentmarking) © 2025 Ansell Limited. All Rights Reserved.

Neither this document nor any other statement made herein by or on behalf of Ansell should be construed as a warranty of merchantability or that any Ansell product is fit for a particular purpose. Ansell assumes no responsibility for the suitability or adequacy of an end user's selection of gloves for a specific application.

