



Cut



Heat



Medium Duty

## Abrasion-resistant medium-duty safety gloves, offer wearers heat and cut resistance

- **Improved durability:** HyFlex® 11-427 medium-duty gloves boast a robust polyurethane/nitrile coating, granting wearers ANSI and EN level 4 abrasion resistance
- **Increased eco-friendliness:** Their PU/nitrile coating is made using a more environmentally conscious water-based process
- **Reduced surface defect risks:** Their silicone-free design eliminates the risk of related contaminant transfer to metal when painting
- **Minimized health risks:** These HyFlex® gloves' DMF-free formulation prevents potential health risks
- **Enhanced defenses:** Their high-visibility, high-performance fibers ensure contact heat resistance up to 100°C/212°F
- **Easy identification:** A color-coded orange HyFlex® indicator button signposts performance, indicating ANSI A2/EN ISO B cut resistance



### Industries

- Automotive
- Chemical

### Applications

- Handling metal sheets & panels
- Handling parts with sharp, rough edges
- Applying sealers, touching up
- Production line support & maintenance
- Loading and unloading trucks and vehicles
- Handling incoming goods
- Handling outgoing goods: cans, vessels, bulkpack and cartons
- Loading trucks & vehicles
- Product shipping, transport and delivery
- Maintenance
- Lock smith

Previously known as: Puretough™P3000TROPIQUE

### Key Features

- **Water-based polyurethane coating:** Durable, but more eco-conscious
- **DMF- and silicone-free:** Fewer health risks, suited to spray-painting
- **High-visibility, high-performance fibers:** Heat\* and cut resistance  
\*contact heat resistance up to 100°C/212°F

### Vulcanization Chemical Accelerators

- Natural rubber proteins (in knitwrist elastic)
- Zinc Diethyldithiocarbamate

Only a very small number of users may be sensitive to this ingredient(s) and hence may develop irritant and/or allergic contact reactions.

### Performance Standards & Regulatory Compliance



### Specifications

BRAND   STYLE	DESCRIPTION	Gauge	SIZE	LENGTH	COATING COLOR	PACKAGE
HyFlex® 11-427	<b>Finishing:</b> ¾ Coated <b>Coating Material:</b> Water-Based polyurethane and nitrile <b>Liner Material:</b> Polyamide, Fiber glass <b>Cuff Style:</b> Knitwrist	13	7, 8, 9, 10, 11	235-260mm; 9.25-10.23 inches	Grey	• 12 pairs in a bag; 12 bags in a carton

For additional information visit us at [www.ansell.com](http://www.ansell.com), or call us at

#### Europe, Middle East & Africa Region

Ansell Healthcare Europe NV  
Riverside Business Park  
Blvd International, 55  
1070 Brussels, Belgium  
T: +32 (0) 2 528 74 00  
F: +32 (0) 2 528 74 01

#### Latin America & Caribbean Region

Ansell Commercial Mexico S.A. de C.V.  
Blvd. Bernardo Quintana No. 7001-C,  
Q7001 Torre II,  
Suites 1304, 1305 y 1306,  
Col. Centro Sur, c.p. 76079  
Queretaro, Qro. Mexico  
T: +52 442 248 1544 / 248 3133

#### North America Region

Ansell Healthcare Products LLC  
111 Wood Avenue South,  
Suite 900  
Iselin, NJ 08830, USA  
T: +1 800 800 0444  
F: +1 800 800 0445

#### Canada

Ansell Canada  
105 Lauder  
Cowansville, QC J2K 2K8  
Canada  
T: +1 800 363 8340  
F: +1 800 267 3551

#### Australia

Ansell Limited  
Level 3, 678 Victoria Street,  
Richmond, Vic, 3121  
Australia  
T: +61 1800 337 041  
F: +61 1800 803 578

#### Asia Pacific Region

Ansell Global Trading Center  
(Malaysia) Sdn Bhd  
Prima 6, Prima Avenue  
Block 3512, Jalan Teknokrat 6  
T: +603 8310 6688  
F: +603 8310 6699