

## Latex exam gloves, offering robust personal protection and secure grip

- **Durable latex:** Soft, stretchable latex provides tough chemical splash protection and superior comfort
- **Secure grip:** These latex medical exam gloves have been developed with textured fingertips for a confident grip even when handling slippery, oily objects
- **Enhanced finger thickness:** 20mm/7.9 mil finger thickness results in greater protection from snags, tears and rips when compared with standard latex alternatives
- **Elevated comfort:** An extra wash during manufacturing makes these gloves smooth, comfortable and are easy to don



**CAUTION:** This product contains natural rubber latex, which may cause allergic reactions

### Industries

- Automotive
- Automotive Aftermarket
- Life Sciences

### Recommended For

- General Purpose Auto Aftermarket
- Tire rotation & changes
- Sample taking and processing
- Raw material sample collection
- Oil, fluids and filter change
- Maintaining lab furniture and equipment
- Inspection (picking, checking and marking)
- Inspection, selecting, checking parts
- Engine transmission and repair

# TECHNICAL DATA SHEET

|                                     | Product Information                                                                                                                                                                                                                                                                                                             |
|-------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Material                            | Natural Rubber Latex                                                                                                                                                                                                                                                                                                            |
| External Glove Surface              | Textured Fingers                                                                                                                                                                                                                                                                                                                |
| Audit Standards                     | ISO 13485, ISO 9001                                                                                                                                                                                                                                                                                                             |
| Product Certification               | Personal Protective Equipment Regulation (EU) 2016/425 Category III risks, EU Food Contact Approved, EC 2023/2006, EN 421:2010, EN ISO 21420:2020, EN ISO 374-1:2016 Type B KPT, EN ISO 374-5:2016 Virus, European Directive 89/686/EEC, Medical Device Regulation (EU) 2017/745 Class I, Please consult the IFU, CE 0493, UKCA |
| Packaging Overview                  | 100 gloves per dispenser<br>10 dispensers per case<br>1000 gloves per case                                                                                                                                                                                                                                                      |
| Storage Instructions                | Keep out of direct sunlight; store in a cool and dry place. Keep away from sources of ozone or ignition.                                                                                                                                                                                                                        |
| Country Of Origin                   | Malaysia                                                                                                                                                                                                                                                                                                                        |
| Product Segmentation                | Robust                                                                                                                                                                                                                                                                                                                          |
| Antistatic                          | No                                                                                                                                                                                                                                                                                                                              |
| Silicone Free                       | No                                                                                                                                                                                                                                                                                                                              |
| Vulcanization Chemical Accelerators | <ul style="list-style-type: none"> <li>Zinc Dibutyldithiocarbamate (ZDBC)</li> <li>Zinc Diethyldithiocarbamate (ZDEC)</li> </ul> <p><i>Only a very small number of users may be sensitive to this ingredient(s) and hence may develop irritant and/or allergic contact reactions.</i></p>                                       |

## PHYSICAL PROPERTIES

|                                         | Typical Values |             | Testing Method                 |
|-----------------------------------------|----------------|-------------|--------------------------------|
| Length (mm/inches)                      | 245 / 9.65     |             | ASTM D3767, ASTM D6977, EN 420 |
| Freedom from Holes (Inspection level I) | 1.5 AQL        |             | ASTM D5151, EN 455-1           |
| Palm Thickness (mm/mils)                | 0.16 / 6.3     |             | ASTM D3767, EN 420             |
| Finger Thickness (mm/mils)              | 0.20 / 7.9     |             | ASTM D3767, EN 420             |
|                                         | BEFORE AGING   | AFTER AGING |                                |
| Elongation at Break (%)                 | ≥ 750          | ≥ 600       | ASTM D412                      |
| Force at break (N)                      | ≥ 6            | ≥ 6         | EN 455-2                       |

ORDERING INFORMATION

| Size         | XS (5.5 - 6) | S (6.5 - 7) | M (7.5 - 8) | L (8.5 - 9) | XL (9.5 - 10) |
|--------------|--------------|-------------|-------------|-------------|---------------|
| Product Code | 63864060     | 63864070    | 63864080    | 63864090    | 63864100      |

Performance Standards and Regulatory Compliance



For additional information visit us at [www.ansell.com](http://www.ansell.com), or call us at

Europe, Middle East & Africa Region

Ansell Healthcare Europe NV  
T: +32 (0) 2 528 74 00  
F: +32 (0) 2 528 74 01

Asia Pacific Region

MY: +603 8310 6688  
apac.medical@ansell.com  
CN: +86 21 38275000  
infochina@ansell.com  
JP: +813 5549 8151  
info.medical.jp@ansell.com

North America Region

Ansell Healthcare Products LLC  
T: +1 800 800 0444  
F: +1 800 800 0445

Latin America & Caribbean Region

BR: +55 (11) 3356-3100  
latam.medical@ansell.com  
MX: +52 442 296 2050  
latam.medical@ansell.com  
CO: +57 1 288 3247  
latam.medical@ansell.com

Australia

Ansell Limited  
T: +61 1800 337 041  
F: +61 1800 803 578

Russia

Ansell PYC  
Ten. +7 495 258 13 16

Ansell, ® and ™ are trademarks owned by Ansell Limited or one of its affiliates. US Patented and US and non-US Patents Pending: [www.ansell.com/patentmarking](http://www.ansell.com/patentmarking) © 2025 Ansell Limited. All Rights Reserved.

Neither this document nor any other statement made herein by or on behalf of Ansell should be construed as a warranty of merchantability or that any Ansell product is fit for a particular purpose. Ansell assumes no responsibility for the suitability or adequacy of an end user's selection of gloves for a specific application.

