

Lightweight latex gloves that provide superior comfort and tactility

- **Exceptional fit and feel:** Made from high-quality elastic latex, TouchNTuff™ 69-318 gloves offer superior comfort
- **Heightened sensitivity:** The thin design provides excellent tactility when compared to standard latex gloves
- **Secure handling:** Fully textured surface allows wearers to securely grip tools, small objects and delicate instruments to be changed
- **Food handling compliance:** These gloves are food-handling compliant, and thus are suitable for a wide variety of food handling applications



CAUTION: This product contains natural rubber latex, which may cause allergic reactions

Industries

- Life Sciences
- Food Processing

Recommended For

- All food processing, applications that have food contact
- Meat, Fish and Food Processing
- Sample taking and processing
- Testing
- Vehicle maintenance
- Secondary food processing
- Food contact
- Food processing and handling

TECHNICAL DATA SHEET

Product Information	
Material	Natural Rubber Latex
External Glove Surface	Fully Textured
Audit Standards	ISO 13485, ISO 9001
Product Certification	Category III, EN ISO 21420:2020, EN ISO 374-1:2016 Type B KPT, EN ISO 374-5:2016 Virus, FDA21 CFR 177-2600-US Food Contact Approved, EU Food Contact Approved, ISO 13485, ISO 9001, UKCA
Packaging Overview	100 gloves per dispenser 10 dispensers per case 1000 gloves per case
Storage Instructions	Keep out of direct sunlight; store in a cool and dry place. Keep away from sources of ozone or ignition.
Country Of Origin	Malaysia
Product Segmentation	Multi-Purpose
Antistatic	Not Tested
Silicone Free	Yes
RightCycle	Yes
Vulcanization Chemical Accelerators	• Zinc Diethyldithiocarbamate (ZDEC) • Zinc Dibutyldithiocarbamate (ZDBC) • Natural rubber proteins <i>Only a very small number of users may be sensitive to this ingredient(s) and hence may develop irritant and/or allergic contact reactions.</i>

PHYSICAL PROPERTIES

	Typical Values		Testing Method
Length (mm/inches)	240 / 9.45		ASTM D3767,EN 420
Freedom from Holes (Inspection level I)	1.5 AQL		ASTM D5151,EN 455-1
Palm Thickness (mm/mils)	0.14 / 5.5		ASTM D3767,EN 420
Finger Thickness (mm/mils)	0.17 / 6.7		ASTM D3767,EN 420
	BEFORE AGING	AFTER AGING	
Elongation at Break (%)	≥ 650	≥ 500	ASTM D412

ORDERING INFORMATION

Size	XS (5.5 - 6)	S (6.5 - 7)	M (7.5 - 8)	L (8.5 - 9)	XL (9.5 - 10)
Product Code	69318060	69318070	69318080	69318090	69318100

Performance Standards and Regulatory Compliance

EN ISO 374-1:2016
Type B


K P T

EN ISO 374-5


VIRUS



ISO 9001



ISO 13485



ISO 10993-10



ISO 10993-23



ISO 16604



UK
CA



For additional information visit us at www.ansell.com, or call us at

Europe, Middle East & Africa Region
Ansell Healthcare Europe NV
T: +32 (0) 2 528 74 00
F: +32 (0) 2 528 74 01

Asia Pacific Region
MY: +603 8310 6688
apac.medical@ansell.com
CN: +86 21 38275000
infochina@ansell.com
JP: +813 5549 8151
info.medical.jp@ansell.com

North America Region
Ansell Healthcare Products LLC
T: +1 800 800 0444
F: +1 800 800 0445

Latin America & Caribbean Region
BR: +55 (11) 3356-3100
latam.medical@ansell.com
MX: +52 442 296 2050
latam.medical@ansell.com
CO: +57 1 288 3247
latam.medical@ansell.com

Australia
Ansell Limited
T: +61 1800 337 041
F: +61 1800 803 578

Russia
Ansell PYC
Ten. +7 495 258 13 16

Ansell, ® and ™ are trademarks owned by Ansell Limited or one of its affiliates. US Patented and US and non-US Patents Pending: www.ansell.com/patentmarking © 2025 Ansell Limited. All Rights Reserved.

Neither this document nor any other statement made herein by or on behalf of Ansell should be construed as a warranty of merchantability or that any Ansell product is fit for a particular purpose. Ansell assumes no responsibility for the suitability or adequacy of an end user's selection of gloves for a specific application.

