

## Reliable hand protection, offering elasticity and comfort

- **Comfortable fit:** These gloves are made of soft and stretchy latex, providing reliable protection, dexterity, elasticity and comfort
- **Secure grip:** The fully textured surface of the gloves provides an enhanced grip
- **Easy donning:** The polymer-coated interior allows for easy donning and doffing
- **Genuine versatility:** Applicable for multi-purpose use across a variety of industries — also available across a broad selection of sizes



**CAUTION:** This product contains natural rubber latex, which may cause allergic reactions

### Industries

- Food Processing
- Automotive

### Recommended For

- Catering/Meal preparation
- Transferring liquids
- Sample taking and processing
- Food processing and handling
- Janitorial, clean up and maintenance
- Inspection, selecting, checking parts
- Adjusting parts and systems
- Equipment repair and maintenance

# TECHNICAL DATA SHEET

Product Information	
Material	Natural Rubber Latex
External Glove Surface	Fully Textured
Audit Standards	ISO 13485, ISO 9001
Product Certification	Medical Device Regulation (EU) 2017/745 Class I, Personal Protective Equipment Regulation (EU) 2016/425 Category III risks, ASTM D3578, EC 2023/2006, EU Food Contact Approved, EN ISO 21420:2020, EN ISO 374-1:2016 Type C Chemical, EN ISO 374-5:2016 Virus, FDA21 CFR 177-2600-US Food Contact Approved, ISO 13485, ISO 9001
Packaging Overview	100 gloves per dispenser 10 dispensers per case 1000 gloves per case
Storage Instructions	Keep out of direct sunlight; store in a cool and dry place. Keep away from sources of ozone or ignition.
Country Of Origin	Malaysia
Product Segmentation	Multi-Purpose
Antistatic	No
Silicone Free	No

## PHYSICAL PROPERTIES

	Typical Values		Testing Method
Length (mm/inches)	240 / 9.45		ASTM D3578,EN 455-2
Freedom from Holes (Inspection level I)	4.0 AQL		ASTM D5151
Palm Thickness (mm/mils)	0.13/5.1		ASTM D3578,EN 455-2
Finger Thickness (mm/mils)	0.15/5.9		ASTM D3578,EN 455-2
	<b>BEFORE AGING</b>	<b>AFTER AGING</b>	
Elongation at Break (%)	≥ 650	≥ 500	ASTM D412 & D573
Force at break (N)	≥ 6	≥ 6	EN 455-2

For additional information visit us at [www.ansell.com](http://www.ansell.com), or call us at

#### Europe, Middle East & Africa Region

Ansell Healthcare Europe NV

T: +32 (0) 2 528 74 00

F: +32 (0) 2 528 74 01

#### Asia Pacific Region

MY +603 8310 6688

apac.medical@ansell.com

CN: +86 21 38275000

infochina@ansell.com

JP: +813 5549 8151

info.medical.jp@ansell.com

#### North America Region

Ansell Healthcare Products LLC

T: +1 800 800 0444

F: +1 800 800 0445

#### Latin America & Caribbean Region

BR +55 (11) 3356-3100

latam.medical@ansell.com

MX: +52 442 296 2050

latam.medical@ansell.com

CO: +57 1 288 3247

latam.medical@ansell.com

#### Australia

Ansell Limited

T: +61 1800 337 041

F: +61 1800 803 578

#### Russia

Ansell PYC

Ten. +7 495 258 13 16

Ansell, ® and ™ are trademarks owned by Ansell Limited or one of its affiliates. US Patented and US and non-US Patents Pending: [www.ansell.com/patentmarking](http://www.ansell.com/patentmarking) © 2025 Ansell Limited. All Rights Reserved.

Neither this document nor any other statement made herein by or on behalf of Ansell should be construed as a warranty of merchantability or that any Ansell product is fit for a particular purpose. Ansell assumes no responsibility for the suitability or adequacy of an end user's selection of gloves for a specific application.

