

Extended, chemical-resistant disposable neoprene gloves, with superb wet and dry grip performance

- **Specialized protection:** Provides strong chemical splash protection from most acids and alcohols and EN 374 Type B chemical resistance certification
- **Strong grip:** Textured fingertips and neoprene material enhance grip performance in wet and dry environments
- **Reduced allergy risk:** Non-latex formulation prevents Type 1 (latex) allergic reactions
- **Easy donning:** Polymer-coated, these MICROFLEX™ gloves are easy to don
- **Extended protection:** MICROFLEX™ NeoTouch™ 25-201 gloves' extended cuff also provides greater forearm and wrist protection



Industries

- Life Sciences

Recommended For

- Transferring liquids and solids
- Sample taking and processing
- Testing

TECHNICAL DATA SHEET

| Product Information | |
|------------------------|--|
| Material | Neoprene |
| External Glove Surface | Textured Fingers |
| Audit Standards | ISO 13485 |
| Product Certification | ASTM D6977, CE 0493, EN 421:2010, EN ISO 21420:2020, EN ISO 374-1:2016 Type B KPT, EN ISO 374-5:2016 Virus, ISO 13485, UKCA, FDA21 CFR 177-2600-US Food Contact Approved, Please consult the IFU |
| Packaging Overview | 100 gloves per dispenser 10 dispensers per case 1000 gloves per case |
| Storage Instructions | Keep out of direct sunlight; store in a cool and dry place. Keep away from sources of ozone or ignition. |
| Country Of Origin | Indonesia |
| Product Segmentation | High Risk |
| Antistatic | Yes EN1149 |
| Silicone Free | No |


PHYSICAL PROPERTIES

| | Typical Values | | Testing Method |
|---|---------------------|--------------------|---------------------|
| Length (mm/inches) | 285 / 11.2 | | ASTM D3767,EN 420 |
| Freedom from Holes (Inspection level I) | 1.5 AQL | | ASTM D5151,EN 455-1 |
| Palm Thickness (mm/mils) | 0.13 | | ASTM D3767,EN 420 |
| Finger Thickness (mm/mils) | 0.16 | | ASTM D3767,EN 420 |
| | BEFORE AGING | AFTER AGING | |
| Elongation at Break (%) | ≥ 700 | ≥ 600 | ASTM D412 |
| Force at break (N) | ≥ 3.6 | ≥ 3.6 | |

ORDERING INFORMATION

| Size | XS (5.5 - 6) | S (6.5 - 7) | M (7.5 - 8) | L (8.5 - 9) | XL (9.5 - 10) |
|--------------|--------------|-------------|-------------|-------------|---------------|
| Product Code | 25201060 | 25201070 | 25201080 | 25201090 | 25201100 |

Performance Standards and Regulatory Compliance



For additional information visit us at www.ansell.com, or call us at

Europe, Middle East & Africa Region

Ansell Healthcare Europe NV

T: +32 (0) 2 528 74 00

F: +32 (0) 2 528 74 01

Asia Pacific Region

MY +603 8310 6688

apac.medical@ansell.com

CN: +86 21 38275000

infochina@ansell.com

JP: +813 5549 8151

info.medical.jp@ansell.com

North America Region

Ansell Healthcare Products LLC

T: +1 800 800 0444

F: +1 800 800 0445

Latin America & Caribbean Region

BR +55 (11) 3356-3100

latam.medical@ansell.com

MX: +52 442 296 2050

latam.medical@ansell.com

CO: +57 1 288 3247

latam.medical@ansell.com

Australia

Ansell Limited

T: +61 1800 337 041

F: +61 1800 803 578

Russia

Ansell PYC

Ten. +7 495 258 13 16

Ansell, ® and ™ are trademarks owned by Ansell Limited or one of its affiliates. US Patented and US and non-US Patents Pending; www.ansell.com/patentmarking © 2025 Ansell Limited. All Rights Reserved.

Neither this document nor any other statement made herein by or on behalf of Ansell should be construed as a warranty of merchantability or that any Ansell product is fit for a particular purpose. Ansell assumes no responsibility for the suitability or adequacy of an end user's selection of gloves for a specific application.

