

92-600

Disposable Nitrile Glove with Enhanced Chemical Splash Protection

An unparalleled combination of chemical splash protection, comfort and durability

- World leader: TouchNTuff[®] 92-600 gloves are the world's leading disposable gloves for chemical splash protection
- **Superior protection:** Made with TNT[™] Chemical Splash Resistance Technology, these gloves effectively safeguard hands from exposure to harmful chemicals
- **Elevated comfort:** Super soft nitrile provides a comfortable feel during extended wear
- Robust durability: Proprietary formulation is extra-strong to prevent tearing during heavyduty work
- Prevents surface defects: Silicone-free, they prevent contaminant transfer that causes flaws in paints, coatings and finishes



Industries

- Life Sciences
- Food Processing
- Automotive
- Machinery and Equipment
- Chemical
- Agriculture
- Utilities
- Warehousing

Recommended For

- Transferring liquids and solids
- Sample taking and processing
- Meat, Fish and Food Processing
- Industrial Production
- Maintenance
- Laboratory analysis
- Chemical Handling



TECHNICAL DATA SHEET

| | Product Information |
|------------------------|--|
| External Glove Surface | Smooth |
| Audit Standards | ISO 9001 |
| Packaging Overview | 100 gloves per dispenser 10 dispensers per case 1000 gloves per case |
| Storage Instructions | Keep out of direct sunlight; store in a cool and dry place. Keep away from sources of ozone or ignition. |
| Country Of Origin | Sri Lanka, Thailand |
| Product Segmentation | Robust |
| Antistatic | Yes EN1149 |

PHYSICAL PROPERTIES

| | Typical | Testing Method | |
|---|--|---------------------|------------------|
| Length (mm/inches) | 240 / | ASTM D3767,EN 420 | |
| Freedom from Holes (Inspection level I) | 4.0 AQL (North & South America) / 1. Asia, P. | ASTM D5151,EN 455-1 | |
| Palm Thickness (mm/mils) | 0.125 | ASTM D3767,EN 420 | |
| Finger Thickness (mm/mils) | 0.14 | ASTM D3767,EN 420 | |
| | BEFORE AGING | AFTER AGING | |
| Ultimate Tensile Strength (MPa) | ≥ 18 | ≥ 18 | ASTM D412 & D573 |
| Elongation at Break (%) | ≥ 500 | ≥ 400 | ASTM D412 |
| Force at break (N) | ≥ 6 | ≥ 6 | EN 455-2 |

ORDERING INFORMATION

| Size | S (6.5 - 7) | M (7.5 - 8) | L (8.5 - 9) | XL (9.5 - 10) |
|--------------|-------------|-------------|-------------|---------------|
| Product Code | 92600070 | 92600080 | 92600090 | 92600100 |

Performance Standards and Regulatory Compliance











For additional information visit us at www.ansell.com, or call us at

Europe, Middle East & Africa Region Ansell Healthcare Europe NV T: +32 (0) 2 528 74 00 F: +32 (0) 2 528 74 01 Asia Pacific Region MY +603 8310 6688

MY +603 8310 6688 apac.medical@ansell.com CN: +86 21 38275000 infochina@ansell.com JP: +813 5549 8151 info.medical.jo@ansell.com North America Region
Ansell Healthcare Products LLC
T: +1 800 800 0444
F: +1 800 800 0445
Latin America & Caribbean Region

BR +55 (11) 3356-3100 latam.medical@ansell.com MX: +52 442 296 2050 latam.medical@ansell.com CO: +57 1 288 3247 latam.medical@ansell.com Australia
Ansell Limited
T: +61 1800 337 041
F: +61 1800 803 578
Russia
Ansell PYC

Ten. +7 495 258 13 16

Technology



Ansell, ® and TM are trademarks owned by Ansell Limited or one of its affiliates. US Patented and US and non-US Patents Pending: www.ansell.com/patentmarking © 2024 Ansell Limited. All Rights Reserved.

Neither this document nor any other statement made herein by or on behalf of Ansell should be construed as a warranty of merchantability or that any Ansell product is fit for a particular purpose. Ansell assumes no responsibility for the suitability or adequacy of an end user's selection of gloves for a specific application.

