## TOUCHNTuff® Advanced product & worker protection

**93-250** Dark Grey Disposable Nitrile Glove with Ansell Grip<sup>™</sup> Technology

# Tough disposable hand protection offering superior wet, oily and dry grip

- Reduces gripping effort: Designed with ANSELL GRIP<sup>™</sup> Technology, lab tests show 80% less finger force and 33% less palm force is required to hold objects when wearing these gloves
- Superior durability and productivity: The strong material helps increase productivity by preventing slippage when handling wet, dry or oily equipment in tough environments
- Elevated comfort: Soft nitrile enhances comfort when wearing gloves during long shifts
- **Prevents surface defects:** Silicone-free, they prevent contaminant transfer that causes flaws in paints, coatings and finishes
- Reliable chemical splash protection: TouchNTuff<sup>®</sup> 93-250 gloves protect against accidental exposure to a range of acids, bases and solvents



#### Industries

- Automotive Aftermarket
- Life Sciences
- Chemical

#### **Recommended For**

- General Purpose Auto Aftermarket
- Oil, fluids and filter change
- Engine transmission and repair
- Spill or leakage cleanup
- Transferring liquids and solids
- Transferring liquids
- Sample taking and processing
- Product shipping, transport and delivery
- Testing
- Maintenance



### **TECHNICAL DATA SHEET**

	Product Information
External Glove Surface	Textured Fingers
Audit Standards	ISO 9001
Packaging Overview	100 gloves per dispenser 10 dispensers per case 1000 gloves per case
Storage Instructions	Keep out of direct sunlight; store in a cool and dry place. Keep away from sources of ozone or ignition.
Country Of Origin	Malaysia
Product Segmentation	Robust
Antistatic	Yes EN1149

#### **PHYSICAL PROPERTIES**

	Typical	Testing Method	
Length (mm/inches)	245 ,	ASTM D3767,EN 420	
Freedom from Holes (Inspection level I)	1.5	ASTM D5151,EN 455-1	
Palm Thickness (mm/mils)	0.13	ASTM D3767,EN 420	
Finger Thickness (mm/mils)	0.20	ASTM D3767,EN 420	
	<b>BEFORE AGING</b>	AFTER AGING	
Ultimate Tensile Strength (MPa)	≥ 36	≥ 25	ASTM D412 & D573
Elongation at Break (%)	≥ 590	≥ 520	ASTM D412
Force at break (N)	≥ 10	≥ 9	EN 455-2

#### **ORDERING INFORMATION**

Size	XS (5.5 - 6)	S (6.5 - 7)	M (7.5 - 8)	L (8.5 - 9)	XL (9.5 - 10)
Product Code	93250060	93250070	93250080	93250090	93250100

#### **Performance Standards and Regulatory Compliance**



#### For additional information visit us at www.ansell.com, or call us at

Europe, Middle East & Africa Region Ansell Healthcare Europe NV T: +32 (0) 2 528 74 00 F: +32 (0) 2 528 74 01 Asia Pacific Region MY +603 8310 6688 apac.medica@ansell.com CN: +86 21 38275000 infochina@ansell.com JP: +813 5549 8151 info.medicalio@ansell.com 
 North America Region

 Ansell Healthcare Products LLC

 T: +1 800 800 0444

 F: +1 800 800 0445

 Latin America & Caribbean Region

 BR +55 (11) 3356-3100

 latam.medica@ansell.com

 MX: +52 442 296 2050

 latam.medica@ansell.com

 C0: +57 1 288 3247

 latam.medica@ansell.com

Australia Ansell Limited T: +61 1800 337 041 F: +61 1800 803 578 Russia

Ansell PYC Ten. +7 495 258 13 16

#### Technology



Ansell, (8) and TM are trademarks owned by Ansell Limited or one of its affiliates. US Patented and US and non-US Patents Pending: www.ansell.com/patentmarking © 2024 Ansell Limited. All Rights Reserved.

Neither this document nor any other statement made herein by or on behalf of Ansell should be construed as a warranty of merchantability or that any Ansell product is fit for a particular purpose. Ansell assumes no responsibility for the suitability or adequacy of an end user's selection of gloves for a specific application.

