

## Robust nitrile exam gloves, ensuring hand protection for diverse applications

- **Improved durability:** MICROFLEX™ 93-843 exam gloves are made with a strong nitrile formulation, offering wearers robust personal protection
- **Strong grip:** These gloves' textured fingertips ensure better grip when handling tools and equipment
- **Low AQL:** 0.65 AQL means these gloves offer excellent barrier protection against potentially hazardous substances



### Industries

- Automotive
- Automotive Aftermarket
- Life Sciences
- Healthcare
- Fire and Rescue

### Recommended For

- General Purpose Auto Aftermarket
- Tire rotation & changes
- Sample taking and processing
- Raw material sample collection
- Protection from Type I latex allergy in HCW's or patients
- Oil, fluids and filter change
- Maintaining lab furniture and equipment
- Higher-risk clinical applications
- Inspection, selecting, checking parts
- Assembly and inspection of components
- Picking and fastening components
- Equipment repair and maintenance
- Engine transmission and repair
- Assembly of parts
- Extra protection over the wrist and arm

# TECHNICAL DATA SHEET

Product Information	
<b>Material</b>	Nitrile
<b>External Glove Surface</b>	Textured Fingers
<b>Product Certification</b>	Medical Device Regulation (EU) 2017/745 Class I, Personal Protective Equipment Regulation (EU) 2016/425 Category III risks, EC 2023/2006, EC 1935/2004, EN 1149-1/2/3, EN 455 1-4, EN ISO 21420:2020, EN ISO 374-1:2016 Type B JKPT, EN ISO 374-5:2016 Virus, ISO 11193, ISO 18889:2019, EU Food Contact Approved
<b>Packaging Overview</b>	100 gloves per dispenser 10 dispensers per case 1000 gloves per case
<b>Storage Instructions</b>	Keep out of direct sunlight; store in a cool and dry place. Keep away from sources of ozone or ignition.
<b>Country Of Origin</b>	Malaysia
<b>Product Segmentation</b>	Robust
<b>Antistatic</b>	Yes EN1149
<b>Silicone Free</b>	No

## PHYSICAL PROPERTIES

	Typical Values		Testing Method
	BEFORE AGING	AFTER AGING	
Length (mm/inches)	245 / 9.65		ASTM D3767,EN 420
Freedom from Holes (Inspection level I)	0.65 AQL		ASTM D5151,EN 455-1
Palm Thickness (mm/mils)	0.11 / 4.3		ASTM D3767,EN 420
Finger Thickness (mm/mils)	0.18 / 7.1		ASTM D3767,EN 420
Elongation at Break (%)	550	500	ASTM D412
Force at break (N)	12	9	EN 455-2

## ORDERING INFORMATION

Size	XS (5.5 - 6)	S (6.5 - 7)	M (7.5 - 8)	L (8.5 - 9)	XL (9.5 - 10)
Product Code	93843060	93843070	93843080	93843090	93843100

### Performance Standards and Regulatory Compliance



### For additional information visit us at [www.ansell.com](http://www.ansell.com), or call us at

#### Europe, Middle East & Africa Region

Ansell Healthcare Europe NV  
T: +32 (0) 2 528 74 00  
F: +32 (0) 2 528 74 01

#### Asia Pacific Region

MY: +603 8310 6688  
apac.medical@ansell.com  
CN: +86 21 38275000  
infochina@ansell.com  
JP: +813 5549 8151  
info.medical.jp@ansell.com

#### North America Region

Ansell Healthcare Products LLC  
T: +1 800 800 0444  
F: +1 800 800 0445

#### Latin America & Caribbean Region

BR: +55 (11) 3356-3100  
latam.medical@ansell.com  
MX: +52 442 296 2050  
latam.medical@ansell.com  
CO: +57 1 288 3247  
latam.medical@ansell.com

#### Australia

Ansell Limited  
T: +61 1800 337 041  
F: +61 1800 803 578

#### Russia

Ansell PYC  
Ten. +7 495 258 13 16

Ansell, ® and ™ are trademarks owned by Ansell Limited or one of its affiliates. US Patented and US and non-US Patents Pending; [www.ansell.com/patentmarking](http://www.ansell.com/patentmarking) © 2025 Ansell Limited. All Rights Reserved.

Neither this document nor any other statement made herein by or on behalf of Ansell should be construed as a warranty of merchantability or that any Ansell product is fit for a particular purpose. Ansell assumes no responsibility for the suitability or adequacy of an end user's selection of gloves for a specific application.

