

Blue nitrile gloves with raised texture surface, offering confident wet, dry and oily grip

- **Strong grip:** Thanks to a Mega Texture surface, MICROFLEX™ 93-283 disposable gloves boast secure grip, for handling wet, oily, or fatty objects
- **Tear-resistant:** These nitrile gloves' 0.2mm/8 mil thickness increases their resistance to tears
- **Food handling compliance:** Certified as food handling gloves, these gloves are ideal for a wide range of food handling applications
- **Ideal for double donning:** Their generous fit allows them to be worn comfortably over thermal or cut-resistant gloves
- **Expanded protection:** Added forearm and wrist protection is provided by an extended cuff design



Industries

- Food Processing
- Automotive Aftermarket
- Machinery and Equipment

Recommended For

- General Purpose Auto Aftermarket
- Chemical Splash
- Production line support and maintenance
- Use as an underglove when double gloving
- Vehicle maintenance
- Packaging and labeling
- Handling of frozen foods
- Janitorial, clean up and maintenance
- Handling of machined parts coated with light oil
- Maintenance of plant and machines
- Chemical Handling
- Enhanced grip in wet environments

TECHNICAL DATA SHEET

	Product Information
Material	Nitrile
External Glove Surface	Raised Diamond Grip Pattern
Audit Standards	ISO 13485, ISO 9001
Product Certification	Medical Device Regulation (EU) 2017/745 Class I, Personal Protective Equipment Regulation (EU) 2016/425 Category III risks, ASTM D6319, CE 0493, EC 2023/2006, EU Food Contact Approved, EN ISO 21420:2020, EN ISO 374-1:2016 Type B JKPT, EN ISO 374-5:2016 Virus, ISO 9001, ISO 13485, ISO 18889:2019, UKCA
Packaging Overview	50 gloves per dispenser 10 dispensers per case 500 gloves per case 2XL and 3XL: 44 gloves per dispenser 440 gloves per case
Storage Instructions	Keep out of direct sunlight; store in a cool and dry place. Keep away from sources of ozone or ignition.
Country Of Origin	Thailand
Product Segmentation	High Risk
Antistatic	Yes EN1149
Silicone Free	No

PHYSICAL PROPERTIES

	Typical Values		Testing Method
Length (mm/inches)	300 / 12		ASTM D3767,EN 420
Freedom from Holes (Inspection level I)	1.5 AQL		ASTM D5151,EN 374-2
Palm Thickness (mm/mils)	0.20/7.9		ASTM D3767,EN 420
Finger Thickness (mm/mils)	0.24/9.4		ASTM D3767,EN 420
	BEFORE AGING	AFTER AGING	
Elongation at Break (%)	500	400	ASTM D412
Force at break (N)	>6	>6	EN 455-2

ORDERING INFORMATION

Size	S (6.5 - 7)	M (7.5 - 8)	L (8.5 - 9)	XL (9.5 - 10)	XXL (10.5 - 11)	XXXL (11.5 - 12)
Product Code	93283070	93283080	93283090	93283100	93283110	93283120

Performance Standards and Regulatory Compliance



For additional information visit us at www.ansell.com, or call us at

Europe, Middle East & Africa Region

Ansell Healthcare Europe NV
T: +32 (0) 2 528 74 00
F: +32 (0) 2 528 74 01

Asia Pacific Region

MY: +603 8310 6688
apac.medical@ansell.com
CN: +86 21 38275000
infochina@ansell.com
JP: +813 5549 8151
info.medical.jp@ansell.com

North America Region

North America Region
Ansell Healthcare Products LLC
T: +1 800 800 0444
F: +1 800 800 0445

Latin America & Caribbean Region

BR: +55 (11) 3356-3100
latam.medical@ansell.com
MX: +52 442 296 2050
latam.medical@ansell.com
CO: +57 1 288 3247
latam.medical@ansell.com

Australia

Australia
Ansell Limited
T: +61 1800 337 041
F: +61 1800 803 578

Russia

Ansell PYC
Ten. +7 495 258 13 16

Ansell, ® and ™ are trademarks owned by Ansell Limited or one of its affiliates. US Patented and US and non-US Patents Pending:
www.ansell.com/patentmarking © 2025 Ansell Limited. All Rights Reserved.

Neither this document nor any other statement made herein by or on behalf of Ansell should be construed as a warranty of merchantability or that any Ansell product is fit for a particular purpose. Ansell assumes no responsibility for the suitability or adequacy of an end user's selection of gloves for a specific application.

