

**85-302** Non-clean/Non-sterile CSM RABS/Isolator Gloves

# Chemical-resistant cleanroom gloves, offering robust hand protection

Port size: 254mm/10" Thickness: 0.4mm/16 mil

- **Specialized defenses:** The AlphaTec® CSM Isolator Glove 85-302 is highly resistant against concentrated acids and bases, helping keep wearers safe
- Elevated comfort: These isolator gloves are made from soft, flexible material, for greater comfort and ease of use
- Prolonged glove life: The AlphaTec® CSM Isolator Glove 85-302 can tolerate sustained exposure to oxygen, UV rays and ozone without rapid wear, and they offer EN 388:2016+A1:2018 Level 3 abrasion resistance
- Reduced contamination risks: These CSM gloves' white coloring also results in easier detection of potential contamination

#### **KEY FEATURES & BENEFITS**

- Robust CSM composition: Protection from concentrated acids and bases
- Flexible material: For isolator gloves offering usability and comfort
- **Durable design:** Tolerates sustained oxygen, UV ray and ozone exposure





# AlphaTec® Advanced chemical protection

### **TECHNICAL DATA SHEET**

Product Reference	85-302
Material	Chlorosulfonated polyethylene_CSM
Color	White
Shape	Ambidextrous
External Glove Surface	Smooth
Cuff Style	Beaded
Storage Instructions	Store in a dry and dark environment, temperature of 5°C to 22°C. Retain in original packaging when not in use.
Available Sizes	11, 9.5
Temperature Range	From -20°C to 120°C
Shelf Life	Three (3) years from date of manufacture.
Standards	CE 0493, EN 388:2016 +A1:2018, EN ISO 21420:2020, EN ISO 374-1:2016 Type B, EN ISO 374- 5:2016, Category III

## Alpha **EC**<sup>®</sup> ADVANCED CHEMICAL PROTECTION

#### **PHYSICAL PROPERTIES**

	Typical Values	Testing Method
Typical Length (mm/in)	800 mm / 32in	EN ISO 21420
Port Size	10"	
Target Single Wall Palm Thickness (mm/mil)	0.4 mm /16 mil	EN 455-2
Target Single Wall Cuff Thickness (mm/mil)	0.4 mm / 16 mil	EN 455-2

#### **PROTECTION AGAINST MECHANICAL RISKS, EN 388:2016+A1:2018**

Risk	Performance level	
Abrasion Resistance	Level 3	
Blade Cut Resistance	Level 1	
Tear Resistance	Level O	
Puncture Resistance	Level 1	

#### **ORDERING INFORMATION**

	PORT SIZE	10"/254mm	10"/254mm
	SIZE	9.5	11
85-302	REORDER NO.	85302095	85302110

#### For additional information visit us at www.ansell.com, or call us at

#### Europe, Middle East & Africa Region Ansell Healthcare Europe NV T: +32 (0) 2 528 74 00 F: +32 (0) 2 528 74 01

Asia Pacific Region Ansell Global Trading Center T: +603 8310 6688 F: +603 8310 6699 North America Region Ansell Healthcare Products LLC US T: +1 800 800 0444 US F: +1 800 800 0445 CA T: +1-800-363-8340

Latin America & Caribbean Region Ansell Commercial Mexico S.A. de C.V. T: +52 442 248 1544 / 248 3133 Australia Ansell Limited T: +61 1800 337 041 F: +61 1800 803 578 UΚ

Ansell Nitritex T: +44 1638 663338 F: +44 1638 668890

#### **Performance Standards and Regulatory Compliance**





Ansell, <sup>®</sup> and <sup>™</sup> are trademarks owned by Ansell Limited or one of its affiliates. US Patented and US and non-US Patents Pending: www.ansell.com/patentmarking © 2024 Ansell Limited. All Rights Reserved.

Neither this document nor any other statement made herein by or on behalf of Ansell should be construed as a warranty of merchantability or that any Ansell product is fit for a particular purpose. Ansell assumes no responsibility for the suitability or adequacy of an end user's selection of gloves for a specific application.

