

85-602Non-clean/Non-sterile EPDM Plus RABS/Isolator Gloves

FDA approved polymer EPDM+ RABS and Isolator gloves, with dual-colored design

AlphaTec® EPDM Plus RABS and Isolator gloves have a dual-layered breach detection system: unique white material on a black lining; are design from high quality material, in compliance with FDA Food Contact regulations (FDA Positive List) 21 CFR 177 Indirect Food Additives; and are designed for repeated autoclave sterilization (up to 50 times), reducing the need for glove replacements.

KEY FEATURES & BENEFITS

- Dual-layered/dual-colored white-onblack design: Simpler breach detection
- EPDM Plus composition: Suited to repeated autoclave sterilization
- Chemical resistance: Hydrogen peroxide/common disinfecting chemicals





85-602

Non-clean/Non-sterile EPDM Plus RABS/Isolator Gloves

TECHNICAL DATA SHEET

Product Reference	85-602		
Material	Ethylene propylene diene rubber_EPDM plus		
Color	White Exterior, Black Interior		
Shape	Ambidextrous		
External Glove Surface	Smooth		
Cuff Style	Beaded		
Storage Instructions	Store in a dry and dark environment, temperature of 5°C to 22°C. Retain in original packaging when not in use.		
Available Sizes	9.5, 11		
Temperature Range	From -20°C to 130°C		
Cleanroom Class	Non-Critical Environment		
Shelf Life	Three (3) years from date of manufacture.		
Tested For Use With Chemotherapy Drugs	No		
Standards	CE 0493, EN 388:2003, EN 388:2016 +A1:2018, EN ISO 21420:2020, EN ISO 374-1:2016, EN ISO 374-1:2016 Type B, EN ISO 374-5:2016, EN 388:2016, Category III		





85-602

Non-clean/Non-sterile EPDM Plus RABS/Isolator Gloves

PHYSICAL PROPERTIES

	Typical Values	Testing Method
Typical Length (mm/in)	800mm/32mil	
Port Size	12"	
Target Single Wall Palm Thickness (mm/mil)	0.51 mm / 20 mil	
Target Single Wall Cuff Thickness (mm/mil)	0.51 mm / 20 mil	

PROTECTION AGAINST MECHANICAL RISKS, EN 388:2016+A1:2018

Risk	Performance level	
Abrasion Resistance	Level 3	
Blade Cut Resistance	Level 1	
Tear Resistance	Level O	
Puncture Resistance	Level O	

ORDERING INFORMATION

	PORT SIZE	12"/305mm	12"/305mm
	SIZE	9.5	11
85-602	REORDER NO.	85602095	85602110

Performance Standards and Regulatory Compliance









For additional information visit us at www.ansell.com, or call us at

Europe, Middle East & Africa Region

Ansell Healthcare Europe NV T: +32 (0) 2 528 74 00 F: +32 (0) 2 528 74 01

Asia Pacific Region

Ansell Global Trading Center T: +603 8310 6688 F: +603 8310 6699

North America Region

Ansell Healthcare Products LLC US T: +1 800 800 0444 US F: +1 800 800 0445 CA T: +1-800-363-8340

Latin America & Caribbean Region

Ansell Commercial Mexico S.A. de C.V. T: +52 442 248 1544 / 248 3133

Australia

Ansell Limited T: +61 1800 337 041 F: +61 1800 803 578

UK

Ansell Nitritex T: +44 1638 663338 F: +44 1638 668890







Ansell, $^{\circledR}$ and $^{\intercal}$ are trademarks owned by Ansell Limited or one of its affiliates. US Patented and US and non-US Patents Pending: www.ansell.com/patentmarking $^{\circledR}$ 2024 Ansell Limited. All Rights Reserved.

