

55-302
Non-clean/Non-sterile Neoprene RABS/Isolator Gloves

Neoprene RABS/isolator gloves, engineered for medium-duty environments with aggressive chemicals

Port size: 203mm/8"
Thickness: 0.51mm/20 mil

- Specialized protection: These chemicalresistant gloves satisfy EN ISO 374:2016 standards, for personal protection against most acids, alcohols, oils, and lubricants
- Assured dexterity: With medium-level thickness, they deliver better dexterity and greater usability as a result
- Reduced contamination risks:
 AlphaTec® Neoprene Isolator Gloves
 55-302 are unlined, lowering chemical absorption potential and related contamination risks
- Enhanced durability: AlphaTec®
 Neoprene Isolator Gloves 55-302 are EN 388:2016-certified for enhanced abrasion resistance

KEY FEATURES & BENEFITS

- **Strong material:** For neoprene gloves with high chemical resistance
- Medium thickness: Better dexterity, for easier parts handling
- Unlined: Reduced contamination risks and more effective cleaning







55-302

Non-clean/Non-sterile Neoprene RABS/Isolator Gloves

TECHNICAL DATA SHEET

Product Reference	55-302
Material	Neoprene Polymer
Color	Black
Shape	Ambidextrous
External Glove Surface	Smooth
Cuff Style	Beaded
Storage Instructions	Store in a dry and dark environment, temperature of 5°C to 22°C. Retain in original packaging when not in use.
Available Sizes	10
Temperature Range	From -30°C to 50°C
Cleanroom Class	Non-Critical Environment
Shelf Life	Five (5) years from date of manufacture.
Tested For Use With Chemotherapy Drugs	No
Antistatic	No
Standards	CE 0493, EN 388:2016, EN ISO 21420:2020, EN ISO 374-1:2016 Type A (KLMNPT), EN ISO 374-5:2016, Category III, UKCA





55-302Non-clean/Non-sterile Neoprene RABS/Isolator Gloves

PHYSICAL PROPERTIES

	Typical Values	Testing Method
Typical Length (mm/in)	813 / 32	EN 455-2
Port Size	203mm/8"	
Target Single Wall Palm Thickness (mm/mil)	0.51 / 20	EN 455-2
Target Single Wall Cuff Thickness (mm/mil)	0.51 / 20	EN 455-2

PROTECTION AGAINST MECHANICAL RISKS, EN 388:2016+A1:2018

Risk	Performance level
Abrasion Resistance	Level 2
Blade Cut Resistance	Level 1
Tear Resistance	Level O
Puncture Resistance	Level O
ISO 13997 Cut Resistance	Level A

ORDERING INFORMATION

	PORT SIZE	8"/203mm
	SIZE	10
55-302	REORDER NO.	55302100

For additional information visit us at www.ansell.com, or call us at

Europe, Middle East & Africa Region

Ansell Healthcare Europe NV T: +32 (0) 2 528 74 00 F: +32 (0) 2 528 74 01

Asia Pacific Region

Ansell Global Trading Center T: +603 8310 6688 F: +603 8310 6699

North America Region

Ansell Healthcare Products LLC US T: +1800 800 0444 US F: +1800 800 0445 CA T: +1-800-363-8340

Latin America & Caribbean Region

Ansell Commercial Mexico S.A. de C.V. T: +52 442 248 1544 / 248 3133

Australia

Ansell Limited T: +61 1800 337 041 F: +61 1800 803 578

UK

Ansell Nitritex T: +44 1638 663338 F: +44 1638 668890 Performance Standards and Regulatory Compliance











Ansell, @ and $^{\text{M}}$ are trademarks owned by Ansell Limited or one of its affiliates. US Patented and US and non-US Patents Pending: www.ansell.com/patentmarking @ 2025 Ansell Limited. All Rights Reserved.

Neither this document nor any other statement made herein by or on behalf of Ansell should be construed as a warranty of merchantability or that any Ansell product is fit for a particular purpose. Ansell assumes no responsibility for the suitability or adequacy of an end user's selection of gloves for a specific application.

