

# 55-105 Non-clean/Non-sterile Latex (NRL) RABS/Isolator Gloves

## NRL RABS/isolator gloves, with certified tear and abrasion resistance

Port size: 203mm/8"

Thickness: 0.76mm/30 mil

 Sustained protection: AlphaTec® NRL RABS and Isolator Gloves 55-105 satisfy EN388:2016 standards for Level 2 tear and abrasion resistance

- Improved durability: Heavyweight thickness means they boast enhanced durability, for longer-lasting wear
- Limited contamination risks: These RABS gloves are susceptible to fewer contamination risks and easy to keep clean, thanks to their unlined and translucent design

#### **KEY FEATURES & BENEFITS**

- EN388:2016 compliance: For tear- and abrasion-resistant safety gloves
- Heavyweight thickness: Enhanced durability, for longer glove life
- **Unlined:** Fewer contamination risks and easier cleaning







### 55-105

Non-clean/Non-sterile Latex (NRL) RABS/Isolator Gloves

#### **TECHNICAL DATA SHEET**

| Product Reference      | 55-105  |
|------------------------|---|
| Material               | Natural Rubber Latex  |
| Color                  | Natural   |
| Shape                  | Ambidextrous  |
| External Glove Surface | Smooth  |
| Cuff Style             | Beaded  |
| Storage Instructions   | Store in a dry and dark environment, temperature of 5°C to 22°C. Retain in original packaging when not in use.    |
| Available Sizes        | 10  |
| Temperature Range      | From -30°C to 50°C  |
| Shelf Life             | Three (3) years from date of manufacture.   |
| Standards              | CE 0493, EN ISO 21420:2020, EN ISO 374-1:2016 Type A (KLMNPT), EN ISO 374-5:2016, EN 388:2016, Category III, UKCA |





## 55-105 Non-clean/Non-sterile Latex (NRL) RABS/Isolator Gloves

#### **PHYSICAL PROPERTIES**

|   | Typical Values | Testing Method |
|---|----------------|----------------|
| Typical Length<br>(mm/in)                     | 813 / 32       | EN 455-2       |
| Port Size                                     | 203mm/8"       |                |
|   |                |                |
|   |                |                |
| Target Single Wall Palm<br>Thickness (mm/mil) | 0.76 / 30      | EN 455-2       |
| Target Single Wall Cuff<br>Thickness (mm/mil) | 0.76 / 30      | EN 455-2       |

#### PROTECTION AGAINST MECHANICAL RISKS, EN 388:2016+A1:2018

| Risk                     | Performance level |
|--------------------------|-------------------|
| Abrasion Resistance      | Level 2           |
| Blade Cut Resistance     | Level 1           |
| Tear Resistance          | Level 2           |
| Puncture Resistance      | Level 1           |
| ISO 13997 Cut Resistance | Level A           |

#### **ORDERING INFORMATION**

|        | PORT SIZE   | 8"/203mm |
|--------|-------------|----------|
|        | SIZE        | 10       |
| 55-105 | REORDER NO. | 55105100 |

#### For additional information visit us at www.ansell.com, or call us at

Europe, Middle East & Africa Region

Ansell Healthcare Europe NV T: +32 (0) 2 528 74 00 F: +32 (0) 2 528 74 01

#### Asia Pacific Region

Ansell Global Trading Center T: +603 8310 6688 F: +603 8310 6699

#### North America Region

Ansell Healthcare Products LLC US T: +1 800 800 0444 US F: +1 800 800 0445 CA T: +1-800-363-8340

#### Latin America & Caribbean Region

Ansell Commercial Mexico S.A. de C.V. T: +52 442 248 1544 / 248 3133

#### Australia

Ansell Limited T: +61 1800 337 041 F: +61 1800 803 578

#### UK

Ansell Nitritex T: +44 1638 663338 F: +44 1638 668890

### Performance Standards and Regulatory Compliance











Ansell, ® and ™ are trademarks owned by Ansell Limited or one of its affiliates. US Patented and US and non-US Patents Pending: www.ansell.com/patentmarking © 2025 Ansell Limited. All Rights Reserved.

Neither this document nor any other statement made herein by or on behalf of Ansell should be construed as a warranty of merchantability or that any Ansell product is fit for a particular purpose. Ansell assumes no responsibility for the suitability or adequacy of an end user's selection of gloves for a specific application.

